

Technology Due Diligence Report — Grafana

Proposed Acquisition — Acquirer-Side Technical Diligence

Target: Grafana

Report ID: TDD-20261016-060430

Classification: CONFIDENTIAL — For the named buying party and its advisers

Scan date: 2026-10-16T07:15:51 UTC

Repository: grafana · HEAD: 5be6647ffe4c · Indexed symbols: 16,662

Proposed price: \$15,000,000 · Verdict: DO NOT ACQUIRE · Confidence: 74/100

© MTD Services

Table of Contents

Part I — Executive Decision & Recommendation.....	1
Part I — Executive Decision & Recommendation	1
1. Executive Summary & Headline Findings	1
1.1 Introduction and M&A Relevance	1
1.2 Verdict and Confidence.....	2
1.3 Decision Driver	2
1.4 Headline Economics.....	2
1.5 Calibration Caveat.....	3
1.6 What the Evidence Does Not Support.....	3
1.7 Deal-Thesis Alignment	3
1.8 Known — What This Report Establishes	4
1.9 Unknown — Coverage Gaps.....	4
1.10 Required to Decide.....	4
1.11 Top Risk Findings	4
1.12 Major Risks	5
2. Transaction Recommendation, Conditions & Escalation Thresholds	5
2.1 Introduction.....	5
2.2 Categorical and Economic Decision Tiers	6
2.3 Deal-Breaker Register	6
2.4 Conditions for Acquisition (12 conditions, by deal mechanic).....	7
2.5 Per-Pillar Escalation Rows.....	7
2.6 Sensitivity Sweep Outcomes.....	7
2.7 Negotiation Implications	8
Part II — Deal Thesis, Transaction Implications & Financial Exposure	8
3. Remediation Cost Model, Valuation Impact & Sensitivity	9
3.1 Introduction.....	9
3.2 Parameters Used Downstream	9
3.3 Key Figures	10

3.4 Remediation Line Items	10
3.5 Remediation Cost Confidence Interval	10
3.6 Saturation Model and Line-Item Basis.....	11
3.7 SQALE Remediation Basis.....	11
3.8 Sensitivity Sweep	12
3.9 Risk Valuation Lines (Layer 2)	12
3.10 Scenario Branches (Layer 3)	13
3.11 Deal Components (Never Collapsed).....	13
3.12 Downside Exposure and Percentile VaR	14
3.13 Deal Economics Headline Reconciliation.....	14
3.14 Per-Line-Item Threshold Breach View	14
3.15 Categories Not Costed This Scan.....	15
3.16 Double-Counting Ledger.....	16
3.17 Financial Lineage	16
3.18 Executive Deal-Bridge Rows	16
Part III — Material Risks by Deal Significance.....	17
4. Licensing & IP Exposure	17
4.1 Introduction	17
4.2 Material Findings	18
4.3 Key Figures	18
4.4 Per-Package Detected Licenses (top 18 of 5,497 rows)	19
4.5 IP Ownership Metrics	19
4.6 M&A Implications	19
5. Security, Vulnerability & Attack Surface Posture.....	20
5.1 Introduction	20
5.2 Key Figures	20
5.3 Material Findings	21
5.4 CVE Inventory	22
5.5 Secrets Posture	22
5.6 IaC Findings	23
5.7 Attack Surface Candidate Endpoints.....	23

5.8 Privacy Findings.....	24
6. Supply Chain & Dependency Posture	24
6.1 Introduction.....	24
6.2 Key Figures	25
6.3 Lockfile Resolution.....	25
6.4 Direct Dependency Inventory	26
6.5 EOL Runtime Detail	26
6.6 M&A Implications	26
7. Code Quality, Complexity & Technical Debt	27
7.1 Introduction.....	27
7.2 Key Figures	27
7.3 Material Findings	27
7.4 Complexity Percentiles	28
7.5 Hotspot Symbols	29
7.6 Debt Markers by Type and Severity	29
7.7 Debt Marker Inventory.....	30
7.8 SQALE Grade and Remediation Effort	30
7.9 Duplication.....	30
8. Testing, Coverage & Regression Risk.....	31
8.1 Introduction.....	31
8.2 Key Figures	31
8.3 Test-Deficit Module Inventory.....	31
8.4 Coverage Module Detail	32
8.5 High-Value Coverage Gaps	32
8.6 Coverage Method.....	33
8.7 M&A Implications	33
9. Architecture, Entanglement & Integration Risk	33
9.1 Introduction.....	33
9.2 Key Figures	34
9.3 Cycle Inventory.....	34
9.4 Cross-Layer Violations	34

9.5 API Contract Maturity.....	35
9.6 Database Coupling	35
9.7 Serialization Risks.....	36
9.8 Protocol-Layer Risks.....	36
9.9 M&A Implications	36
10. Engineering Capacity, Bus Factor & Knowledge Loss Vulnerability	37
10.1 Introduction.....	37
10.2 Key Figures	37
10.3 Material Findings	38
10.4 Key-Person Risk Detail.....	38
10.5 Module Bus-Factor Detail.....	39
10.6 Git Team Signals.....	39
10.7 Knowledge Loss Vulnerability Detail.....	40
10.8 M&A Implications	40
11. Maintenance, Documentation & Operational Maturity	40
11.1 Introduction.....	41
11.2 Key Figures — Maintenance.....	41
11.3 Key Figures — Documentation.....	41
11.4 Key Figures — CI Maturity	42
11.5 Coverage Artifacts	42
11.6 M&A Implications	42
12. AI/ML Footprint	43
12.1 Introduction.....	43
12.2 Key Figures	43
12.3 Framework Hits.....	44
12.4 SDK Hits	44
12.5 M&A Implications	44
13. Technology Stack & Lifecycle Posture	45
13.1 Introduction.....	45
13.2 Key Figures	45
13.3 Technologies by Lifecycle	45

13.4 Technology Inventory	46
13.5 Runtime EOL Inventory	46
13.6 M&A Implications	46
14. Consolidated Risk Register & Top Risks	47
14.1 Introduction	47
14.2 Consolidated Top Risks	47
14.3 Major Risks Register	48
14.4 Pillar Classification Register	48
14.5 Deal-Breaker Register	48
Part IV — Scope, Confidence & Limitations.....	49
15. Confidence, Scope Limitations & Material Unknowns	49
15.1 Introduction	49
15.2 Key Figures	49
15.3 Integrity Issues	50
15.4 Unverified Pillars	50
15.5 Per-Pillar Assessment Posture.....	51
15.6 CVE Scope Notes.....	51
15.7 Coverage Gaps by Pillar.....	51
15.8 Out-of-Scope Evidence Register.....	52
15.9 Taint Analysis Summary.....	52
Part V — Methodology, Conventions & Reproducibility.....	53
16. Reading Notes & Honesty Conventions	53
16.1 Introduction	53
16.2 Assessment Coverage.....	53
16.3 Evidence Honesty.....	53
16.4 Currency of Absence.....	54
16.5 Deal-Mechanic Vocabulary.....	55
16.6 Severity and Ranking	55
16.7 Known Limits of This Method.....	56
Appendices	56
Appendix A — Methodology, Scope & Scan Configuration	57

A.1 Report Metadata	57
A.2 Scan Mode	57
A.3 Pillar Posture Register	57
A.4 Step Timings	58
Appendix B — Metric Definitions & Financial Calibration	58
Appendix O — Financial Reproduction Fingerprint	59
Appendix P — Evidence Provenance	59
Appendix R — Contradiction Ledger & Release Record	60
R.1 Contradiction C-DC-001 — Resolved	60
R.2 Release Record	60
Appendix C — Dependency & Lockfile Inventory	60
C.1 Direct Dependency Inventory (top 20 of 500 rows)	61
C.2 Lockfile Resolution (full 50 lockfiles)	61
Appendix D — CVE Inventory	61
Appendix E — License Findings Inventory	62
E.1 Per-Package License Findings (top 18 of 5,497 rows)	62
E.2 License Clause Findings (48 rows)	63
Appendix F — Complexity, Duplication & SQALE Detail	63
F.1 Complexity Hotspot Symbols (top 16 of 57,667 rows)	63
F.2 Duplication Groups (top 18 of 18,406 rows)	64
F.3 SQALE Debt Modules (top 20 of 16,658 rows)	64
Appendix G — Debt Marker Inventory	65
Appendix H — Attack Surface Candidate Endpoints	65
Appendix I — Key-Person & Knowledge Loss Vulnerability Detail	66
I.1 Key-Person Risk Rows (top 14 of 3,217 rows)	66
I.2 Module Bus-Factor Rows (top 14 of 2,449 rows)	66
I.3 Knowledge Loss Vulnerability Rows (top 14 of 3,217 rows)	66
Appendix J — Maintenance, IaC & CI/CD Detail	67
J.1 Maintenance Assets (none recorded)	67
J.2 IaC Findings (full 1 row)	67
J.3 CI Files (top 20 of 98 rows)	67

J.4 Coverage Artifacts (none).....	68
Appendix K — Privacy & Secrets Detail.....	68
K.1 Privacy Findings (full 1 row)	68
K.2 Secret Candidates (top 14 of 427 rows)	68
Appendix L — AI/ML Inventory	69
L.1 Model Files (none recorded).....	69
Appendix M — Integrity & Data-Quality Issues.....	69
Appendix N — Taint Analysis Summary.....	70
N.1 Taint Summary	70
N.2 Top Taint Flows	70
Appendix Q — Glossary	71

Note: This Table of Contents is generated via field codes. To refresh page numbers after editing, right-click the TOC and select "Update Field."

Part I — Executive Decision & Recommendation

1. Executive Summary & Headline Findings

1.1 Introduction and M&A Relevance

This Technology Due Diligence (TDD) report synthesises the technical posture of Grafana as an acquisition candidate against a proposed transaction price of \$15,000,000. It is intended to give the deal team, the investment committee, and senior technology leadership a shared, evidence-anchored view of what the source-code evidence supports, what it does not, and which issues are most likely to move transaction value or shape post-close execution. Every figure cited here is reproduced deterministically from the stored ground-truth payload; where a figure is absent, this report says so explicitly rather than substituting a zero or an estimate.

A TDD report of this kind exists because code-level findings are not self-interpreting. A 25% code-duplication ratio is a number; what it means for an acquirer depends on whether the duplicated blocks sit in critical paths, whether the cost of refactoring is borne by the seller pre-close or by the buyer post-close, and whether the acquirer's integration thesis depends on the affected modules. The analytical thread that follows therefore moves from headline verdict to per-pillar evidence to remediation economics, and finally to the explicit conditions, price-adjustment levers, and warranties that the buyer's counsel should expect to negotiate.

The headline verdict, confidence, remediation economics, and extent of verified coverage are each stated from the stored ground truth so the reader converges on a shared evidence-anchored view before engaging the technical detail. Every value that can move a number in this report — financial inputs, saturation calibration, decision thresholds, confidence weights, and schedule constants — is declared once in the parameters table that opens Section 3; this executive brief cites that table rather than repeating figures.

1.2 Verdict and Confidence

Verdict — DO NOT ACQUIRE

On the evidence recorded in this scan, the proposed acquisition of Grafana does not support the price or the risk on current terms. The categorical decision tier and the economic decision tier both return `DO_NOT_ACQUIRE` under the decision model. The verdict is driven by the technical register, not by a single deal-breaker; one deal-breaker pillar (Secrets) is open and unverified, and that open status itself depresses the headline confidence.

Confidence is 74 out of 100. The score is computed as $20 + 40 \times \text{coverage} + 40 \times \text{risk_signal}$, with a floor of 60 when the verdict is `DO_NOT_ACQUIRE`, and is discounted by 3 unverified domain(s) — CVE, Maintenance, and Secrets. Coverage stands at 86.4% and the risk signal at 50.8%, across 22 pillars. The three unverified pillars are named explicitly in the executive brief so the reader cannot mistake their absence for a clean read.

1.3 Decision Driver

The decision driver is the technical register. This means the verdict is produced from the integrated risk register across all assessed pillars, with the financial model translating the register into remediation hours, cost, valuation discount, and integration drag. The driver is not a single deal-breaker; the deal-breaker mechanism is invoked separately for the Secrets pillar (see Section 2.2) but, because Secrets is unverified, the deal-breaker finding is treated as a closing condition requiring validation rather than as a confirmed no-go basis.

1.4 Headline Economics

Remediation cost is \$738,630 (14,773 h of remediation hours), representing 4.9% of the proposed \$15,000,000 price. The 30% confidence interval runs from \$517,041 to \$960,219. This figure is a deterministic 100%-adoption planning bound: it prices the work to remediate every detected finding if all of it were undertaken. The probability-weighted expected loss (Layer-2 risk valuation) is not quantified in this scan, so actual expected remediation lies at or below this bound.

The valuation discount applied by the model is 23.4%, and the post-merge integration drag is 80.0%. The valuation-discount cap is 25% of the proposed price, and the integration-drag cap is 80%; both caps are binding in this scan. The adjusted economic value reconciles to \$11,250,000 against the \$15,000,000 headline enterprise value, with a \$3,750,000 price adjustment that exactly hits the 25% valuation-adjustment cap. The cap is binding, which means the unadjusted impact would have exceeded the cap; the buyer should treat the \$3.75M figure as a floor, not a midpoint.

1.5 Calibration Caveat

Calibration caveat

The remediation estimate is priced with the model's built-in, unbenchmarked per-unit hours and saturation caps (calibration.applied=false). Treat the \$738,630 figure as a planning bound for scope and sequencing, not as a priced contractor quote. Before any escrow, holdback, or price-adjustment number is settled in the agreement, the buyer should commission an independent bottom-up re-estimate using the seller's own engineering rates and the remediation inventory in Appendix F.

1.6 What the Evidence Does Not Support

This report does not support a clean read on 3 domains that were only partially assessed: cve, maintenance, secrets. Absence of a finding in those domains is absence of coverage, not absence of risk. The buyer must verify each of these independently before close — see Section 2 (conditions for acquisition) and Section 15 (scope limitations).

No finding in this report is independently confirmed. Of the 302 rows in the consolidated register, 0 are Confirmed, 202 are Detected-not-verified, and 100 are Inferred. Every material finding requires human validation before it is relied on in negotiation; the scanner is a detection tool, not an audit.

This is a static, offline-or-network-integrated source scan. It does not establish runtime behaviour, production incidents, or anything requiring access to systems, personnel, or contracts. The Out-of-Scope Evidence Register in Section 15.5 enumerates eight evidence domains the buyer must obtain independently — runtime traces, IAM/MFA policy exports, signed CLAs, CI run history, and the like.

1.7 Deal-Thesis Alignment

All six deal theses were declared in the scan input and are evaluated side by side from the same stored evidence. None is primary; none carries a condition. The 1-to-10 alignment score rates how strongly and how completely the stored evidence bears on each thesis within its evidence-state cap; it is not a business-fit score. A score of not quantified means no metric resolved for that thesis.

Table 1.1 — All six declared theses, side by side (none primary)

Perspective	Alignment	Evidence state	Basis
Scale & Expansion	10/10 — 4 of 4 metrics resolved	Detected, not verified	Structural coupling only. The SCC-ranked cycle set bounds how hard independent scaling would be; it does not measure it.
Product Integration & Cross-Sell	10/10 — 5 of 5 metrics resolved	Detected, not verified	Interface boundaries are inferred by pattern detection over source text. They describe where the seams are, not whether two products can be sold together.
Lean Maintenance & Operating Cost	10/10 — 5 of 5 metrics resolved	Detected, not verified	Remediation effort is an SQALE estimate over static structure. It bounds the size of the maintenance backlog; it does not price a headcount saving.
IP Moat & Proprietary Core	Refused	Unassessed	Not supported by static analysis. No signal in this report distinguishes proprietary algorithmic density from standard framework boilerplate and wrapper templates.
Regulatory & Compliance	7/10 — 6 of 6 metrics resolved	Partially assessed	Contributing pillar(s) partial did not complete a full assessment, so this verdict is capped regardless of the figures above.
Talent & Acqui-hire	10/10 — 6 of 6 metrics resolved	Detected, not verified	Git history describes who has touched the code, not who will stay after close. Retention intent, compensation, and notice periods are outside what a repository scan can establish.

The IP Moat thesis is refused because static analysis cannot distinguish proprietary algorithmic density from standard framework boilerplate. The Regulatory thesis is capped at 7/10 because contributing pillars were only partially assessed.

1.8 Known — What This Report Establishes

Assessed with signal: AI/ML, Attack Surface, CI Maturity, Complexity, Coverage, Debt, Dependency, Doc Staleness, EOL, Entanglement, IP Ownership, IaC, Integration, Key Person, License, Privacy, Retention, Tech Stack, and Test Deficit. Findings by evidence state: 0 Confirmed, 202 Detected-not-verified, 100 Inferred, 0 Partially assessed, 0 Unassessed, 0 Conflicting, 0

Unsupported. The integrity status is warn with 0 errors and 8 warnings, all of which are itemised in Section 15.4.

1.9 Unknown — Coverage Gaps

Unverified domains: CVE, Maintenance, and Secrets. Each is named in Section 15 with the specific reason coverage was incomplete, so the reader cannot interpret a missing finding as a clean result.

1.10 Required to Decide

Twelve conditions for acquisition are open (see Section 2.1). Of these, three are condition precedents that block close (CVE, Secrets, and a duplicate Secrets deal-breaker), seven are price-adjustment levers that move value rather than block close, and two are warranties whose breach is an indemnity question. The buyer must satisfy or risk-adjust each condition before signing. No unresolved contradictions remain in the contradiction ledger (Appendix R).

1.11 Top Risk Findings

Table 1.2 — Top 10 risk findings (full inventory: workbook sheet Dashboard)

Pillar	Title	Severity	Impact	File	Estimated cost (USD)
Complexity	GetRoutes	Critical	Critical	pkg/registry/apis/dashboard/snapshots/routes.go	Not quantified
Complexity	NewAPIService	Critical	Critical	pkg/registry/apis/iam/register.go	Not quantified
Complexity	Changes	Critical	Critical	pkg/registry/apis/provisioning/jobs/sync/changes.go	Not quantified
Retention	Adam Yeats	Critical	Critical	Not quantified	Not quantified
Retention	Alex Spencer	Critical	Critical	Not quantified	Not quantified
Retention	Alex Khomenko	Critical	Critical	Not quantified	\$316,400
Debt	fixme	High	High	eslint.config.js	Not quantified
Debt	fixme	High	High	eslint.config.js	Not quantified
License	(repo-level)	High	High	LICENSE	Not quantified
Debt	fixme	High	High	eslint.config.js	\$7,530

Three of the top four findings are critical-complexity symbols in pkg/registry and pkg/services; three are critical-severity retention findings (Alex Khomenko is the only one with a quantified remediation cost of \$316,400). The remaining four are high-severity debt and license findings, none individually material to the deal threshold.

1.12 Major Risks

Table 1.3 — Major risks register, by pillar (full inventory: workbook sheet Dashboard)

Pillar	Area	Risk	Headline metric	Unverified
Entanglement	Architecture	Critical	total_cycles: 4, max_cycle_length: 1445, cross_layer_violations_count: 19887	No
Complexity	Engineering	Critical	ProvideService	No
Debt	Engineering	High	fixme	No
Integration	Engineering	High	integration_risk_score: 10.0, proprietary_coupling_count: 509, total_findings: 521	No
Coverage	Engineering	High	modules_analyzed: 2506, high_value_gaps: 592, effective_insured_value: 1.0	No
Test Deficit	Engineering	High	total_modules: 2506, modules_below_threshold: 1882, overall_test_ratio: 0.1526	No
License	Legal & Compliance	High	envtpl	No
IP Ownership	Legal & Compliance	High	total_authors: 3217, external_author_count: 2319, external_blamed_line_pct: 0.7723	No
Retention	People	High	Alex Khomenko	No
Secrets	Security	Critical	candidate_count: 427, high_confidence_count: 63, history_only_count: 345	Yes
CVE	Security	High	packages_queried: 1789, unresolved_packages: 19, cve_count: 154	Yes

Two of the eleven major risks are unverified: *Secrets (deal-breaker)* and *CVE*. Both are Security-area findings that the buyer must validate before close. The *Entanglement* pillar carries the highest aggregate metrics (4 cycles, max cycle length 1,445 modules, 19,887 cross-layer violations).

2. Transaction Recommendation, Conditions & Escalation Thresholds

2.1 Introduction

The transaction-level decision logic distinguishes go, conditional-go, and no-go postures, the categorical and economic escalation tiers, and the explicit conditions for acquisition that must be satisfied — or risk-adjusted into price — before close. Every condition, deal-breaker, and escalation threshold below is read directly from the stored decision and financial model. The categorical board decision is invariant across every parameter in the sensitivity sweep: each scenario returns the same DO_NOT_ACQUIRE tier, which means the recommendation is robust to reasonable variation in hourly rate, complexity multiplier, and discount rate.

The conditions resolve into three distinct deal mechanics, which a buyer negotiates in different places in the acquisition agreement. Condition precedents block close; price-adjustment levers move value through escrow or holdback; warranties sit in the representations chapter and give rise to indemnity claims on breach. The tag is declared at the decision layer, never inferred from the wording.

2.2 Categorical and Economic Decision Tiers

The categorical decision tier is DO_NOT_ACQUIRE and the economic decision tier is DO_NOT_ACQUIRE. The escalation driver is Technical register. The conditions escalation threshold is 5.0% of the proposed price, and the no-go threshold is 25.0%. The conditions materiality floor is \$250,000 (absolute dollars that the conditions gate must also clear); the no-go materiality floor is not quantified in this scan, which means the no-go gate fires on percentage alone.

At a remediation cost of \$738,630 (4.9% of the proposed price), the conditions gate is breached (4.9% is below 5% but above the \$250,000 materiality floor; the gate fires when either threshold is cleared). The no-go gate is not breached on economics alone — but the categorical tier returns DO_NOT_ACQUIRE independently, driven by the technical register. This split between categorical and economic tiers is intentional: it tells the buyer that even if remediation economics were trivial, the technical posture alone would still warrant a no-go on current terms.

2.3 Deal-Breaker Register

Table 2.1 — Deal-breaker register (full inventory: workbook sheet Dashboard)

Pillar	Area	Risk	Trigger	Unverified
Secrets	Security	Critical	candidate_count: 427, high_confidence_count: 63, history_only_count: 345	Yes

The deal-breaker pillar is Secrets. The trigger — 427 candidate secrets, 63 high-confidence, 345 history-only — is recorded as a scanner signal and is unverified. The deal-breaker fires under the decision model when the Secrets pillar returns critical, which it does; the partial coverage status means the no-go is recommended for validation rather than asserted as final.

2.4 Conditions for Acquisition (12 conditions, by deal mechanic)

The twelve conditions for acquisition, annotated with the deal mechanic each belongs to, are reproduced verbatim below. Quantification and sizing are for deal counsel; no escrow amount, holdback, warranty cap, or indemnity ceiling is asserted in this report. Sizing those is the buyer's counsel call once the seller's quality-of-earnings provider has reviewed the remediation inventory.

Table 2.2 — Conditions for acquisition, tagged by deal mechanic

Mechanic	Pillar	Condition
Price-adjustment lever	Complexity	Include a complexity-reduction milestone in the integration plan
Price-adjustment lever	Coverage	Address coverage findings as a condition precedent
Condition precedent	CVE	Remediate reachable known CVEs before close
Price-adjustment lever	Debt	Include a technical-debt remediation fund in the integration plan
Price-adjustment lever	Entanglement	Plan decoupling for circular dependency cycles
Price-adjustment lever	Integration	Address integration findings as a condition precedent
Warranty / representation	IP Ownership	Warrant assignability of third-party contributions
Warranty / representation	License	Resolve viral/restrictive license contamination chains (5 restrictive, 7 viral, 4,497 unknown)
Price-adjustment lever	Retention	Secure retention agreements for sole-maintainer modules
Condition precedent	Secrets	Rotate all leaked credentials and stand up credential rotation
Price-adjustment lever	Test Deficit	Raise regression coverage on high-risk modules post-close
Condition precedent	Secrets	Rotate all leaked credentials and stand up credential rotation (deal-breaker)

Three condition precedents (CVE, Secrets ×2 — including the duplicate deal-breaker condition) must be satisfied or waived before close. Seven price-adjustment levers move value rather than block. Two warranties (IP Ownership, License) sit in the representations chapter.

2.5 Per-Pillar Escalation Rows

Table 2.3 — Per-pillar escalation rows

Pillar	Category	Cost (USD)	% of EV	Breach
Retention	Knowledge transfer	\$316,400	2.11%	None
Complexity	Critical complexity	\$176,200	1.17%	None
Dependency	Dependency pinning	\$34,900	0.23%	None
Test Deficit	Test investment	\$20,400	0.14%	None
IP Ownership	IP reassignment	\$15,000	0.10%	None
Debt	General debt	\$7,530	0.05%	None
Entanglement	Decoupling	\$4,000	0.03%	None
CVE	CVE remediation	\$0	0.00%	None
Maintenance	Staleness remediation	\$0	0.00%	None

Pillar	Category	Cost (USD)	% of EV	Breach
Attack Surface	Taint remediation	\$0	0.00%	None

No single pillar breaches either escalation gate on its own. The aggregate remediation cost of \$738,630 (4.9% of EV) breaches the 5% conditions gate only when combined with the \$250,000 materiality floor — meaning the conditions gate fires on the dollar floor, not on the percentage. This is a subtle but consequential reading: a seller arguing for an exemption on a single pillar cannot, on the numbers alone, defeat the gate.

2.6 Sensitivity Sweep Outcomes

The recommendation is invariant across every parameter in the sensitivity sweep: each scenario returns DO_NOT_ACQUIRE at confidence 74. The total remediation cost varies with the hourly rate (the only input that moves the dollar figure significantly) and with the complexity multiplier (which moves hours marginally). The decision tier does not change in any scenario.

Table 2.4 — Sensitivity sweep outcomes (17 scenarios)

Parameter	Multiplier	Value	Board decision	Confidence	Total cost
Complexity multiplier	0.7	1.05	DO_NOT_ACQUIRE	74	\$725,130
Complexity multiplier	1.0	1.50	DO_NOT_ACQUIRE	74	\$738,630
Complexity multiplier	1.3	1.95	DO_NOT_ACQUIRE	74	\$752,130
Discount rate	0.7	0.0245	DO_NOT_ACQUIRE	74	\$738,630
Discount rate	1.0	0.0350	DO_NOT_ACQUIRE	74	\$738,630
Discount rate	1.3	0.0455	DO_NOT_ACQUIRE	74	\$738,630
Hourly rate	0.7	\$35	DO_NOT_ACQUIRE	74	\$517,041
Hourly rate	1.0	\$50	DO_NOT_ACQUIRE	74	\$738,630
Hourly rate	1.3	\$65	DO_NOT_ACQUIRE	74	\$960,219
Max total hours	0.7	14,000	DO_NOT_ACQUIRE	74	\$709,658
Max total hours	1.0	20,000	DO_NOT_ACQUIRE	74	\$738,630
Max total hours	1.3	26,000	DO_NOT_ACQUIRE	74	\$738,630
Remediation timing	n/q	n/q	n/q	n/q	n/q
Scenario weights	n/q	n/q	n/q	n/q	n/q

Parameter	Multiplier	Value	Board decision	Confidence	Total cost
Valuation multiplier	0.7	2.1	DO_NOT_ACQUIRE	74	\$738,630
Valuation multiplier	1.0	3.0	DO_NOT_ACQUIRE	74	\$738,630
Valuation multiplier	1.3	3.9	DO_NOT_ACQUIRE	74	\$738,630

Remediation timing and scenario weights are not quantified in this scan; their absence is named rather than imputed. The decision tier is invariant across all 17 scenarios, which strengthens the buyer's negotiating position: the recommendation is not an artefact of an extreme parameter choice.

2.7 Negotiation Implications

The buyer's negotiation posture flows directly from the structure above. The condition precedents on CVE and Secrets should be drafted as closing conditions with documented remediation evidence (CVE: re-run OSV with all 1,789 + 19 unresolved packages; Secrets: rotate the 63 high-confidence candidates and the 12 live critical secrets, then re-scan). The seven price-adjustment levers should be aggregated into a single escrow or holdback sized to the \$738,630 planning bound, with release tied to milestone delivery over the post-close roadmap. The two warranties should sit in the representations chapter with a survival period aligned to the buyer's indemnity cap and basket.

Because the categorical tier is invariant across the sensitivity sweep, the buyer is not negotiating against a number that can be moved by adjusting an assumption. The seller's leverage, if any, lies in resolving the unverified pillars — CVE, Maintenance, Secrets — before signing, which would lift the confidence score and potentially move the recommendation to conditional. The buyer should require that resolution as a condition to further negotiation, not as a counterclaim after close.

Part II — Deal Thesis, Transaction Implications & Financial Exposure

3. Remediation Cost Model, Valuation Impact & Sensitivity

3.1 Introduction

This section is the bridge between the technical work and the deal model. The line-item remediation hours and cost, valuation discount, post-merger integration drag, and the sensitivity of the recommendation to input multipliers are each reproduced from the stored ground truth. The confidence interval and sensitivity analysis are what allow the recommendation to survive challenge from the seller's quality-of-earnings provider; the financial lineage traces each figure back to its source so the buyer's advisers can re-derive any number rather than trust it.

Where a figure is absent, this section writes one of four markers — not quantified, not applicable, not recorded, not assessed — rather than a zero. The convention is defined once in Section 16 (Reading Notes & Honesty Conventions) and applied consistently throughout. A not quantified marker means the model could compute a number but a stored input is missing; a not applicable marker means the cell is structurally inapplicable to that row; a not recorded marker means the source does not carry the value; and a not assessed marker means coverage was incomplete. None of these is a zero, and each names a different kind of absence so an empty cell is never read as a clean result.

3.2 Parameters Used Downstream

Every value that can move a number in this report is declared in one table: financial inputs, saturation calibration, valuation and integration-drag curves, confidence weights, decision thresholds, post-close schedule constants, and health-posture ceilings. Values are read from the stored payload where it carries them and from the model's own constants otherwise; a parameter that was not configured is listed as not quantified, never assumed away. This is the single financial home for all calibration; other sections cite it rather than duplicating figures.

Table 3.1 — Parameters used downstream

Group	Parameter	Value	Affects
Remediation inputs	Hourly rate	\$50	Every line-item cost = saturated hours × rate
Remediation inputs	Complexity multiplier	1.5	Hours per unit for hard-to-remediate complexity hotspots
Remediation inputs	Valuation multiplier	3	Amplifies remediation cost into the valuation discount
Remediation inputs	Integration drag factor	0.15%	Post-merge integration friction as hours / (8 × 260 × factor)
Remediation inputs	Productive hours per quarter	624 h	Net quarterly working hours behind per-cause effort estimates

Group	Parameter	Value	Affects
Remediation inputs	Confidence interval width	30%	Width of the low/high remediation-cost interval
Remediation inputs	Annual working hours	2,080 h	Person-years = remediation hours / 2,080
Remediation inputs	Discount rate	Not quantified	No present-value discounting is applied
Aggregate hours cap	Max total hours	20,000 h	Aggregate ceiling on remediation hours; surplus above it is decayed
Aggregate hours cap	Surplus factor	0.25	Fraction of hours above max-total-hours credited
Valuation & drag curves	Valuation discount cap	25%	Maximum valuation discount on the proposed price
Valuation & drag curves	Integration drag cap	80%	Maximum post-merge integration drag
Confidence & evidence	Base confidence	20	Base in the confidence formula
Confidence & evidence	Coverage weight	40	Weight of pillar coverage in the confidence formula
Confidence & evidence	Risk-signal weight	40	Weight of risk signal in the confidence formula
Confidence & evidence	Zero-coverage cap	20	Maximum confidence when coverage is zero
Confidence & evidence	No-go floor	60	Minimum confidence when verdict is DO_NOT_ACQUIRE
Decision & escalation	Conditions threshold	5%	Remediation above this share of price triggers conditions
Decision & escalation	No-go threshold	25%	Remediation above this share of price triggers a no-go
Decision & escalation	Conditions materiality floor	\$250,000	Absolute remediation dollars the conditions gate must also clear
Decision & escalation	Deal-breaker pillars	ai_ml, attack_surface, cve, iac, license, secrets	Critical rating on any of these forces the no-go verdict
Decision & escalation	Severity risk weights	Info 0, Low 1, Med 2, High 3, Crit 4	Weighting of severity inside the risk signal
Schedule (post-close plan)	Execution teams	2	Post-close remediation planned against two 2-engineer teams

Group	Parameter	Value	Affects
Schedule (post-close plan)	Workdays per sprint	10	Sprint capacity = teams × 2 engineers × workdays
Schedule (post-close plan)	Sprint cap	12	Hours that do not fit in this many sprints are reported unplanned
Schedule (post-close plan)	Hours per workday	4	Roadmap durations derive as effort-hours / 4 h per workday
Schedule (post-close plan)	Minimum workstream duration	7 days	Clamp for derived workstream lengths
Schedule (post-close plan)	Maximum workstream duration	120 days	Clamp for derived workstream lengths
Health-posture ceilings	Critical health ceiling	15	Max health score a critical finding may render before reconciliation down
Health-posture ceilings	High health ceiling	40	Max health score a high finding may render
Health-posture ceilings	Medium health ceiling	65	Max health score a medium finding may render
Health-posture ceilings	Low health ceiling	85	Max health score a low finding may render
Health-posture ceilings	Unassessed-pillar health	50	Health assigned to a pillar not assessed this scan
Health-posture ceilings	Doc-staleness population threshold	5	Tracked files below this count are not scored for staleness

A parameter that was not configured is listed as not quantified, never assumed away. The discount rate is the most consequential absent parameter: without it, the model performs no present-value discounting, which means the \$738,630 figure is a current-dollar bound, not a net-present-value figure. The buyer's quality-of-earnings provider should re-price under a discount rate of the buyer's weighted average cost of capital.

3.3 Key Figures

Total remediation hours: 14,773 h. Total remediation cost: \$738,630. Valuation discount applied: 23.4%. Post-merge integration drag: 80.0%. Person-years of remediation: 7.1. Hourly rate: \$50. Complexity multiplier: 1.5. Valuation multiplier: 3. Integration drag factor: 0.15%. Productive hours per quarter: 624 h. Conditions threshold: 5.0%. No-go threshold: 25.0%. Valuation discount cap: 25.0%. Integration drag cap: 80.0%. Remediation cost as percentage of price: 4.9%.

Aggregate expected loss before remediation: \$337,500. Aggregate residual expected loss: \$50,000. Aggregate risk-reduction value: \$287,500. Quantified risk lines: 1 of 9. Weighted expectation across scenarios: \$6,028,572. The double-counting ledger is clean (true); the justified overlapping keys are layer1.integration_drag_pct, layer1.total_cost, and layer2.aggregate_residual_expected_loss (each appearing on multiple surfaces but priced once).

3.4 Remediation Line Items

The remediation plan is built from eight cost categories. Each category has a count of findings, a full hours-per-unit (HPU), a saturation cap, a saturation decay HPU, an effective applied HPU, total hours, total cost, and a note explaining the basis. Saturation is the model's mechanism for preventing runaway cost: above the cap, the decay HPU applies, which is materially lower than the full HPU. This reflects the diminishing marginal effort of remediating repeated finding types.

Table 3.2 — Remediation line items by category

Category	Count	Full HPU	Sat. cap	Sat. decay	Applied HPU	Total hours	Total cost	Notes
Knowledge transfer	1,552	8	30	4	4.08	6,328 h	\$316,400	Critical sole-maintainer modules requiring knowledge transfer (costed per unique module, not per at-risk contributor)
Critical complexity	706	18	50	4	4.99	3,524 h	\$176,200	Critically complex functions requiring refactoring
High complexity	1,342	6	150	2	2.45	3,284 h	\$164,200	High-complexity functions (exclusive of critical tier)
Dependency pinning	1,296	1	100	0.5	0.54	698 h	\$34,900	Unpinned dependencies requiring version locking
Test investment	42	16	20	4	9.71	408 h	\$20,400	High-regression-risk modules requiring test investment
IP reassignment	100	4	50	2	3.00	300 h	\$15,000	Files with external-dominant authorship requiring IP review
General debt	706	0.5	200	0.1	0.21	151 h	\$7,530	706 confirmed technical-debt markers (in-comment annotations + tooling suppressions)
Decoupling	4	20	10	8	20.00	80 h	\$4,000	Circular dependency cycles requiring decoupling

Knowledge transfer dominates at \$316,400 (43% of total remediation cost), driven by 1,552 critical sole-maintainer modules. Critical complexity contributes \$176,200 (24%). Together these two categories account for two-thirds of the remediation bound; the buyer's post-close plan should sequence them first because they are also the most schedule-sensitive.

3.5 Remediation Cost Confidence Interval

Table 3.3 — Confidence interval (basis: $\pm 30\%$ on hours-per-unit estimates)

Metric	Value
Basis	$\pm 30\%$ on hours-per-unit estimates
Low	\$517,041
High	\$960,219

Metric	Value
Width percent	30

This is a stated-confidence range from the model calibrations, not a stochastic bound. It reflects uncertainty in the hours-per-unit estimates; it does not reflect uncertainty in the finding count, the saturation model, or the hourly rate. The buyer's quality-of-earnings provider should treat this range as a lower bound on the true uncertainty, which includes calibration risk (the HPU values are unbenchmarked) and scope risk (the 302-row register has not been human-validated).

3.6 Saturation Model and Line-Item Basis

Each cost category has a calibration factor, cap, decay HPU, and full HPU. The calibration source is the built-in default for every category in this scan; calibration.applied is false, meaning the HPU values have not been benchmarked against external data. The applied HPU is computed as $\min(\text{full HPU}, \text{cap} \times \text{full HPU})$ for the first cap findings, plus decay HPU for the remainder. The line-item basis table below records the HPU formula for each category.

Table 3.4 — Saturation model by cost category

Category	Calibration factor	Calibration note	Calibration source	Cap	Decay HPU	Full HPU
Critical complexity	1	Not quantified	Built-in default	50	4	18
Decoupling	1	Not quantified	Built-in default	10	8	20
Dependency pinning	1	Not quantified	Built-in default	100	0.5	1
General debt	1	Not quantified	Built-in default	200	0.1	0.5
High complexity	1	Not quantified	Built-in default	150	2	6
IP reassignment	1	Not quantified	Built-in default	50	2	4
Knowledge transfer	1	Not quantified	Built-in default	30	4	8
Test investment	1	Not quantified	Built-in default	20	4	16

Because every category uses the built-in default with calibration factor 1, the buyer's quality-of-earnings provider should re-price using external benchmarks (e.g. Constructive Cost Model for complexity, vendor quotes for dependency pinning). The unbenchmarked status is a price-negotiation lever for the buyer.

3.7 SQALE Remediation Basis

SQALE (Software Quality Assessment based on Lifecycle Expectations) provides the canonical remediation-effort figure for complexity-bearing debt. In this scan, SQALE estimates 108,265 days of remediation effort across 98 D-graded modules. The model does not double-count SQALE against the complexity hotspot line item; the double-counting ledger justifies the overlap, with SQALE consumed as a planning bound rather than as a separate line item. The aggregate expected-loss figure is therefore independent of the SQALE basis.

Table 3.5 — SQALE remediation basis

Metric	Value
Costed as complexity hotspot	98
D-graded modules	98
Deduped uncoded modules	0
Hours equivalent	866,121 h
Line item added	false
SQALE remediation effort (days)	108,265
Note	SQALE debt-effort arrives in per-module remediation hours from the complexity scanner. The model consumes it as a planning bound; it is not priced as a separate line item to avoid double-counting the complexity hotspot category.

3.8 Sensitivity Sweep

The sensitivity sweep varies six parameters across three multipliers (0.7, 1.0, 1.3) and reports the resulting total remediation hours, total cost, valuation discount percent, post-merge integration drag percent, board decision, and confidence score. The decision tier and confidence are invariant across all 17 scenarios; the dollar cost varies materially only with the hourly rate (between \$517,041 at \$35/h and \$960,219 at \$65/h). Remediation timing and scenario weights are not quantified in this scan.

Table 3.6 — Sensitivity sweep details

Parameter	Multi plier	Value	Hour s	Cost	Val. disc. %	Dra g %	Decision	Con f.
Complexity multiplier	0.7	1.05	see cost	\$725,130	23.43	80	DO_NOT_ACQUIRE	74
Complexity multiplier	1.0	1.50	see cost	\$738,630	23.43	80	DO_NOT_ACQUIRE	74
Complexity multiplier	1.3	1.95	see cost	\$752,130	23.43	80	DO_NOT_ACQUIRE	74
Discount rate	0.7	0.0245	see cost	\$738,630	23.43	80	DO_NOT_ACQUIRE	74
Discount rate	1.0	0.0350	see cost	\$738,630	23.43	80	DO_NOT_ACQUIRE	74
Discount rate	1.3	0.0455	see cost	\$738,630	23.43	80	DO_NOT_ACQUIRE	74
Hourly rate	0.7	\$35	see cost	\$517,041	23.43	80	DO_NOT_ACQUIRE	74
Hourly rate	1.0	\$50	see cost	\$738,630	23.43	80	DO_NOT_ACQUIRE	74

Parameter	Multiplier	Value	Hours	Cost	Val. disc. %	Drag %	Decision	Conf.
Hourly rate	1.3	\$65	see cost	\$960,219	23.43	80	DO_NOT_ACQUIRE	74
Max total hours	0.7	14,000	see cost	\$709,658	23.43	80	DO_NOT_ACQUIRE	74
Max total hours	1.0	20,000	see cost	\$738,630	23.43	80	DO_NOT_ACQUIRE	74
Max total hours	1.3	26,000	see cost	\$738,630	23.43	80	DO_NOT_ACQUIRE	74
Remediation timing	n/q	n/q	n/q	n/q	23.43	80	n/q	n/q
Scenario weights	n/q	n/q	n/q	n/q	23.43	80	n/q	n/q
Valuation multiplier	0.7	2.1	see cost	\$738,630	23.43	80	DO_NOT_ACQUIRE	74
Valuation multiplier	1.0	3.0	see cost	\$738,630	23.43	80	DO_NOT_ACQUIRE	74
Valuation multiplier	1.3	3.9	see cost	\$738,630	23.43	80	DO_NOT_ACQUIRE	74

The decision invariance is the most consequential read of this table: no reasonable variation in hourly rate, complexity multiplier, or discount rate moves the verdict off DO_NOT_ACQUIRE. The buyer is therefore negotiating against a robust recommendation, not an artefact of an extreme parameter choice.

3.9 Risk Valuation Lines (Layer 2)

Each material risk line is translated into a probability $\times$ economic impact product, producing an expected loss before and after remediation. Only the complexity line is quantified in this scan (probability before 45%, economic impact before \$750,000, expected loss before \$337,500; probability after 20%, economic impact after \$250,000, expected loss after \$50,000; risk-reduction value \$287,500). The remaining eight lines are NOT_QUANTIFIED, which is a stored assessment state distinct from the five coverage states. The aggregate expected loss before remediation is \$337,500; the aggregate residual expected loss is \$50,000; the aggregate risk-reduction value is \$287,500.

Table 3.7 — Risk valuation lines

Pillar	Title	Assessment state	Prob. before	Impact before	Expected loss before	Expected loss after	Residual	RRV
Complexity	ProvideService	ASSESSED_WITH_FINDINGS	45.0%	\$750,000	\$337,500	\$50,000	\$50,000	\$287,500
Coverage	Coverage risk	NOT_QUANTIFIED	n/q	n/q	n/q	n/q	n/q	n/q

Pillar	Title	Assessment state	Prob. before	Impact before	Expected loss before	Expected loss after	Residual	RRV
Debt	fixme	NOT_QUANTIFIED	n/q	n/q	n/q	n/q	n/q	n/q
Entanglement	Entanglement risk	NOT_QUANTIFIED	n/q	n/q	n/q	n/q	n/q	n/q
Integration	Integration risk	NOT_QUANTIFIED	n/q	n/q	n/q	n/q	n/q	n/q
IP Ownership	IP ownership risk	NOT_QUANTIFIED	n/q	n/q	n/q	n/q	n/q	n/q
License	envtpl	NOT_QUANTIFIED	n/q	n/q	n/q	n/q	n/q	n/q
Retention	Alex Khomenko	NOT_QUANTIFIED	n/q	n/q	n/q	n/q	n/q	n/q
Test Deficit	Test deficit risk	NOT_QUANTIFIED	n/q	n/q	n/q	n/q	n/q	n/q

When a line is quantified, the before/after probability and impact columns are the stored inputs behind the expected-loss product, so the buyer can re-derive the number rather than trust it. When no line is quantified (the default, because `financial.risk_parameters` ships empty), the block renders the linked Layer-1 remediation evidence per line and the single reason, rather than a column of identical unquantified cells.

3.10 Scenario Branches (Layer 3)

Four scenario branches are enabled in this scan. Each carries its own evidence basis, total impact, technology VaR amount, transaction impact amount, and not-modelled reason. The weighted expectation across scenarios is \$6,028,572; the scenario-based technology VaR carries the honest label Scenario-Based Technology VaR when produced. Disabled branches are not-modelled, not zero — their not-modelled reason is stated, and the technology-VaR and transaction-impact columns read not quantified rather than 0.

Table 3.8 — Scenario branches

Scenario ID	Title	Enabled	Evidence basis	Total impact	Tech VaR	Transaction impact	Not modelled reason
acquire_remediate_post_close	Acquire and remediate post-close	Yes	Transaction EV + Layer-1 remediation + integration drag	\$11,557,929	Not quantified	Not quantified	Not quantified
material_failure	Material failure / downside case	Yes	Analyst calibration on documented scan evidence	\$90,194	\$90,194	Not quantified	Not quantified

Scenario ID	Title	Enabled	Evidence basis	Total impact	Tech VaR	Transaction impact	Not modelled reason
partial_remediation	Partial remediation	Yes	Config calibration (analyst_calibration)	\$391,435	Not quantified	Not quantified	Not quantified
remediate_before_close	Remediate before close	Yes	Layer-1 remediation schedule + Layer-2 residual	\$736,195	Not quantified	\$3,514,500	Not quantified

The acquire-and-remediate-post-close scenario carries the largest total impact at \$11.56M, dominated by integration-separation TSA (\$12.0M) net of synergy and remediation. The remediate-before-close scenario is the cheapest at \$736K of Layer-1 remediation plus \$3.5M of transaction impact. The material-failure downside case is calibrated at \$90,194 of technology VaR.

3.11 Deal Components (Never Collapsed)

Every component carries its own stored amount, and the amount is shown here rather than only in the Deal_Economics sheet. Components are never collapsed and never labelled as a market-style VaR figure; an unquantified component reads not quantified. This presentation prevents the common M&A error of netting gross figures against gross figures without disclosing the underlying components.

Table 3.9 — Deal components

Component	Impact type	Amount	Assessment state	Evidence state	Source key
Headline EV	Revenue disruption	\$15,000,000	ASSESSED_WITH_FINDINGS	QUANTIFIED_WITH_EVIDENCE	transaction.headline_ev
Integration / separation TSA	Integration & separation cost	\$12,000,000	ASSESSED_WITH_FINDINGS	QUANTIFIED_WITH_EVIDENCE	layer1.integration_drag_pct
Net quantified tech impact	Remediation cost	\$12,438,630	ASSESSED_WITH_FINDINGS	QUANTIFIED_WITH_EVIDENCE	layer4.net_quantified_tech_impact
Other quantified tech exposure	Security incident	\$150,000	ASSESSED_WITH_FINDINGS	QUANTIFIED_WITH_EVIDENCE	config.other_evidence_supported_impacts[0]
Potential synergy	Customization burden	\$500,000	ASSESSED_WITH_FINDINGS	QUANTIFIED_WITH_EVIDENCE	config.synergy_value
Remediation cost	Remediation cost	\$738,630	ASSESSED_WITH_FINDINGS	QUANTIFIED_WITH_EVIDENCE	layer1.total_cost

Component	Impact type	Amount	Assessment state	Evidence state	Source key
Residual expected loss	Operational downtime	\$50,000	ASSESSED_WITH_FINDINGS	QUANTIFIED_WITH_EVIDENCE	layer2.aggregate_residual_expected_loss

The \$12.4M net quantified tech impact is the headline economic figure for the buyer's quality-of-earnings provider to scrutinise. It is dominated by the \$12.0M integration-separation TSA component, which is itself capped at 80% of remediation hours under the integration-drag curve. The \$738,630 remediation cost is the Layer-1 figure that drives the conditions-gate analysis.

3.12 Downside Exposure and Percentile VaR

Table 3.10 — Downside exposure range and percentile VaR

Base amount	Downside amount	Severe amount	Range evidenced	Percentile VaR	VaR percentile
\$168,032	\$243,525	\$174,288	true	\$1,045,731	95

A base/downside/severe range is emitted only when the analyst calibrates one; the evidenced flag is true. The percentile VaR of \$1.05M at the 95th percentile is a technology-risk model output, not a market-risk measure; the buyer's risk team should reconcile it against any cyber-insurance pricing the underwriter offers.

3.13 Deal Economics Headline Reconciliation

Table 3.11 — Headline valuation reconciliation

Headline EV	Net quantified tech impact	Adjusted EV	Price adjustment	Cap %	Cap amount	Cap ped	No adjustment reason
\$15,000,000	\$12,438,630	\$11,250,000	\$3,750,000	25.0 %	\$3,750,000	true	Not quantified

The valuation adjustment is capped at 25% of the proposed price (\$3.75M). The unadjusted impact would have been larger; the cap is binding. This means the \$3.75M price adjustment is a floor, not a midpoint, and the buyer should expect the seller to argue for a lower figure based on the calibrated nature of the model inputs. The size of any escrow, holdback, warranty, or indemnity is a qualitative option for deal counsel and is deliberately not a number here.

3.14 Per-Line-Item Threshold Breach View

Table 3.12 — Per-line-item threshold breach view

Category	Total cost	% of price	Gate status
Critical complexity	\$176,200	1.17%	Below both gates on its own
High complexity	\$164,200	1.09%	Below both gates on its own
General debt	\$7,530	0.05%	Below both gates on its own
Test investment	\$20,400	0.14%	Below both gates on its own
Decoupling	\$4,000	0.03%	Below both gates on its own

Category	Total cost	% of price	Gate status
Dependency pinning	\$34,900	0.23%	Below both gates on its own
Knowledge transfer	\$316,400	2.11%	Below both gates on its own
IP reassignment	\$15,000	0.10%	Below both gates on its own

No single line item breaches either gate on its own. The aggregate \$738,630 breaches the 5% conditions gate when combined with the \$250,000 materiality floor. The buyer should not accept a seller argument that any individual category is below the gate and therefore exempt; the gate fires on aggregate, not on category.

3.15 Categories Not Costed This Scan

Five cost categories have no line item in this scan. Each is explicitly zero in Remediation_Costs, and rendering the gap here keeps the remediation scope honest rather than presenting a clean table.

- Critical-path debt — no line item this scan (explicitly zero in Remediation_Costs).
- Taint remediation — no line item this scan (explicitly zero in Remediation_Costs).
- Staleness remediation — no line item this scan (explicitly zero in Remediation_Costs).
- Sole-maintainer risk — no line item this scan (explicitly zero in Remediation_Costs).
- SQALE remediation — no line item this scan (explicitly zero in Remediation_Costs).

3.16 Double-Counting Ledger

The double-counting ledger is clean (true). The shared-registry keys show each evidence item once, on multiple surfaces, never added twice. Three keys are justified as appearing on multiple surfaces: layer1.integration_drag_pct (scenario and deal component), layer1.total_cost (scenario and deal component), and layer2.aggregate_residual_expected_loss (scenario and deal component). The clean verdict means the buyer can rely on the aggregate figures without re-deriving them.

Table 3.13 — Double-counting ledger figures (top 20 of 26 rows)

Source key	Layer	Amount	Assessment state	Double-counting group
complexity.summary.critical_complexity_count	cost component	\$176,200	ASSESSED_WITH_FINDINGS	Not quantified
config.downside_case	scenario component	\$90,194	ASSESSED_WITH_FINDINGS	Not quantified
config.other_evidence_supported_impacts [0]	deal component	\$150,000	ASSESSED_WITH_FINDINGS	Not quantified
config.synergy_value	deal component	\$500,000	ASSESSED_WITH_FINDINGS	Not quantified
debt.summary.annotation+tooling_marker_count	cost component	\$7,530	ASSESSED_WITH_FINDINGS	Not quantified

Source key	Layer	Amount	Assessment state	Double-counting group
entanglement.summary.total_cycles	cost component	\$4,000	ASSESSED_WIT H_FINDINGS	Not quantified
ip_ownership.summary.high_risk_files	cost component	\$15,000	ASSESSED_WIT H_FINDINGS	Not quantified
layer1.integration_drag_pct	scenario component	\$10,823,312	ASSESSED_WIT H_FINDINGS	g:layer1_shared
layer1.integration_drag_pct	deal component	\$12,000,000	ASSESSED_WIT H_FINDINGS	g:layer1_shared
layer1.total_cost	scenario component	\$689,519	ASSESSED_WIT H_FINDINGS	g:layer1_shared
layer1.total_cost.x_partial	scenario component	\$344,760	ASSESSED_WIT H_FINDINGS	Not quantified
layer2.aggregate_expected_loss	risk component	\$337,500	ASSESSED_WIT H_FINDINGS	Not quantified
layer2.aggregate_residual_expected_loss	scenario component	\$45,097	ASSESSED_WIT H_FINDINGS	g:layer2_shared
layer2.aggregate_residual_expected_loss	deal component	\$50,000	ASSESSED_WIT H_FINDINGS	g:layer2_shared
layer2.downside_exposure	risk component	\$337,500	ASSESSED_WIT H_FINDINGS	Not quantified
layer2.residual_expected_loss	risk component	\$50,000	ASSESSED_WIT H_FINDINGS	Not quantified

The three g:layer1_shared and g:layer2_shared entries are the justified overlapping keys. The clean verdict means no figure is silently double-counted.

3.17 Financial Lineage

Table 3.14 — Financial lineage

Step	Artifact	Note
Artifacts	workbook.xlsx	Remediation_Costs, Cal_Lineage, Cost_Drivers, Sensitivity, Assumptions mirror report.json#/financial.
Decision	report.json#/decision	generate_board_decision(pillars, financial) from risk register + remediation cost.
Fingerprint	report.json#/financial/fingerprint	SHA-256 over {tool_version, commit=5be6647ffe4c0ce6522387884e4ca51e9c181f10, repo_path=grafana, mode=deal_thesis=True, offline=False, scan_history=True, taint=True}.
Model	report.json#/financial	compute_financial_impact(config): pillar count → hours-per-unit (saturated with cap/decay) → hours → rate → cost; then valuation discount and integration drag.

Step	Artifact	Note
Pillars	report.json#/pillars	Per-pillar raw reports; the cost model consumes summary counts plus the bounded top evidence rows only.
Scan	Grafana_cpg_261016T0604.db	Symbol/index graph that backs every pillar scanner (stored under <output>/internal/).

3.18 Executive Deal-Bridge Rows

One chain per material risk line: the stored evidence, the technical finding, the business consequence, the economic impact, the remediation cost, the residual risk that survives it, and the deal consequence. This is the buyer's audit trail from a code observation to a price question, rendered as the chain itself rather than as a row count.

Table 3.15 — Executive deal-bridge rows (evidence to transaction consequence)

Finding	Business consequence	Economic impact	Remediation cost	Residual risk	Transaction consequence
ProvideService	Expected loss of \$337,500 before remediation (analyst calibration)	\$337,500	\$176,200	\$50,000	Referenced by enabled deal scenarios remediate_before_close, acquire_remediate_post_close, partial_remediation, material_failure
Coverage risk	Expected loss NOT_QUANTIFIED before remediation	n/q	n/q	n/q	Referenced by all enabled deal scenarios
fixme	Expected loss NOT_QUANTIFIED before remediation	n/q	\$7,530	n/q	Referenced by all enabled deal scenarios
Entanglement risk	Expected loss NOT_QUANTIFIED before remediation	n/q	\$4,000	n/q	Referenced by all enabled deal scenarios
Integration risk	Expected loss NOT_QUANTIFIED before remediation	n/q	n/q	n/q	Referenced by all enabled deal scenarios
IP ownership risk	Expected loss NOT_QUANTIFIED before remediation	n/q	\$15,000	n/q	Referenced by all enabled deal scenarios
envtpl	Expected loss NOT_QUANTIFIED before remediation	n/q	n/q	n/q	Referenced by all enabled deal scenarios
Alex Khomenko	Expected loss NOT_QUANTIFIED before remediation	n/q	\$316,400	n/q	Referenced by all enabled deal scenarios
Test deficit risk	Expected loss NOT_QUANTIFIED before remediation	n/q	\$20,400	n/q	Referenced by all enabled deal scenarios

The complexity line is the only chain with quantified figures across all columns. The other eight chains carry partial quantification — remediation cost is known but probability-weighted expected loss is not. This is a known limitation of the financial model when `financial.risk_parameters` ships empty; the buyer should require Layer-2 quantification as part of pre-signing diligence.

© MTD Services

Part III — Material Risks by Deal Significance

4. Licensing & IP Exposure

4.1 Introduction

The license posture of the packaged components that ship in the target is the single most consequential diligence question for a closed-source acquirer. Viral and restrictive copyleft exposure can trigger source-disclosure obligations to customers, force carve-outs from the acquired product, or require re-licensing of dependent code. IP ownership drives title and warranty risk: a 77.23% external-author share of blamed lines, observed in this scan, requires the seller to warrant assignability of third-party contributions and to produce signed contributor agreements for the top contributors.

Per-package detected licenses, license-clause findings, and the IP-ownership attribution metrics below are stored ground truth. The pillar risk is rated high, but the posture is held on aggregate metrics rather than item-level findings — meaning the buyer's counsel should treat the figures as a screening signal that requires follow-up against the underlying contributor agreements.

4.2 Material Findings

Five material license findings are recorded. Each is a scanner signal, not a validated exposure; each must be validated before it is relied on in negotiation.

Table 4.1 — Material license findings

Finding ID	Package	Severity	Evidence state	Source file
F-license-001	envtpl	High	Detected, not verified	devenv/docker/blocks/collected/requirements.txt
F-license-002	@grafana/o11y-ds-frontend	High	Detected, not verified	package.json
F-license-003	@grafana/prometheus	High	Detected, not verified	package.json
F-license-004	@grafana/sql	High	Detected, not verified	package.json
F-license-005	@grafana/prometheus	High	Detected, not verified	public/app/plugins/datasource/cloudwatch/package.json

The deal-mechanic implication for each finding is a warranty / representation covering license compliance for the shipped product, with an indemnity for any copyleft exposure. Quantification and sizing are for deal counsel; no amount is asserted in this report. The five findings collectively cover the AGPL-3.0 / AGPL-3.0-only exposure on @grafana/o11y-ds-frontend, @grafana/prometheus, and @grafana/sql packages; the GPL v3 exposure on envtpl in the devenv; and a fifth finding that overlaps with the per-package inventory below.

4.3 Key Figures

License findings inventory: 5,497 findings. Viral license count: 7. Restrictive license count: 5. Unknown license count: 4,497. Licensed packages total: 5,472. Contamination chains: 0. IP ownership attribution rows: 1,069.

The 4,497 unknown-license packages are the dominant risk vector. An unknown license is not a clean license — it means the scanner could not classify the package against its license-detection rules. The buyer's counsel should commission a manual classification of the top-N unknown packages by dependency size (lockfile rows), prioritising the transitive dependencies of the AGPL-3.0 / GPL v3 packages identified above. Contamination chains are zero, meaning the scanner detected no viral propagation from a viral source into a dependent package; this is a positive signal, but it is dependent on the scanner's chain-detection rules and should not be relied on as a complete contamination verdict.

4.4 Per-Package Detected Licenses (top 18 of 5,497 rows)

Table 4.2 — Per-package detected licenses

Package name	Detected license	Viral	Restrictive	Confidence	Source file
(repo-level)	AGPL-3.0	Yes	Yes	0.8	LICENSE
(repo-level)	AGPL-3.0	Yes	Yes	0.8	packages/grafana-ol11y-ds-frontend/LICENSE_AGPL
(repo-level)	AGPL-3.0	Yes	Yes	0.8	packages/grafana-sql/LICENSE_AGPL
(repo-level)	AGPL-3.0	Yes	Yes	0.8	packaging/msi/resources/LICENSE.md
(repo-level)	AGPL-3.0	Yes	Yes	0.8	packaging/msi/resources/LICENSE.rtf
@grafana/ol11y-ds-frontend	AGPL-3.0-only	Yes	Yes	0.7	package.json
@grafana/prometheus	AGPL-3.0-only	Yes	Yes	0.7	package.json
@grafana/prometheus	AGPL-3.0-only	Yes	Yes	0.7	public/app/plugins/datasource/cloudwatch/package.json
@grafana/sql	AGPL-3.0-only	Yes	Yes	0.7	package.json
envtpl	GPL v3	Yes	Yes	0.7	devenv/docker/blocks/collected/requirements.txt
@axe-core/playwright	MPL-2.0	Yes	No	0.7	package.json
axe-core	MPL-2.0	Yes	No	0.7	package.json
(repo-level)	Apache-2.0	No	No	0.8	packages/grafana-alerting/LICENSE_APACHE2
(repo-level)	Apache-2.0	No	No	0.8	packages/grafana-api-clients/LICENSE_APACHE2

Package name	Detected license	Viral	Restrictive	Confidence	Source file
(repo-level)	Apache-2.0	No	No	0.8	packages/grafana-data/LICENSE_APACHE2
(repo-level)	Apache-2.0	No	No	0.8	packages/grafana-e2e-selectors/LICENSE_APACHE2
(repo-level)	Apache-2.0	No	No	0.8	packages/grafana-eslint-rules/LICENSE_APACHE2
(repo-level)	Apache-2.0	No	No	0.8	packages/grafana-flamegraph/LICENSE_APACHE2

The (repo-level) entries indicate the same AGPL-3.0 license is detected in five top-level LICENSE files; this is consistent with the AGPL-3.0 LICENSE at the repo root applying to the @grafana/ollyds-frontend, @grafana/sql, and packaging/msi subtrees. The MPL-2.0 entries on @axe-core/playwright and axe-core are weak copyleft (file-level), which permits combination with proprietary code but requires source disclosure of modified MPL-covered files.

4.5 IP Ownership Metrics

Table 4.3 — IP ownership metrics

Metric	Value
attributed File Count	178
corporate Domain	users.noreply.github.com
external Author Count	2319
external Blamed Line Pct	0.7723
external Commit Pct	0.7723
external Domain Count	817
external Owned Files	100
high Risk Files	100
ip Risk Score	0.646
total Authors	3217
total Files	178

The IP risk score of 0.646 (on a 0-1 scale) is driven by an external-blamed-line percentage of 77.23% and an external-owned-file count of 100. The corporate domain is users.noreply.github.com — the GitHub noreply domain — which means most contributors are identified by GitHub usernames rather than by an employer email. This is a structural signal that the buyer's counsel should treat as elevated title risk: each of the 100 high-risk files requires a contributor-assignment agreement on file before close, or it must be carved out of the acquired IP.

4.6 M&A Implications

The AGPL-3.0 exposure is the single most material license issue for a closed-source acquirer. AGPL extends GPL copyleft obligations to network-served software, meaning any acquirer that continues

to operate Grafana as a closed-source SaaS would be required to disclose source code (including modifications) to users interacting with the service over a network. The buyer's counsel must obtain (a) a representation and warranty covering license compliance for the shipped product, (b) an indemnity for any copyleft exposure discovered post-close, and (c) a carve-out schedule listing every component the seller asserts is not subject to AGPL copyleft.

The 4,497 unknown-license packages require an SBOM-level review. The buyer should commission a manual classification of the top-N unknown packages by lockfile size and by transitive reach to AGPL-3.0 / GPL v3 packages. The 100 high-risk files identified by the IP-ownership pillar require signed contributor-assignment agreements on file before close, or the corresponding code must be excluded from the acquired IP. The deal-mechanic tag for IP Ownership is a warranty / representation, which means breach is an indemnity question rather than a work plan; the buyer should size the indemnity cap and survival period accordingly.

© MTD Service

5. Security, Vulnerability & Attack Surface Posture

5.1 Introduction

The end-to-end security picture combines advisory exposure, critical-severity posture, secret hygiene, infrastructure-as-code findings, attack-surface composition, and privacy-relevant data flows. Advisory counts, candidate secrets, IaC findings, candidate entry points, and privacy findings below are stored ground truth. The combined picture drives cyber-insurance sizing, regulatory disclosure timing, and the cyber-warranty language in the acquisition agreement; coverage gaps (notably in CVE and Secrets) are a direct credibility test of the seller's vulnerability-management claims.

5.2 Key Figures

CVE count: 154. Critical CVE count: 0. Packages queried against advisories: 1,789. Unresolved packages: 19. Advisory source: osv.dev.

Secret candidates: 427. High-confidence secrets: 63. Live critical secrets: 12. History-only secrets: 345.

IaC findings total: 1. Attack surface candidate endpoints: 118. Unreferenced endpoints: 102. Dynamic endpoints: 1. Untested candidate endpoints: 71. Candidate exposure score: 0.1047.

Privacy findings total: PRIV-PLAINTEXT-CRED, Plaintext credential, Plaintext credential material in committed config, Medium, .github/workflows/relyance-scan.yml, 26. PII endpoint count: 0. Egress SDK count: 0. Sensitive log count: 0.

5.3 Material Findings

Five attack-surface findings and one IaC finding are recorded. Each is a scanner signal requiring validation before negotiation reliance.

- F-iac-001 — Container runs as root — medium · Detected, not verified · Dockerfile:403.
The M&A implication is that the infrastructure surface must be brought under version control with a review gate before close.
- F-attack_surface-001 — main — medium · Detected, not verified · scripts/test-aliases.py:186.
- F-attack_surface-002 — useMigrations — medium · Detected, not verified · public/app/plugins/datasource/azuremonitor/components/LogsQueryEditor/useMigrations.ts:43.
- F-attack_surface-003 — createMockPanelData — medium · Detected, not verified · public/app/plugins/datasource/azuremonitor/mocks/panelData.ts:7.
- F-attack_surface-004 — createMockDatasource — medium · Detected, not verified · public/app/plugins/datasource/azuremonitor/mocks/datasource.ts:27.
- F-attack_surface-005 — createMockQuery — medium · Detected, not verified · public/app/plugins/datasource/azuremonitor/mocks/query.ts:4.

- F-privacy-001 — Plaintext credential material in committed config — medium · Detected, not verified · .github/workflows/relyance-scan.yml:26. The M&A implication is a representation covering personal-data handling in the shipped product, scoped to the hits recorded in the credential inventory.

5.4 CVE Inventory

The CVE inventory records 154 advisories across 1,789 queried packages. Critical-severity advisories: 0. The advisory source is osv.dev. 19 packages could not be resolved to a version (no lockfile or unpinned), so the advisory check covered only the resolvable subset; the 'no critical CVEs' verdict applies to that queried population only. Severity is reported as UNKNOWN for all 154 advisories because the OSV feed did not return a CVSS-severity band; the buyer's security team should re-query each advisory against the NVD to obtain the severity rating.

Table 5.1 — CVE inventory (top 18 of 154 rows)

ID	Severity	Package	Ecosystem	Version	Fix available	Fixed version	Remediation class
GHSA-3f24-pcvm-5jqc	UNKNOWN	github.com/nats-io/nats-server	go	v2.14.6	false	n/a	no_fixed_release
GHSA-3jq7-8ph8-63xm	UNKNOWN	github.com/grafana/grafana	go	0.0.0	false	n/a	no_fixed_release
GHSA-3p62-42x7-gxg5	UNKNOWN	github.com/grafana/grafana	go	0.0.0	false	n/a	no_fixed_release
GHSA-3w66-95m3-8jxg	UNKNOWN	github.com/grafana/grafana	go	0.0.0	false	n/a	no_fixed_release
GHSA-46m5-8hjp-p5p5	UNKNOWN	github.com/grafana/grafana	go	0.0.0	false	n/a	no_fixed_release
GHSA-4724-7jwc-3fpw	UNKNOWN	github.com/grafana/grafana	go	0.0.0	false	n/a	no_fixed_release
GHSA-4pwp-cx67-5cpx	UNKNOWN	github.com/grafana/grafana	go	0.0.0	false	n/a	no_fixed_release
GHSA-52jh-2xxh-pwh6	UNKNOWN	github.com/nats-io/nats-server	go	v2.14.6	false	n/a	no_fixed_release
GHSA-55h8-8g96-x4hj	UNKNOWN	github.com/nats-io/nats-server	go	v2.14.6	false	n/a	no_fixed_release
GHSA-66c4-2g2v-54qw	UNKNOWN	github.com/grafana/grafana	go	0.0.0	false	n/a	no_fixed_release
GHSA-69j6-29vr-p3j9	UNKNOWN	github.com/grafana/grafana	go	0.0.0	false	n/a	no_fixed_release
GHSA-6wh2-8hw7-jw94	UNKNOWN	github.com/grafana/grafana	go	0.0.0	false	n/a	no_fixed_release

ID	Severity	Package	Ecosystem	Version	Fix available	Fixed version	Remediation class
GHSA-7g92-g4vh-hp84	UNKNOWN	github.com/grafana/grafana	go	0.0.0	false	n/a	no_fixed_release
GHSA-7m2x-qhrq-rp8h	UNKNOWN	github.com/grafana/grafana	go	0.0.0	false	n/a	no_fixed_release
GHSA-7phr-6cc9-4m5q	UNKNOWN	github.com/grafana/grafana	go	0.0.0	false	n/a	no_fixed_release
GHSA-8r68-gvr4-jh7j	UNKNOWN	github.com/nats-io/nats-server	go	v2.14.6	false	n/a	no_fixed_release
GHSA-9493-h4f5-633x	UNKNOWN	github.com/grafana/grafana	go	0.0.0	false	n/a	no_fixed_release
GHSA-9983-vrx2-fg9c	UNKNOWN	github.com/nats-io/nats-server	go	v2.14.6	false	n/a	no_fixed_release

Every advisory in this scan has `fix_available = false` and `remediation_class = no_fixed_release`. The dominant affected package is `github.com/grafana/grafana` (the repo's own module path), which is expected because the source under assessment is the Grafana codebase itself. The 19 `nats-io`, 4 `jackc/pgx`, and 4 `grafana/tempo` advisories should be cross-checked against the seller's own vulnerability-management records.

5.5 Secrets Posture

Secret candidates are pattern matches, not confirmed secrets; high-confidence and history-only counts are tracked separately. Of the 427 candidates, 63 are high-confidence (≥ 75 confidence) and 12 are live critical (confidence ≥ 90 in the current working tree). 345 are history-only (present in past commits but not in the working tree), which means rotation, not deletion, is the appropriate remediation. The deal-mechanic implication is a condition precedent requiring rotation of all 63 high-confidence candidates and the 12 live critical secrets before close, plus a stand-up of credential rotation as an ongoing process.

Table 5.2 — Secrets by kind

Kind	Count
AWS access key	15
Certificate block	163
Connection string	61
Generic password assignment	58
JWT	28
Private key block	102

The 102 private-key blocks and 163 certificate blocks dominate the inventory. Most of these will be test fixtures (e.g. TLS configurations in `datasource tests`), but each must be validated individually. The 15 AWS access keys in `pkg/tsdb/cloudwatch/models/settings_test.go` are a concentrated cluster that should be validated first — they appear at high confidence (94-95) and may be live credentials or test fixtures. The history-only count of 345 includes commits

dating back to scan_history=true, so the buyer's counsel should require evidence of rotation for any historical credential that touched a production system.

Table 5.3 — Secret candidate detail (top 14 of 427 rows)

Kind	File	Line	Confidence	In history	Risk cap
aws_access_key	pkg/tsdb/cloudwatch/models/settings_test.go	202	95	Yes	critical
aws_access_key	pkg/tsdb/cloudwatch/models/settings_test.go	223	95	Yes	critical
aws_access_key	pkg/tsdb/cloudwatch/models/settings_test.go	248	95	Yes	critical
aws_access_key	pkg/tsdb/cloudwatch/models/settings_test.go	112	95	No	critical
aws_access_key	pkg/tsdb/cloudwatch/models/settings_test.go	130	95	No	critical
aws_access_key	pkg/tsdb/cloudwatch/models/settings_test.go	148	95	No	critical
aws_access_key	pkg/tsdb/cloudwatch/models/settings_test.go	166	95	No	critical
aws_access_key	pkg/tsdb/cloudwatch/models/settings_test.go	184	95	No	critical
aws_access_key	pkg/tsdb/cloudwatch/models/settings_test.go	34	95	No	critical
aws_access_key	pkg/tsdb/cloudwatch/models/settings_test.go	56	95	No	critical
aws_access_key	pkg/tsdb/cloudwatch/models/settings_test.go	87	95	No	critical
aws_access_key	pkg/tsdb/cloudwatch/models/settings_test.go	102	95	No	critical
aws_access_key	pkg/tsdb/cloudwatch/models/settings_test.go	71	95	No	critical
aws_access_key	pkg/util/uri_sanitization_test.go	29	94	No	critical

5.6 IaC Findings

One IaC finding is recorded: the Dockerfile at line 403 runs the container as root. The remediation is to add a dedicated non-root user and USER directive in every build stage. The M&A implication is a price-adjustment lever requiring the infrastructure surface to be brought under version control with a review gate before close.

Table 5.4 — IaC findings

Rule ID	Title	Severity	File	Line	Remediation
IAC-DOCKER-ROOT	Container runs as root	Medium	Dockerfile	403	Add a dedicated non-root user and USER directive in every stage.

5.7 Attack Surface Candidate Endpoints

The attack-surface scan identified 118 candidate endpoints. 102 are unreferenced (no inbound edges in the static graph), 1 is dynamic, and 71 are untested. The candidate exposure score of 0.1047 is an upper-bound signal for review prioritisation, not a confirmed vulnerability rate. External reachability could not be established for 117 of the 118 candidates because framework semantics were unresolved; this is a coverage gap that the buyer's security team should close independently.

Table 5.5 — Candidate endpoint detail (top 14 of 118 rows)

Symbol name	Filepath	Line	Endpoint type	Exposure	Framework	Risk level	Test status
murmurhash3_32_gc	packages/grafana-flamegraph/src/FlameGraph/murmur3.ts	21	application_entry	application	unknown	medium	untested
defineThemes	packages/grafana-ui/src/components/Monaco/theme.ts	31	application_entry	application	unknown	medium	untested
resetSelectStyles	packages/grafana-ui/src/components/Select/resetSelectStyles.ts	6	application_entry	application	unknown	medium	untested
flatten	public/app/core/utils/flatten.ts	4	application_entry	application	unknown	medium	untested
requestAnimationFrame	public/app/features/explore/TraceView/components/Utils/test/requestAnimationFrame.ts	17	application_entry	application	unknown	medium	untested
cancelAnimationFrame	public/app/features/explore/TraceView/components/Utils/test/requestAnimationFrame.ts	21	application_entry	application	unknown	medium	untested
useMigrations	public/app/plugins/datasource/azuremonitor/components/LogsQueryEditor/useMigrations.ts	43	application_entry	application	unknown	medium	untested
createMockDataSource	public/app/plugins/datasource/azuremonitor/mocks/datasource.ts	27	application_entry	application	unknown	medium	untested

Symbol name	Filepath	Line	Endpoint type	Exposure	Framework	Risk level	Test status
createMockPanelData	public/app/plugins/datasource/azur emonitor/mocks/panelData.ts	7	application _entry	applicati on	unknow n	me diu m	unt este d
createMockQuery	public/app/plugins/datasource/azur emonitor/mocks/query.ts	4	application _entry	applicati on	unknow n	me diu m	unt este d
messageFromError	public/app/plugins/datasource/azur emonitor/utis/messageFromError.ts	13	application _entry	applicati on	unknow n	me diu m	unt este d
migrateAnnotation	public/app/plugins/datasource/azur emonitor/utis/migrateAnnotation.ts	10	application _entry	applicati on	unknow n	me diu m	unt este d
useLastError	public/app/plugins/datasource/azur emonitor/utis/useLastError.ts	9	application _entry	applicati on	unknow n	me diu m	unt este d
migrateAnnotation	packages/grafana- sql/src/utis/migration.ts	6	application _entry	applicati on	unknow n	me diu m	unt este d

5.8 Privacy Findings

One privacy finding is recorded: a plaintext-credential rule hit at `.github/workflows/relyance-scan.yml:26`. The remediation is to move the credential to a secret store or environment injection and to rotate the committed value. The M&A implication is a representation covering personal-data handling in the shipped product, scoped to the hits recorded in the credential inventory. PII endpoint count is 0; egress SDK count is 0; sensitive log count is 0 — but each of these is a detection result, not a confirmation of absence, and the partial coverage on Secrets means the buyer's privacy counsel should re-verify independently.

Table 5.6 — Privacy findings

Rule ID	Category	Title	Severity	File	Line
PRIV-PLAINTEXT-CRED	Plaintext credential	Plaintext credential material in committed config	Medium	<code>.github/workflows/relyance-scan.yml</code>	26

6. Supply Chain & Dependency Posture

6.1 Introduction

The third-party software supply chain combines direct and transitive breadth, pinning discipline, lockfile hygiene, ecosystem mix, and runtime end-of-life exposure. A broad unpinned transitive supply chain creates upstream-advisory and silent-breaking-change exposure and affects post-close security operating cost and SBOM obligations. The pillar risk is medium, held on aggregate metrics rather than item-level findings.

Direct-dependency rows, lockfile resolutions, pinning bookkeeping, and EOL runtime rows below are stored ground truth. The dependency posture reads from manifests / lockfiles as stored; where no lockfile is present, the gap is itemised below. The transitive resolved package count of 19,945 is the headline figure: it represents the supply-chain breadth that an SBOM must enumerate and that continuous-monitoring tooling must track post-close.

6.2 Key Figures

Direct dependency count: 1,533. Pinned dependencies: 237. Ranged dependencies: 1,296. Unpinned dependencies: 1,296. Pin ratio: 15.5%. Transitive resolved packages: 19,945. Lockfiles present: 50. Manifests found: 82.

EOL runtime rows: 1. EOL count: 0. Runtimes checked: 1. CVE unresolved packages (cross-ref): 19.

6.3 Lockfile Resolution

50 lockfiles are present across the repository, ranging from small (22 resolved packages) to large (3,721 packages in the root go.sum). The presence of lockfiles is a positive reproducibility signal — it means the seller's build is deterministic for the resolved subset. However, the 1,296 unpinned direct dependencies indicate that the manifest layer does not enforce version pinning, which means any newly added or updated dependency can drift between builds even when the lockfile is regenerated. The buyer's security operations team should require deploy-time enforcement of lockfile-based dependency resolution post-close.

Table 6.1 — Lockfile resolution (top 20 of 50 rows)

Lockfile	Resolved packages
.citools/src/air/go.sum	210
.citools/src/cue/go.sum	72
.citools/src/golangci-lint/go.sum	567
.citools/src/govulncheck/go.sum	22
.citools/src/lefthook/go.sum	108
.citools/src/swagger/go.sum	149
apps/advisor/go.sum	1,757

Lockfile	Resolved packages
apps/alerting/alertenrichment/go.sum	98
apps/alerting/alertrulequality/go.sum	96
apps/alerting/notifications/go.sum	300
apps/alerting/rules/go.sum	236
apps/annotation/go.sum	236
apps/collections/go.sum	170
apps/correlations/go.sum	236
apps/dashboard/go.sum	381
apps/dashvalidator/go.sum	1,747
apps/example/go.sum	252
apps/folder/go.sum	170
apps/iam/go.sum	236
apps/live/go.sum	236

6.4 Direct Dependency Inventory

500 direct dependencies are listed in the workbook, with a representative sample shown below. The vast majority are Go modules in apps/advisor and .citools subdirectories, indicating a Go-dominated backend with significant development-tooling overhead. The pin ratio of 15.5% (237 pinned of 1,533 direct) means 84.5% of direct dependencies are declared with a version range rather than an exact version, which exposes the build to silent upstream changes.

Table 6.2 — Direct dependency inventory (top 20 of 500 rows)

Name	Specified	Pin ned	Scop e	Ecosy stem	Manifest
4d63.com/gocheckcompilerdirectives	v1.4.0	No	go.mo d	Go	.citools/src/golangci-lint/go.mod
4d63.com/gochecknoglobals	v0.2.2	No	go.mo d	Go	.citools/src/golangci-lint/go.mod
cel.dev/expr	v0.25.3	No	go.mo d	Go	apps/advisor/go.mod
charm.land/lipgloss/v2	v2.0.6	No	go.mo d	Go	.citools/src/golangci-lint/go.mod
cloud.google.com/go/compute/metadata	v0.9.0	No	go.mo d	Go	apps/advisor/go.mod
codeberg.org/chavacava/garif	v0.2.1	No	go.mo d	Go	.citools/src/golangci-lint/go.mod
codeberg.org/polyfloyd/go-errorlint	v1.9.0	No	go.mo d	Go	.citools/src/golangci-lint/go.mod

Name	Specified	Pin ned	Scop e	Ecosy stem	Manifest
cuelabs.dev/go/oci/ociregistry	v0.0.0-20250722084951-074d06050084	No	go.mo d	Go	.citoools/src/cue/go.mod
cuelang.org/go	v0.15.4	No	go.mo d	Go	.citoools/src/cue/go.mod
dario.cat/mergo	v1.0.2	No	go.mo d	Go	.citoools/src/air/go.mod
dev.gaijin.team/go/exhauststruct/v4	v4.0.0	No	go.mo d	Go	.citoools/src/golangci-lint/go.mod
dev.gaijin.team/go/exhauststruct/v5	v5.2.0	No	go.mo d	Go	.citoools/src/golangci-lint/go.mod
dev.gaijin.team/go/golib	v0.8.1	No	go.mo d	Go	.citoools/src/golangci-lint/go.mod
filippo.io/edwards25519	v1.2.0	No	go.mo d	Go	apps/advisor/go.mod
github.com/4meepo/tagalign	v1.4.4	No	go.mo d	Go	.citoools/src/golangci-lint/go.mod
github.com/Abirdcfly/dupword	v0.1.8	No	go.mo d	Go	.citoools/src/golangci-lint/go.mod
github.com/AdminBenni/iota-mixing	v1.0.0	No	go.mo d	Go	.citoools/src/golangci-lint/go.mod
github.com/air-verse/air	v1.62.0	No	go.mo d	Go	.citoools/src/air/go.mod
github.com/alecthoas/chroma/v2	v2.27.0	No	go.mo d	Go	.citoools/src/golangci-lint/go.mod
github.com/alecthoas/go-check-sumtype	v0.5.1-0.20260828200218-ac6904d28606	No	go.mo d	Go	.citoools/src/golangci-lint/go.mod

6.5 EOL Runtime Detail

One runtime is checked: golang go 1.27.2, which is not end-of-life (latest is 1.27.2). The Go runtime is current, which is a positive signal — the buyer's modernization capital is not consumed by language upgrades. The end-of-life check uses endoflife.date as the source; the buyer's platform team should integrate continuous EOL monitoring into the post-close CI pipeline.

Table 6.3 — EOL runtime detail

Product	Runti me	Version	Is EOL	Latest	EOL date	Support
golang	go	1.27.2	No	1.27.2	Not quantified	Not quantified

6.6 M&A Implications

The 19 CVE-unresolved packages are the most actionable supply-chain finding. These are packages that the OSV advisory check could not resolve to a version, which means the seller's manifests declare a version range or have no lockfile. The buyer's security operations team should require (a) a complete SBOM generated from the resolved lockfiles, (b) a deploy-time enforcement policy that prevents deploying unresolvable dependencies, and (c) a 30-day SLA for upgrading dependencies with critical advisories. The deal-mechanic tag for Dependency is not currently in the conditions register (no price-adjustment lever is sized), but the buyer's counsel should consider adding one given the breadth of the transitive surface.

© MTD Services

7. Code Quality, Complexity & Technical Debt

7.1 Introduction

The maintainability economics of the codebase are converted from raw metrics into remediation capital and engineering time — the framing the deal model can use — anchored to the same hotspots a quality-of-earnings reviewer will probe. Complexity symbol metrics, percentiles, SQALE grades, duplication, and debt-marker inventories below are stored ground truth. The pillar risk is rated critical.

The headline figures: 57,667 symbols analysed; 2,048 high-complexity and 706 critical-complexity symbols; SQALE grade E with 108,265 days of remediation effort; debt ratio 26.4%; 828,217 duplicated lines (25.2% duplication ratio across 18,406 groups); 883 debt markers (0 on the critical path).

7.2 Key Figures

Average cyclomatic complexity: 3.1. Average cognitive complexity: 4.05. Complexity hotspot score: 0.0375. Debt density: 0.006614.

7.3 Material Findings

Five critical-complexity findings and five high-severity debt findings are recorded. Each is a scanner signal requiring validation before negotiation reliance. The complexity findings drive the critical-complexity line item (\$176,200); the debt findings drive the general-debt line item (\$7,530).

Table 7.1 — Material complexity findings

Finding ID	Symbol	Severity	Evidence state	File
F-complexity-001	ProvideService	Critical	Detected, not verified	pkg/services/live/live.go
F-complexity-002	applyIncrementalChanges	Critical	Detected, not verified	pkg/registry/apis/provisioning/jobs/sync/incremental.go
F-complexity-003	Plot	Critical	Detected, not verified	public/vendor/flot/jquery.flot.js
F-complexity-004	useQueryCoauthoringSession	Critical	Detected, not verified	public/app/features/dashboard-scene/panel-edit/PanelEditNext/QueryEditor/coauthoring/useQueryCoauthoringSession.ts
F-complexity-005	RunTestList	Critical	Detected, not verified	pkg/apiserver/storage/testing/store_tests.go

Table 7.2 — Material debt findings

Finding ID	Marker	Severity	Evidence state	File
F-debt-001	fixme	High	Detected, not verified	eslint.config.js:40

Finding ID	Marker	Severity	Evidence state	File
F-debt-002	fixme	High	Detected, not verified	eslint.config.js:624
F-debt-003	fixme	High	Detected, not verified	eslint.config.js:638
F-debt-004	fixme	High	Detected, not verified	eslint.config.js:658
F-debt-005	fixme	High	Detected, not verified	eslint.config.js:683

The deal-mechanic implication for the complexity findings is a price-adjustment lever treating the critical-complexity population as a priced integration work stream, sequenced with the plan the buyer commissions. For the debt findings, the implication is a holdback against delivery of the general-debt remediation programme. Quantification and sizing are for deal counsel; no amount is asserted in this report.

7.4 Complexity Percentiles

The cyclomatic complexity percentiles (P50=2, P90=7, P99=19) and cognitive complexity percentiles (P50=1, P90=12, P99=45) describe the distribution of structural complexity across the analysed symbols. The P50 values are favourable — most functions are simple. The P99 values, however, indicate that the most complex 1% of functions carry extreme complexity: a P99 cognitive complexity of 45 means a typical engineer would need significant time to understand the worst 1% of functions.

Table 7.3 — Cyclomatic complexity percentiles

Metric	Value
P50	2
P90	7
P99	19

Table 7.4 — Cognitive complexity percentiles

Metric	Value
P50	1
P90	12
P99	45

7.5 Hotspot Symbols

The hotspot table identifies the highest-complexity symbols by composite risk score. These are the symbols the buyer's post-close engineering team should refactor first. The Plot function in public/vendor/plot/jquery.flot.js (cyclomatic 473, cognitive 1,683) is the single most complex symbol — it is in vendored code, which means refactoring it requires either replacing the vendored library or accepting the complexity. The updateSchema function in DashboardMigrator.ts (cyclomatic 138) is the second-most-complex and is in first-party code, which makes it the highest-priority refactoring target.

Table 7.5 — Hotspot symbols (top 16 of 57,667 rows)

Name	Filepath	Cyclo.	Cogn.	Maint. idx	Compos ite risk
Plot	public/vendor/flot/jquery.flot.js	473	1,683	0	0.95
updateSchema	public/app/features/dashboard/state/Dashboa rdMigrator.ts	138	210	0	0.90
jsonDataToMetaJSO NData	apps/plugins/pkg/app/meta/converter.go	134	138	0	0.9125
InitializeForTest	pkg/server/bootstrap/wire/wire_gen.go	130	129	0	0.8575
Initialize	pkg/server/bootstrap/wire/wire_gen.go	130	129	0	0.87
TestRouteGetRuleSt atuses	pkg/services/ngalert/api/api_prometheus_test .go	121	186	0	0.9125
bytes2Value	pkg/util/xorm/session_convert.go	121	558	0	0.90
slice2Bean	pkg/util/xorm/session.go	120	455	0	0.90
getNavTitle	public/app/core/utils/navBarItem- translations.ts	109	109	10.7	0.8911
createGrafDir	pkg/tests/testinfra/testinfra.go	102	109	0	0.9375
authorize	pkg/services/ngalert/api/authorization.go	90	84	0	0.90
process	pkg/registry/apis/provisioning/controller/rep ository.go	88	134	0	0.90
graphToTimeseries Options	public/app/plugins/panel/timeseries/migratio ns.ts	80	307	2.05	0.9084
readDashboardIter	pkg/services/store/kind/dashboard/dashboard .go	76	237	14.82	0.9329
getStatementPositio n	public/app/plugins/datasource/cloudwatch/la nguage/cloudwatch-logs- sql/completion/statementPosition.ts	73	103	10.96	0.8906
buildUpdates	pkg/util/xorm/statement.go	69	623	16.96	0.8661

The composite risk score (0-1 scale, higher is riskier) weights cyclomatic, cognitive, and maintainability dimensions. A score ≥ 0.9 indicates a hotspot that should be refactored before any major modification. 16 of 16 shown symbols are ≥ 0.85 , indicating concentrated structural risk in the codebase.

7.6 Debt Markers by Type and Severity

Debt markers (in-source annotations like FIXME, TODO, HACK, XXX) total 883. None are on the critical path (0 critical-path markers), which is favourable. The type distribution shows 656 TODOs (74%), 121 debug-print-TS statements (14%), 44 FIXMEs (5%), and smaller counts of debug-print-JS, debug-print-PY, bare-except, hack, and xxx. The severity distribution shows 48 high, 656 medium, and 179 low.

Table 7.6 — Debt markers by type

Marker type	Count
Bare Except	5
Debug Print JS	38
Debug Print Py	13
Debug Print TS	121
Fixme	44
Hack	4
Todo	656
Xxx	2

Table 7.7 — Debt markers by severity

Severity	Count
High	48
Low	179
Medium	656

7.7 Debt Marker Inventory

The debt-marker inventory shows the `eslint.config.js` file hosts five FIXMEs at lines 40, 624, 638, 658, and 683 — four of which read 'FIXME: Remove once all enterprise issues are fixed'. This pattern indicates a known outstanding clean-up tied to enterprise / open-source boundary issues that the seller has deferred. The buyer's counsel should require disclosure of the specific 'enterprise issues' referenced and confirm whether they affect the licensed product.

Table 7.8 — Debt marker inventory (top 16 of 883 rows)

Filepath	Line	Marker	Severity	Critical path	Text
<code>eslint.config.js</code>	40	fixme	high	No	// [FIXME] add comment about this applying everywhere
<code>eslint.config.js</code>	624	fixme	high	No	// FIXME: Remove once all enterprise issues are fixed -
<code>eslint.config.js</code>	638	fixme	high	No	// FIXME: Remove once all enterprise issues are fixed -
<code>eslint.config.js</code>	658	fixme	high	No	// FIXME: Remove once all enterprise issues are fixed -
<code>eslint.config.js</code>	683	fixme	high	No	// FIXME: Remove once all enterprise issues are fixed -

Filepath	Line	Marker	Severity	Critical path	Text
packages/grafana-api-clients/src/clients/rtkq/dashboard/v2/endpoints.gen.ts	1,073	fixme	high	No	/** Link type. Accepted values are dashboards (to refer to another dashboard) and link...
packages/grafana-api-clients/src/clients/rtkq/dashboard/v2beta1/endpoints.gen.ts	1,617	fixme	high	No	/** Link type. Accepted values are dashboards (to refer to another dashboard)...
packages/grafana-api-clients/src/clients/rtkq/provisioning/v0alpha1/endpoints.gen.ts	1,710	fixme	high	No	/** Paths to be deleted. Examples: dashboard.json (file) ...
packages/grafana-api-clients/src/clients/rtkq/provisioning/v0alpha1/endpoints.gen.ts	1,734	fixme	high	No	/** Paths to be deleted. Examples ...
packages/grafana-api-clients/src/clients/rtkq/provisioning/v0alpha1/endpoints.gen.ts	1,762	fixme	high	No	/** FIXME: we should validate this in admission hooks Target branch for export (only git) */
packages/grafana-api-clients/src/clients/rtkq/provisioning/v0alpha1/endpoints.gen.ts	1,770	fixme	high	No	/** FIXME: we should validate this in admission hooks Prefix in target file system */
packages/grafana-schema/src/schema/dashboard/v2/types.spec.gen.ts	1,586	fixme	high	No	// FIXME: The type is generated as `type: DashboardLinkType   dashboardLinkType.Link;` ...
packages/grafana-schema/src/schema/dashboard/v2alpha1/types.spec.gen.ts	1,050	fixme	high	No	// FIXME: The type is generated as `type: DashboardLinkType   dashboardLinkType.Link;` ...
packages/grafana-schema/src/schema/dashboard/v2beta1/types.spec.gen.ts	1,578	fixme	high	No	// FIXME: The type is generated as `type: DashboardLinkType   dashboardLinkType.Link;` ...
packages/grafana-test-utils/src/types/browse-dashboards.ts	1	fixme	high	No	// FIXME: This file is a duplication of types within the core code
packages/grafana-ui/src/components/Forms/commonStyles.ts	39	hack	high	No	/* Welcome to 2005. This is a HACK to get rid of Chromes default autofill styling */

The HACK markers in packages/grafana-ui/src/components/Forms/commonStyles.ts ('Welcome to 2005. This is a HACK to get rid of Chromes default autofill styling') indicate known workarounds for browser quirks. These should not affect valuation but should be on the post-close refactoring backlog.

7.8 SQALE Grade and Remediation Effort

The SQALE grade of E (worst on the A-E scale) is driven by a debt ratio of 26.4% — meaning technical debt represents over a quarter of the equivalent rewrite effort. The SQALE remediation effort of 108,265 days (≈ 421 person-years at 8h/day, 260 days/year) is the canonical planning figure. The model does not add SQALE as a separate line item to avoid double-counting with the complexity

hotspot category; instead it consumes SQALE as a planning bound. The buyer should treat the 108K-day figure as a long-tail backlog indicator, not as a remediation obligation to be sized into the price.

7.9 Duplication

828,217 lines of code are duplicated across 18,406 groups, representing a 25.2% duplication ratio against the 57,667 analysed symbols. A duplication ratio above 20% is a structural concern: it indicates the codebase carries copy-paste legacy that amplifies the cost of any change to the duplicated logic. The buyer's post-close engineering team should commission a duplication-removal sprint focused on the highest-occurrence groups first.

© MTD Services

8. Testing, Coverage & Regression Risk

8.1 Introduction

Where the codebase is structurally covered by tests and where it is not drives the leading indicator of post-close regression incidents and the cost of mandated refactoring. The effective insured value translates directly into contingent-liability sizing. Test-ratio module rows, coverage ratios, and high-value gap modules below are stored ground truth. The pillar risk is high.

The headline figures: 2,506 modules analysed; 1,882 below threshold; overall test ratio 15.3%; 42 high regression-risk modules; effective insured value 1; value coverage ratio 4.8%; 592 high-value gaps. The coverage method is a static symbol-share proxy, not runtime or line/branch coverage.

8.2 Key Figures

The overall test ratio of 15.3% means that across the 2,506 analysed modules, only 15.3% of the file count is test files. The value coverage ratio of 4.8% means that only 4.8% of high-blast-symbol value is insured by tests — meaning 95.2% of high-blast symbols are uninsured. The effective insured value of 1 (on a normalised scale where the most valuable module = 1) means that only one module — pkg/storage/unified/resource with 4,210 production symbols — is fully insured; every other module has partial or zero coverage.

8.3 Test-Deficit Module Inventory

The 2,506 analysed modules include 1,882 below threshold (75.1%). The 14 modules shown below all carry a test ratio of 1.0 (all test files, no source files) — these are e2e-playwright test suites and grafana-alerting test directories. The modules with ratio 1.0 do not contribute to the test deficit; the deficit is concentrated in the 1,882 modules with ratio below threshold (typically below 0.3).

Table 8.1 — Test-deficit module inventory (top 14 of 2,506 rows)

Module path	Test files	Source files	Test ratio	Regression risk
e2e-playwright/plugin-catalog-suite/tests	2	0	1	0
e2e-playwright/plugin-catalog-suite/tests/useMTPlugins	1	0	1	0
e2e-playwright/test-plugins/grafana-extensiontest-app/tests	4	0	1	0
e2e-playwright/test-plugins/grafana-extensiontest-app/tests/translations	2	0	1	0
e2e-playwright/test-plugins/grafana-extensiontest-app/tests/useMTPlugins	3	0	1	0
e2e-playwright/test-plugins/grafana-test-app/tests	2	0	1	0
e2e-playwright/test-plugins/grafana-test-app/tests/useMTPlugins	1	0	1	0
e2e-playwright/test-plugins/grafana-test-datasource/tests	4	0	1	0

Module path	Test files	Source files	Test ratio	Regression risk
e2e-playwright/test-plugins/grafana-test-datasource/tests/translations	2	0	1	0
e2e-playwright/test-plugins/grafana-test-datasource/tests/useMTPlugins	1	0	1	0
e2e-playwright/test-plugins/grafana-test-panel/tests	3	0	1	0
e2e-playwright/test-plugins/grafana-test-panel/tests/translations	2	0	1	0
e2e-playwright/test-plugins/grafana-test-panel/tests/useMTPlugins	2	0	1	0
grafana-alerting/tests	3	0	1	0

8.4 Coverage Module Detail

The coverage module detail is the central regression-risk indicator. The 14 modules shown below have 0 coverage despite carrying high production-symbol counts. pkg/storage/unified/resource (4,210 symbols) is the single most material gap — it carries the maximum risk weight of 1.0 and has zero coverage. The buyer's post-close engineering team should treat these modules as the priority for test investment; the test_investment line item (\$20,400) is sized for 42 high-regression-risk modules but the actual backlog is much larger.

Table 8.2 — Coverage module detail (top 14 of 2,506 rows)

Module	Prod symbols	Coverage ratio	Risk weight	Value exposure
pkg/storage/unified/resource	4,210	0	1	1
pkg/storage/unified/search	1,469	0	0.3718	0.3602
pkg/api	1,590	0	0.2452	0.2876
dashboard/pkg/migration/conversion	574	0	0.2455	0.2471
pkg/util/xorm	672	0	0.2331	0.2401
pkg/registry/apis/provisioning/resources	919	0	0.2289	0.2388
pkg/setting	1,353	0	0.1676	0.2264
pkg/router	1,342	0	0.2193	0.2232
iam/pkg/apis/iam/v0alpha1	1,299	0	0.1433	0.1958
pkg/services/ngalert/api	981	0	0.1755	0.1932
pkg/registry/apis/folders	453	0	0.2180	0.1865
pkg/services/ngalert/notifier	873	0	0.1569	0.1857
pkg/registry/apis/provisioning/controller	710	0	0.1771	0.1807
pkg/registry/apis/datasource	411	0	0.2128	0.1732

8.5 High-Value Coverage Gaps

The high-value gaps table isolates the modules whose coverage gap carries the highest risk weight. These are the modules where the buyer's quality-of-earnings provider should focus regression-risk validation. The 592 high-value gaps total means 592 modules carry a risk weight above the high-value threshold and have zero or near-zero coverage. The deal-mechanic implication is a price-adjustment lever raising regression coverage on high-risk modules post-close.

Table 8.3 — High-value coverage gaps (top 14 of 592 rows)

Module	Risk weight	Coverage ratio
pkg/storage/unified/resource	1	0
pkg/storage/unified/search	0.3718	0
dashboard/pkg/migration/conversion	0.2455	0
pkg/api	0.2452	0
pkg/util/xorm	0.2331	0
pkg/registry/apis/provisioning/resources	0.2289	0
pkg/router	0.2193	0
pkg/registry/apis/folders	0.2180	0
pkg/registry/apis/datasource	0.2128	0
public/app/plugins/panel/geomap/layers/basemaps	0.2058	0
pkg/registry/apis/provisioning/controller	0.1771	0
pkg/services/ngalert/api	0.1755	0
pkg/setting	0.1676	0
pkg/registry/apps/alerting/rules/search	0.1668	0

8.6 Coverage Method

Coverage is measured by a static symbol-share proxy: Static symbol-share proxy (test-file symbols weighted by structural value); not runtime or line/branch coverage. This means the reported coverage is structural (test-file symbols exist) rather than runtime (lines or branches executed). The buyer's post-close engineering team should commission runtime coverage as a follow-up, prioritising the modules with high structural risk weight and zero structural coverage.

8.7 M&A Implications

The 95.2% uninsured exposure on high-blast symbols is the most consequential testing finding. It means that any refactoring the buyer commissions post-close will be undertaken without a regression safety net for the vast majority of high-value code. The 42 high-regression-risk modules sized under the test_investment line item (\$20,400) are a planning bound for the most acute gap, not a comprehensive remediation figure. The buyer's counsel should require (a) a price-adjustment lever raising regression coverage on high-risk modules post-close, (b) a holdback against delivery of the

test-investment programme, and (c) a warranty covering the absence of known regression defects in the modules with zero coverage.

© MTD Services

9. Architecture, Entanglement & Integration Risk

9.1 Introduction

The architectural shape determines how cleanly the asset can be integrated: layering discipline, cyclic dependencies, cross-layer violations, API-contract maturity, database coupling, and serialization risks. Integration cost is the most under-estimated line item in software acquisition; entanglement and integration-risk scores give the integration-management office a defensible basis for the synergy model and transition-services scope. Cycle inventories, cross-layer violations, API-contract and coupling metrics, and serialization-risk rows below are stored ground truth. The pillar risk is rated critical (Entanglement) and high (Integration).

9.2 Key Figures

Circular-dependency cycles: 4. Max cycle length: 1,445 modules. Cross-layer violations: 19,887. Modules in cycles: 1,451. Entanglement score: 1. Integration risk score: 10 (maximum on the 0-10 scale). Schema drift risk: High. Proprietary coupling count: 509. Integration findings total: 521.

9.3 Cycle Inventory

Four cyclic dependencies are detected. The largest spans 1,445 modules — an extreme architectural pathology indicating deep inter-dependency among the affected modules. The other three cycles are smaller (2 modules each) but still flag decoupling work. The decoupling line item (\$4,000) is sized for all four cycles at \$1,000 each, but the 1,445-module cycle will require materially more effort than the small cycles; the buyer's engineering team should re-estimate using a code-complexity-weighted approach.

Table 9.1 — Cycle inventory

Cycle length	Severity	Modules
1,445	Critical	1,445 modules
2	Medium	2 modules
2	Medium	2 modules
2	Medium	2 modules

9.4 Cross-Layer Violations

19,887 cross-layer violations are recorded — an extreme count indicating pervasive architectural layering breaches. The violations are predominantly presentation-to-data calls (e.g. alerting alertrichment / alertrulequality / notifications / rules APIs calling into pkg/expr, which is the data layer). This pattern indicates that the API-layer types are reaching past the service layer into expression evaluation, which means the service layer is not actually abstracting data access. The buyer's post-close architectural review should commission a layering audit and a remediation plan.

Table 9.2 — Cross-layer violation detail (top 14 of 19,887 rows)

From module	To module	From layer	To layer	Rel type	Severity
alerting/alertenrichment/pkg/apis/alertenrichment/v1beta1	pkg/expr	presentation	data	calls	Critical
alerting/alerrulequality/pkg/apis/alerrulequality/v0alpha1	pkg/expr	presentation	data	calls	Critical
alerting/notifications/pkg/apis/alertingnotifications/v0alpha1/fakes	pkg/expr	presentation	data	calls	Critical
alerting/rules/pkg/apis/alerting/v0alpha1	pkg/expr	presentation	data	calls	Critical
collections/pkg/apis/collections/v1alpha1	pkg/expr	presentation	data	calls	Critical
dashboard/pkg/apis/dashboard/v0alpha1	pkg/expr	presentation	data	calls	Critical
dashboard/pkg/apis/dashboard/v0alpha1	dashboard/pkg/migration/schemaversion	presentation	data	imports	Critical
dashboard/pkg/apis/dashboard/v1	pkg/expr	presentation	data	calls	Critical
dashboard/pkg/apis/dashboard/v1	dashboard/pkg/migration/schemaversion	presentation	data	imports	Critical
dashboard/pkg/apis/dashboard/v2	dashboard/pkg/migration/conversion	presentation	data	calls	Critical
dashboard/pkg/apis/dashboard/v2	pkg/expr	presentation	data	calls	Critical
dashboard/pkg/apis/dashboard/v2alpha1	dashboard/pkg/migration	presentation	data	calls	Critical
dashboard/pkg/apis/dashboard/v2alpha1	pkg/expr	presentation	data	calls	Critical
dashboard/pkg/apis/dashboard/v2beta1	pkg/expr	presentation	data	calls	Critical

Every shown violation is critical-severity and presentation-to-data. The 19,887 total indicates that the API surface is structurally coupled to the data layer across alerting, collections, dashboard, and provisioning subsystems. This pattern is the single most material architectural finding in the scan.

9.5 API Contract Maturity

API contract maturity is assessed on five metrics. 17 endpoints are detected; 13 proto files define the contract surface; 152 types are declared. OpenAPI and GraphQL are both absent, which means the REST API surface is not declared via a standard specification — this drives the high schema-drift-risk rating and contributes to the integration risk score of 10.

Table 9.3 — API contract maturity

Metric	Value
Endpoint count	17

Metric	Value
GraphQL found	No
OpenAPI found	No
Proto files	13
Type count	152

The absence of OpenAPI means the buyer's API-consumer teams cannot rely on a published specification; they must reverse-engineer the contract from source. The 13 proto files indicate gRPC-style contracts, which are typically machine-generated and well-typed; the buyer should request the generated client libraries as part of transition-services scope.

9.6 Database Coupling

Database coupling shows cross-schema access (Yes), 40 destructive DDL statements, 178 migration files, 0 migration tooling entries, no ORM usage, and 2,601 raw SQL statements. The combination of cross-schema access and 2,601 raw SQL statements means the application is structurally coupled to a specific database schema and dialect — migrating to a different database (e.g. for an acquirer requiring PostgreSQL-on-cloud-native) would be a major engineering effort. The 40 destructive DDL statements should be reviewed for irreversible schema changes that have been applied historically.

Table 9.4 — Database coupling

Metric	Value
Cross schema access	Yes
Destructive DDL count	40
Migration files	178
Migration tooling	0
ORM usage	No
Raw SQL count	2,601

The absence of an ORM is unusual for a codebase of this size and is a deliberate architectural choice. The buyer's engineering team should validate that the seller's choice is intentional (e.g. for performance reasons) rather than legacy. The 178 migration files indicate a long migration history; the buyer should request the migration runbook as part of operational handover.

9.7 Serialization Risks

Serialization risks include `dynamic_function` calls and `eval_call` patterns — both are dangerous deserialization patterns that can lead to remote code execution if untrusted input reaches them. 509 proprietary-coupling findings and 521 total integration findings are recorded. The `eval_call` cluster in `pkg/api/admin.go` (lines 93, 103, 123, 134, 144) is particularly concerning because it is in the admin API surface, which is typically a privileged endpoint. The buyer's security team should require validation of these patterns as part of the Secrets / CVE condition precedent.

Table 9.5 — Serialization risks (top 14 of 509 rows)

Risk type	Filepath	Line	Severity	Description
serialization:dynamic_function	e2e-playwright/panels-suite/xychart.spec.ts	91	High	Dangerous deserialization: dynamic_function
serialization:dynamic_function	public/app/features/dashboard/dashboardgrid/DashboardLibrary/Utils/communityDashboardHelpers.ts	181	High	Dangerous deserialization: dynamic_function
serialization:dynamic_function	scripts/rspack/hmrConfig.test.ts	91	High	Dangerous deserialization: dynamic_function
serialization:dynamic_function	public/app/features/dashboard/services/DashboardLoaderSrv.ts	102	High	Dangerous deserialization: dynamic_function
serialization:dynamic_function	public/app/plugins/panel/xychart/scatter.ts	684	High	Dangerous deserialization: dynamic_function
serialization:dynamic_function	public/app/plugins/panel/xychart/scatter.ts	682	High	Dangerous deserialization: dynamic_function
serialization:eval_call	public/app/features/dashboard/dashboardgrid/DashboardLibrary/Utils/communityDashboardHelpers.ts	180	High	Dangerous deserialization: eval_call
serialization:eval_call	pkg/expr/threshold.go	212	High	Dangerous deserialization: eval_call
serialization:eval_call	pkg/expr/threshold.go	209	High	Dangerous deserialization: eval_call
serialization:eval_call	pkg/api/admin.go	134	High	Dangerous deserialization: eval_call
serialization:eval_call	pkg/api/admin.go	93	High	Dangerous deserialization: eval_call
serialization:eval_call	pkg/api/admin.go	103	High	Dangerous deserialization: eval_call
serialization:eval_call	pkg/api/admin.go	144	High	Dangerous deserialization: eval_call
serialization:eval_call	pkg/api/admin.go	123	High	Dangerous deserialization: eval_call

9.8 Protocol-Layer Risks

Twelve protocol-layer risks are recorded, all related to raw socket usage for WebSocket handling in Grafana Live. The risks are medium-severity because raw socket usage is expected for WebSocket implementations, but the buyer's security team should validate that the WebSocket handlers do not accept untrusted input directly. The pkg/services/live subsystem is the main location; the buyer should require disclosure of the WebSocket message-rate-limiting and authentication posture.

Table 9.6 — Protocol-layer risks

Risk type	Filepath	Line	Severity	Description	Evidence
protocol:raw_socket	public/app/features/api/server/client.ts	203	Medium	Raw socket usage detected	Polling fallback when the Grafana Live WebSocket Observable errors.
protocol:raw_socket	pkg/services/live/live.go	490	Medium	Raw socket usage detected	GrafanaLive manages live real-time connections to Grafana (over WebSocket).
protocol:raw_socket	pkg/services/live/push/ws/push_stream.go	17	Medium	Raw socket usage detected	Handler handles WebSocket client connections that push data to Live.
protocol:raw_socket	pkg/setting/setting.go	570	Medium	Raw socket usage detected	LiveMaxConnections is a maximum number of WebSocket connections.
protocol:raw_socket	pkg/services/live/push/ws/push_pipeline.go	14	Medium	Raw socket usage detected	PipelinePushHandler handles WebSocket client connections that push data to Live Pipeline.
protocol:raw_socket	pkg/router/watch.go	32	Medium	Raw socket usage detected	watch over WebSocket. The router does not proxy upgrades.
protocol:raw_socket	public/app/features/api/server/client.test.ts	351	Medium	Raw socket usage detected	const wsError = new Error('WebSocket failed');
protocol:raw_socket	public/app/features/api/server/client.test.ts	370	Medium	Raw socket usage detected	const wsError = new Error('WebSocket failed');
protocol:raw_socket	pkg/router/watch.go	38	Medium	Raw socket usage detected	http.Error(w, 'the router does not support protocol upgrades...')
protocol:raw_socket	pkg/middleware/gzipper.go	103	Medium	Raw socket usage detected	prefix('/api/live/push') - WebSocket does not support gzip compression.
protocol:raw_socket	pkg/middleware/gzipper.go	102	Medium	Raw socket usage detected	prefix('/api/live/ws') - WebSocket does not support gzip compression.
protocol:raw_socket	pkg/router/watch_test.go	356	Medium	Raw socket usage detected	require.Contains(t, string(body), 'watch over WebSocket is not supported')

9.9 M&A Implications

The integration risk score of 10 (maximum) is the headline architectural finding. It means the buyer's integration-management office should expect the integration to require significant transition-services scope, a dedicated integration team, and a longer integration timeline than a typical SaaS acquisition. The 1,445-module cycle and the 19,887 cross-layer violations are the dominant cost drivers. The buyer's counsel should draft the transition-services agreement with explicit milestones for architectural decoupling, sized against the decoupling line item (\$4,000 — a planning bound, not a priced quote) and the integration-drag percentage (80%).

The deal-mechanic tag for Entanglement is a price-adjustment lever requiring a plan for decoupling circular dependency cycles. The deal-mechanic tag for Integration is a price-adjustment lever addressing integration findings as a condition precedent — the wording 'as a condition precedent' is unusual for a price-adjustment lever and the buyer's counsel should clarify whether the seller intends this as a blocking condition or a priced work stream. The schema-drift risk rating of high should drive a warranty covering API-contract stability for the buyer's API-consumer teams.

© MTD Services

10. Engineering Capacity, Bus Factor & Knowledge Loss Vulnerability

10.1 Introduction

The human-capital risk embedded in the codebase drives retention-bonus sizing, earn-out structure, and the transition-services window. Sole-maintainer modules are a primary cause of post-close silent outages and warrant explicit warranty language. Concentration risk is recorded across 3,217 contributors, with 510 at-risk contributors and 1,552 critical sole-maintainer modules. The knowledge-loss vulnerability score of 0.531 (on a 0-1 scale, higher is riskier) is the headline human-capital figure.

10.2 Key Figures

Total authors: 3,217. Overall bus factor: 33. Critical key-person rows: 0. Key-person risk rows: 3,217. Module bus-factor rows: 2,449.

Retention: total contributors 3,217; active 591; inactive 2,626; at-risk 510; knowledge loss vulnerability score 0.531; critical modules 4,548; at-risk contributors (model input) 510; critical sole-maintainer modules (model input) 1,552.

10.3 Material Findings

Five key-person findings (all low severity, inferred) and five retention findings (all critical severity, inferred) are recorded. Each is a scanner signal requiring validation before negotiation reliance. The deal-mechanic implication for key-person is a named closing condition: identify the bus-factor holders and bind their transition terms. For retention, the implication is securing retention or transition agreements from the contributors carrying institutional knowledge as a condition to key-employee arrangements.

Table 10.1 — Material key-person findings

Finding ID	Author	Severity	Evidence state
F-key_person-001	ryantxu@gmail.com	Low	Inferred
F-key_person-002	ashley.harrison@grafana.com	Low	Inferred
F-key_person-003	joshhunt@users.noreply.github.com	Low	Inferred
F-key_person-004	torkel@grafana.com	Low	Inferred
F-key_person-005	stephanie.hingtgen@grafana.com	Low	Inferred

Table 10.2 — Material retention findings

Finding ID	Contributor	Severity	Evidence state
F-retention-001	Alex Khomenko	Critical	Inferred
F-retention-002	Roberto Jiménez Sánchez	Critical	Inferred
F-retention-003	Kevin Minehart	Critical	Inferred
F-retention-004	Sofia Papagiannaki	Critical	Inferred

Finding ID	Contributor	Severity	Evidence state
F-retention-005	Galen Kistler	Critical	Inferred

The five critical retention findings identify the contributors whose departure would destabilise the most institutional knowledge: Alex Khomenko (blast radius 246 modules), Roberto Jiménez Sánchez, Kevin Minehart, Sofia Papagiannaki (blast radius 246 modules, tenure 1,820 days), and Galen Kistler (blast radius 68 modules). Each should be the subject of an individual retention-bonus negotiation in the post-close plan.

10.4 Key-Person Risk Detail

The top key-person risk rows identify the contributors with the highest concentration of activity. ryantxu@gmail.com carries a risk score of 0.265 with 234,722 commits — extreme concentration in a single contributor. ashley.harrison@grafana.com (0.216, 131K commits) and joshhunt@users.noreply.github.com (0.104, 63K commits) follow. The departure-impact is rated low for every shown contributor because the bus factor of 33 across the codebase is sufficient to absorb any single departure; the risk is in the long tail of sole-maintainer modules, not in the top contributors.

Table 10.3 — Key-person risk detail (top 14 of 3,217 rows)

Author name	Author email	Risk score	Total commits	Departure impact
ryantxu@gmail.com	ryantxu@gmail.com	0.26468	234,722	Low
ashley.harrison@grafana.com	ashley.harrison@grafana.com	0.216071	131,354	Low
joshhunt@users.noreply.github.com	joshhunt@users.noreply.github.com	0.103575	63,357	Low
torkel@grafana.com	torkel@grafana.com	0.0803188	90,155	Low
stephanie.hingtgen@grafana.com	stephanie.hingtgen@grafana.com	0.0686434	40,405	Low
hugo.haggmark@gmail.com	hugo.haggmark@gmail.com	0.0615704	65,580	Low
29139614+renovate[bot]@users.noreply.github.com	29139614+renovate[bot]@users.noreply.github.com	0.0612221	11,923	Low
roberto.jimenez@grafana.com	roberto.jimenez@grafana.com	0.0528524	132,108	Low
macabu@users.noreply.github.com	macabu@users.noreply.github.com	0.050841	31,702	Low
leoniya@gmail.com	leoniya@gmail.com	0.0498112	48,560	Low
45561153+kaydelaney@users.noreply.github.com	45561153+kaydelaney@users.noreply.github.com	0.0477866	28,972	Low
marcus.efraimsson@gmail.com	marcus.efraimsson@gmail.com	0.0463529	26,936	Low

Author name	Author email	Risk score	Total commits	Departure impact
academo@users.noreply.github.com	academo@users.noreply.github.com	0.0456318	7,270	Low
laura.fernandez@grafana.com	laura.fernandez@grafana.com	0.041486	11,503	Low

10.5 Module Bus-Factor Detail

Module bus-factor rows identify modules where the contributor count is concentrated. pkg/setting (bus factor 22) is the most resilient module; pkg/api (12), _unassigned (9, but 6,605 files), grafana-data/src/types (9), and pkg/services/sqlstore (9) follow. The lower the bus factor, the greater the concentration risk. Modules with bus factor of 1 are sole-maintainer — these are the modules sized under the knowledge-transfer line item.

Table 10.4 — Module bus-factor detail (top 14 of 2,449 rows)

Module path	Bus factor	Total files
pkg/setting	22	54
pkg/api	12	96
_unassigned	9	6,605
grafana-data/src/types	9	58
pkg/services/sqlstore	9	21
public/app/types	9	26
pkg/api/dtos	8	18
grafana-data/src/utls	7	51
pkg/registry/backgroundsvcs	7	1
pkg/server	7	29
pkg/services/sqlstore/migrations	7	41
pkg/tests/testinfra	7	2
pkg/util	7	33
public/app/core/utls	7	53

10.6 Git Team Signals

The git team signals reveal several stress indicators. The after-hours-commits percentage of 0.329 (32.9%) is high and indicates either a globally distributed team or sustained crunch-mode development. The bus-factor proxy of 0.906 indicates the team is structurally healthy on aggregate (the proxy approaches 1.0 when contributor concentration is low). The cadence of 1,000 commits per week is sustained, indicating active development. The ghost-author count of 42 (contributors with no email attribution) is a data-quality signal that should be cleaned up before close.

Table 10.5 — Git team signals

Metric	Value
After-hours commits	658
After-hours percentage	0.329
Bus factor proxy	0.906
Cadence per week	1,000
Ghost author count	42
Modules analyzed	39
Top-1 author share	0.094
Top-3 author share	0.1705
Top-5 author share	0.222
Total commits	2,000
Unique authors	184
Unique emails	179

The top-1 author share of 0.094 (9.4%) indicates reasonable contributor distribution at the aggregate level. The top-3 (17%) and top-5 (22%) shares confirm that no single contributor dominates commit volume at the codebase level — the concentration risk is concentrated in the long tail of sole-maintainer modules, not in the top contributors.

10.7 Knowledge Loss Vulnerability Detail

The knowledge-loss vulnerability detail identifies contributors whose tenure, recent activity, and sole-maintainership profile combine to create critical retention risk. Each shown contributor has been classified as critical retention risk based on a multi-factor score. The buyer's HR team should obtain retention terms for each named contributor before close; the retention-bonus pool should be sized against the knowledge-transfer line item (\$316,400).

Table 10.6 — Knowledge loss vulnerability detail (top 14 of 3,217 rows)

Author name	Author email	Tenure days	Days since last commit	Retention risk	Blast radius at risk
undeflnd	10127682+undeflnd@users.noreply.github.com	1,021	0	Critical	19
Galen Kistler	109082771+gtk-grafana@users.noreply.github.com	1,534	0	Critical	68
Fayzal Ghantiwala	114010985+fayzal-g@users.noreply.github.com	896	55	Critical	0
volcanonoodle	114113189+volcanonoodle@users.noreply.github.com	1,063	2	Critical	72

Author name	Author email	Tenure days	Days since last commit	Retention risk	Blast radius at risk
Liza Detrick	114438185+L2D2Grafana@users.noreply.github.com	883	7	Critical	0
Shubham Nainwal	118589955+Shubham19032004@users.noreply.github.com	491	93	Critical	0
grafana-delivery-bot[bot]	132647405+grafana-delivery-bot[bot]@users.noreply.github.com	1,212	150	Critical	0
Fabrizio	135109076+fabrizio-grafana@users.noreply.github.com	1,198	1	Critical	42
Lucy Chen	140550297+lucychen-grafana@users.noreply.github.com	1,154	21	Critical	0
Tobias Skarhed	1438972+tskarhed@users.noreply.github.com	2,455	8	Critical	30
Marc M.	146180665+grafakus@users.noreply.github.com	716	0	Critical	121
alerting-team[bot]	158350966+alerting-team[bot]@users.noreply.github.com	591	0	Critical	0
Adam Yeats	16296989+adamyeads@users.noreply.github.com	1,186	3	Critical	15
Sofia Papagiannaki	1632407+papagian@users.noreply.github.com	1,820	0	Critical	246

10.8 M&A Implications

The 510 at-risk contributors and 1,552 critical sole-maintainer modules are the most actionable human-capital findings. The 81.7% inactive contributor ratio (2,626 of 3,217) means the active development team is materially smaller than the historical contributor base suggests; the buyer's HR team should obtain the current headcount and the active-contributor list as part of due diligence. The 32.9% after-hours commit percentage is a stress indicator that should be discussed in management presentations — sustained high after-hours ratios correlate with retention risk.

The deal-mechanic tag for Retention is a price-adjustment lever securing retention agreements for sole-maintainer modules. The knowledge-transfer line item (\$316,400) is sized per unique module, not per at-risk contributor — meaning the buyer's HR team can choose to deploy the budget against the most acute sole-maintainer modules rather than against individual contributors. The buyer's counsel should draft retention agreements with vesting tied to a transition-services window of at least 12 months post-close.

© MTD Services

11. Maintenance, Documentation & Operational Maturity

11.1 Introduction

Documentation and CI maturity determine onboarding velocity for the acquirer's engineers and the run-rate cost of keeping the asset alive during integration. The maintenance backlog score anchors the post-close engineering-budget uplift. The pillar risk for Maintenance is unverified — no files were scanned by the asset-staleness scanner. The pillar risk for Doc Staleness is low. The pillar risk for CI Maturity is medium.

11.2 Key Figures — Maintenance

Maintenance total files: 0. Neglected files: 0. At-risk files: 0. Healthy files: 0. Average staleness: 0. Maintenance backlog score: 0. Maintenance asset rows: 0.

The maintenance pillar is NOT ASSESSED. The asset-staleness scanner produced zero rows because no files were scanned under its current configuration. The pillar is demoted to informational and labelled UNVERIFIED. The buyer should commission an independent asset-staleness assessment as part of pre-signing diligence — the absence of a staleness figure is a coverage gap, not a clean result.

11.3 Key Figures — Documentation

Documents inventoried: 797. Stale documents: 63. Document staleness ratio: 7.9%. Average docstring density: 0.0003. The 7.9% staleness ratio means 63 of 797 inventoried documentation files are stale relative to the staleness threshold. The docstring density of 0.0003 is effectively zero — the codebase has negligible inline documentation, which materially affects onboarding velocity for the acquirer's engineers.

Table 11.1 — Document inventory (top 14 of 797 rows)

File	Last documented	Stale
docs/sources/developer-resources/api-reference/http-api/apis.md	2026-07-07	Yes
docs/sources/developer-resources/api-reference/http-api/api-legacy/correlations.md	2026-06-26	Yes
docs/sources/developer-resources/api-reference/http-api/dashboard.md	2026-07-01	Yes
docs/sources/shared/test.md	2023-07-18	Yes
docs/sources/developer-resources/api-reference/http-api/api-legacy/annotations.md	2026-09-14	Yes
docs/sources/shared/example.md	2023-08-31	Yes
docs/sources/developer-resources/api-reference/http-api/folder.md	2026-07-01	Yes
docs/sources/developer-resources/api-reference/http-api/playlist.md	2026-07-01	Yes
docs/sources/developer-resources/api-reference/http-api/api-legacy/preferences.md	2026-06-26	Yes

File	Last documented	Stale
docs/sources/datasources/tempo/configure-tempo-data-source/provision.md	2026-04-09	Yes
docs/sources/administration/cli.md	2025-10-28	Yes
docs/sources/developer-resources/api-reference/http-api/api-legacy/admin.md	2026-09-22	Yes
docs/sources/shared/back-up/back-up-grafana.md	2025-06-19	Yes
docs/sources/developer-resources/api-reference/http-api/api-legacy/team.md	2026-06-26	Yes

The stale documents include API reference files (most recently modified 2026-06-26 to 2026-09-22) and shared documentation files (some dating to 2023). The 7.9% ratio is favourable in aggregate, but the docstring density of 0.0003 is the more concerning figure because it indicates near-total absence of inline code documentation.

11.4 Key Figures — CI Maturity

CI defined: true. CI files checked: 98. CI gate strictness: Medium. Tests run in CI: true. Reported coverage in CI: Not quantified.

The CI surface is substantial — 98 GitHub Actions workflows are checked. The gate strictness is medium, which means CI runs tests but does not enforce coverage thresholds or block on coverage regressions. The reported coverage metric is not quantified, which is a data-quality gap: the seller's CI runs tests but does not publish a coverage report that the scanner could consume. The buyer's engineering team should require a coverage gate as part of post-close CI improvement.

Table 11.2 — CI files (top 20 of 98 rows)

CI file path
/content/grafana/.github/workflows/actionlint.yml
/content/grafana/.github/workflows/add-to-whats-new.yml
/content/grafana/.github/workflows/alerting-swagger-gen.yml
/content/grafana/.github/workflows/alerting-update-module.yml
/content/grafana/.github/workflows/analytics-events-report.yml
/content/grafana/.github/workflows/auto-milestone.yml
/content/grafana/.github/workflows/backend-code-checks.yml
/content/grafana/.github/workflows/backend-unit-tests.yml
/content/grafana/.github/workflows/backport-trigger.yml
/content/grafana/.github/workflows/backport-workflow.yml
/content/grafana/.github/workflows/build-docker-variants.yml
/content/grafana/.github/workflows/build-go-matrix.yml
/content/grafana/.github/workflows/bump-version.yml
/content/grafana/.github/workflows/changelog.yml

CI file path`/content/grafana/.github/workflows/check-frontend-test-coverage.yml``/content/grafana/.github/workflows/cleanup-branches.yml``/content/grafana/.github/workflows/codeowners-validator.yml``/content/grafana/.github/workflows/commands.yml``/content/grafana/.github/workflows/community-release.yml``/content/grafana/.github/workflows/create-next-release-branch.yml`**11.5 Coverage Artifacts**

No coverage artifacts are recorded in this scan. This is consistent with the reported `coverage_pct` = not quantified figure: the CI surface does not publish a coverage report that the scanner could consume. The buyer's engineering team should require the seller to publish a coverage report (e.g. via Codecov or Coveralls) and to enforce a coverage threshold as part of the post-close CI improvement plan.

11.6 M&A Implications

The maintenance pillar's unverified status is the most consequential finding in this section. Because no files were scanned, the buyer cannot rely on the staleness figure (which reads 0) — it is an artefact of the scanner configuration, not a clean result. The buyer should commission an independent asset-staleness assessment covering the same file scope as the complexity scan (16,662 files) and should require the seller to remediate any neglected-file finding as a pre-close condition.

The CI maturity figure is favourable in workflow count (98 workflows) but unfavourable in gate strictness (medium, not high) and reported coverage (not quantified). The buyer's engineering team should treat the CI improvement plan as a price-adjustment lever sized against the `test_investment` line item (\$20,400) plus an additional allowance for the coverage-tooling gap.

12. AI/ML Footprint

12.1 Introduction

The AI/ML surface of the asset triggers distinct regulatory obligations and creates model-licensing and training-data IP risk that is materially different from conventional open-source risk. The pillar risk is informational, which is the most favourable rating — but the informational rating reflects the absence of bundled model files rather than the absence of AI/ML surface area. Framework and SDK hits indicate production AI/ML integration that the buyer's counsel should review against the EU AI Act, model-licensing terms, and training-data IP risk.

12.2 Key Figures

AI/ML source files scanned: 11,696. Framework groups in use: 1. SDK groups in use: 5. Bundled model files: 0. Production model files: 0. Unlicensed model files: 0.

12.3 Framework Hits

One framework group is in use: Huggingface, with 183 hits. Huggingface is the dominant open-source model-hosting ecosystem; the hits indicate that the codebase references Huggingface libraries, model identifiers, or both. The buyer's AI/ML team should validate whether any Huggingface model is actually loaded into production runtime (the `bundled_model_files = 0` result suggests not, but the SDK calls may load models dynamically).

Table 12.1 — Framework hits

Framework	Hits
Huggingface	183

12.4 SDK Hits

Five SDK groups are in use: Anthropic (1), AWS Bedrock (21), Azure OpenAI (113), Cohere (9), and OpenAI (5). The Azure OpenAI dominance (113 hits) is the most material signal — it indicates production integration with Azure OpenAI Service, which carries Azure-specific contractual and data-residency obligations. The 21 AWS Bedrock hits indicate additional multi-cloud LLM usage. The 1 Anthropic and 5 OpenAI hits are minor and may be experimental.

Table 12.2 — SDK hits

SDK	Hits
Anthropic	1
AWS Bedrock	21
Azure OpenAI	113
Cohere	9
OpenAI	5

12.5 M&A Implications

The AI/ML surface is informational in severity because no bundled model files are detected — the codebase does not ship model artifacts. This is a positive signal: the buyer does not inherit model-licensing or training-data IP risk from bundled models. However, the SDK hits indicate the codebase makes runtime calls to external LLM providers (Azure OpenAI, AWS Bedrock, Anthropic, Cohere, OpenAI), which creates two distinct post-close obligations. First, the buyer must inherit or re-negotiate the seller's contracts with each LLM provider — Azure OpenAI in particular may carry enterprise-tier commitments that affect pricing and data-handling. Second, the buyer's counsel should review the seller's prompt-management and content-moderation practices against the EU AI Act and any applicable sectoral regulation (e.g. HIPAA for healthcare data sent to LLMs).

The Huggingface framework hits should be reviewed to confirm whether any model is loaded at runtime; if so, the model license and training-data provenance must be verified. The five license findings in Section 4 overlap with this section because the AI/ML surface area triggers license review for the SDKs and frameworks in use.

© MTD Services

13. Technology Stack & Lifecycle Posture

13.1 Introduction

The base-layer inventory records which technologies are in use, their lifecycle status, and any end-of-life or legacy exposure. A clean active stack is a positive value driver and reduces modernization capital. The structural-not-runtime caveat of technology detection is material to warranty representations: the buyer's counsel should not rely on the active rating as a runtime verification; the EOL pillar performs that verification against endoflife.date.

13.2 Key Figures

Technologies total: 8. EOL technology count: 0. Legacy technology count: 0. Active technologies: 8. EOL count (runtime verification): 0.

13.3 Technologies by Lifecycle

Table 13.1 — Technologies by lifecycle

Lifecycle	Count
Active	8

13.4 Technology Inventory

Eight technologies are detected, all active. The stack is dual-language Go (backend) and JavaScript/TypeScript (frontend), with Docker and Docker Compose for deployment, Angular in the frontend (likely legacy code, given the React-based grafana-ui packages observed elsewhere), Python pip in the devenv, and Go module checksums for supply-chain integrity. The detection confidence varies: Go, Docker, Docker Compose, and JavaScript/Node.js are detected at 1.0 confidence; Angular, JavaScript/Node.js (Yarn), and Python (pip) are detected at 0.6-0.7 confidence, indicating the detection is based on indirect signals rather than explicit declarations.

Table 13.2 — Technology inventory

Technology	Lifecycle	Confidence
Angular	active	0.7
Docker	active	1.0
Docker Compose	active	1.0
Go	active	1.0
Go (module checksums)	active	1.0
JavaScript/Node.js	active	1.0
JavaScript/Node.js (Yarn)	active	0.6
Python (pip)	active	0.6

13.5 Runtime EOL Inventory

One runtime is checked: golang go 1.27.2, which is not end-of-life (latest is 1.27.2). The Go runtime is current. The endoflife.date source is used for the runtime EOL check; the buyer's platform team should integrate continuous EOL monitoring into the post-close CI pipeline.

Table 13.3 — Runtime EOL inventory

Product	Runtime	Version	Is EOL	Latest
golang	go	1.27.2	No	1.27.2

13.6 M&A Implications

The clean active stack is a positive value driver. The buyer's counsel should treat the active rating as structural-detection basis, not as runtime verification; the runtime EOL check confirms Go 1.27.2 is current but does not verify that the deployed runtime matches the declared runtime. The buyer's engineering team should require evidence of the deployed runtime version as part of operational handover. The Angular detection is notable because it suggests the codebase carries legacy frontend code alongside the React-based grafana-ui packages; the buyer's frontend team should commission a migration assessment.

14. Consolidated Risk Register & Top Risks

14.1 Introduction

The single integrated view of every material risk is ranked by severity, with impact, file and line evidence where applicable, and ownership mapping to the relevant pillar. The risk register maps directly to the disclosure schedule, the indemnity-cap allocation, and the post-close remediation tracker in the acquisition agreement. The consolidated top-risks, major-risks, pillar-classification, and deal-breaker registers below are stored ground truth.

14.2 Consolidated Top Risks

Table 14.1 — Consolidated top risks

Findin g ID	Pillar	Title	Sever ity	Evide nce state	Imp act	File	Cost (USD)
F-complex ity-006	Comple xity	GetRoutes	Critica l	Detecte d, not verified	Critic al	pkg/registry/apis/dashboard/snapshot /routes.go	Not quantif ied
F-complex ity-034	Comple xity	NewAPISe rvice	Critica l	Detecte d, not verified	Critic al	pkg/registry/apis/iam/register.go	Not quantif ied
F-complex ity-019	Comple xity	Changes	Critica l	Detecte d, not verified	Critic al	pkg/registry/apis/provisioning/jobs/s ync/changes.go	Not quantif ied
F-retentio n-021	Retentio n	Adam Yeats	Critica l	Inferre d	Critic al	Not quantified	Not quantif ied
F-retentio n-035	Retentio n	Alex Spencer	Critica l	Inferre d	Critic al	Not quantified	Not quantif ied
F-retentio n-001	Retentio n	Alex Khomenko	Critica l	Inferre d	Critic al	Not quantified	\$316,4 00
F-debt- 002	Debt	fixme	High	Detecte d, not verified	High	eslint.config.js:624	Not quantif ied
F-debt- 003	Debt	fixme	High	Detecte d, not verified	High	eslint.config.js:638	Not quantif ied
F-licen se-006	License	(repo- level)	High	Detecte d, not verified	High	LICENSE	Not quantif ied
F-debt- 001	Debt	fixme	High	Detecte d, not verified	High	eslint.config.js:40	\$7,530

Three complexity findings (*GetRoutes*, *NewAPIService*, *Changes*) are in *pkg/registry* and *pkg/services* API surface — these are the highest-priority refactoring targets because they sit on the request-handling hot path. Three retention findings identify critical-flight-risk contributors; Alex Khomenko is the only one with a quantified remediation cost (\$316,400) tied to the knowledge-transfer line item.

14.3 Major Risks Register

Table 14.2 — Major risks register

Pillar	Area	Risk	Headline metric	Unverified
Entanglement	Architecture	Critical	total_cycles: 4, max_cycle_length: 1445, cross_layer_violations_count: 19887	No
Complexity	Engineering	Critical	ProvideService	No
Debt	Engineering	High	fixme	No
Integration	Engineering	High	integration_risk_score: 10.0, proprietary_coupling_count: 509, total_findings: 521	No
Coverage	Engineering	High	modules_analyzed: 2506, high_value_gaps: 592, effective_insured_value: 1.0	No
Test Deficit	Engineering	High	total_modules: 2506, modules_below_threshold: 1882, overall_test_ratio: 0.1526	No
License	Legal & Compliance	High	envtpl	No
IP Ownership	Legal & Compliance	High	total_authors: 3217, external_author_count: 2319, external_blamed_line_pct: 0.7723	No
Retention	People	High	Alex Khomenko	No
Secrets	Security	Critical	candidate_count: 427, high_confidence_count: 63, history_only_count: 345	Yes
CVE	Security	High	packages_queried: 1789, unresolved_packages: 19, cve_count: 154	Yes

14.4 Pillar Classification Register

The pillar classification register maps each pillar to a classification (Critical Risk, Major Risk, Minor Risk, Acceptable, or Deal-Breaker) and a health score. The classification drives the conditions in Section 2; the health score communicates the pillar-level posture.

Table 14.3 — Pillar classification register

Pillar	Area	Risk	Classification	Health score	Unverified
AI/ML	AI/ML Exposure	Informational	Informational Finding	90	No
Attack Surface	Security	Medium	Manageable Risk	65	No
CI Maturity	Process	Medium	Manageable Risk	35	No

Pillar	Area	Risk	Classification	Health score	Unverified
Complexity	Engineering	Critical	Major Risk	15	No
Coverage	Engineering	High	Major Risk	40	No
CVE	Security	High	Major Risk	50	Yes
Debt	Engineering	High	Major Risk	40	No
Dependency	Supply Chain	Medium	Manageable Risk	65	No
Doc Staleness	Process	Low	Informational Finding	85	No
Entanglement	Architecture	Critical	Major Risk	15	No
EOL	Platform	Low	Informational Finding	85	No
IaC	Security	Medium	Manageable Risk	65	No
Integration	Engineering	High	Major Risk	40	No
IP Ownership	Legal & Compliance	High	Major Risk	40	No
Key Person	People	Low	Informational Finding	85	No
License	Legal & Compliance	High	Major Risk	40	No
Maintenance	Engineering	Low	Unverified	50	Yes
Privacy	Legal & Compliance	Informational	Informational Finding	95	No
Retention	People	High	Major Risk	40	No
Secrets	Security	Critical	Deal-Breaker	50	Yes

Two pillars carry the lowest health score of 15: Complexity (critical) and Entanglement (critical). Three pillars are unverified: CVE (high, 50), Maintenance (low, 50), Secrets (critical, 50). The Secrets pillar is the single Deal-Breaker classification; its unverified status is the most material epistemic gap in the report.

14.5 Deal-Breaker Register

Table 14.4 — Deal-breaker register

Pillar	Area	Risk	Trigger	Unverified
Secrets	Security	Critical	candidate_count: 427, high_confidence_count: 63, history_only_count: 345	Yes

The deal-breaker trigger fires on Secrets because the pillar returns critical severity under the decision model. Because the pillar is unverified (partial coverage, 24 path-excluded candidates not scanned), the deal-breaker is recommended for validation rather than asserted as final. The buyer must close the coverage gap before relying on the deal-breaker in negotiation.

Part IV — Scope, Confidence & Limitations

15. Confidence, Scope Limitations & Material Unknowns

15.1 Introduction

The epistemic boundaries of this report prevent over-reliance on the headline numbers. Coverage caveats size the warranty and indemnity chapter, the working-group escrow, and the credibility of the seller's vulnerability-management claims. The integrity block, confidence ledger, per-pillar assessment postures, and taint summary are replayed here verbatim from the ground truth.

15.2 Key Figures

Integrity status: warn. Integrity error count: 0. Integrity warning count: 8. Confidence coverage: 86.4%. Confidence risk signal: 50.8%. Confidence signal count: 19 of 22. Confidence degraded pillars: 3. Taint flows found: 0. Taint pass bounded: false.

15.3 Integrity Issues

Eight integrity warnings are recorded. Five are critical_pillar_no_findings warnings for pillars that are high or critical but render no item-level findings — the reading guide must state the aggregate basis (summary metrics) for these pillars. Three are unverified_pillar warnings for CVE, Maintenance, and Secrets, each with the specific reason coverage was incomplete. No errors are recorded.

Table 15.1 — Integrity issues

Tier	Code	Subject	Message
Warn	critical_pillar_no_findings	pillars.coverage	Pillar 'coverage' is high but renders no item-level findings.
Warn	critical_pillar_no_findings	pillars.entanglement	Pillar 'entanglement' is critical but renders no item-level findings.
Warn	critical_pillar_no_findings	pillars.integration	Pillar 'integration' is high but renders no item-level findings.
Warn	critical_pillar_no_findings	pillars.ip_ownership	Pillar 'ip_ownership' is high but renders no item-level findings.
Warn	critical_pillar_no_findings	pillars.test_deficit	Pillar 'test_deficit' is high but renders no item-level findings.
Warn	unverified_pillar	pillars.cve	Pillar 'cve' is partial — conclusions UNVERIFIED.
Warn	unverified_pillar	pillars.maintenance	Pillar 'maintenance' is not_assessed — conclusions UNVERIFIED.
Warn	unverified_pillar	pillars.secrets	Pillar 'secrets' is partial — conclusions UNVERIFIED.

The five critical_pillar_no_findings warnings require the buyer's reader to interpret the high/critical ratings on coverage, entanglement, integration, IP ownership, and test_deficit as aggregate-metric-based rather than item-finding-

based. The three unverified_pillar warnings require the buyer to validate CVE, Maintenance, and Secrets independently before close.

15.4 Unverified Pillars

Three pillars are unverified: CVE, Maintenance, and Secrets. Each is named in the executive brief and in the conditions for acquisition (Section 2). The buyer must verify each independently before close; absence of a finding in those domains is absence of coverage, not absence of risk.

- CVE — partial. 19 package requirements could not be resolved to a version (no lockfile / unpinned), so the advisory check covered only the 1,789 resolvable packages; 'no critical CVEs' applies to that queried population only.
- Maintenance — not_assessed. No files were scanned by the asset-staleness scanner — maintenance not assessed.
- Secrets — partial. 24 path-excluded candidate paths were not scanned; 16,662 files were scanned.

15.5 Per-Pillar Assessment Posture

Table 15.2 — Per-pillar assessment posture

Pillar	Area	Risk	Classification	Health score	Unverified
AI/ML	AI/ML Exposure	Informational	Informational Finding	90	No
Attack Surface	Security	Medium	Manageable Risk	65	No
CI Maturity	Process	Medium	Manageable Risk	35	No
Complexity	Engineering	Critical	Major Risk	15	No
Coverage	Engineering	High	Major Risk	40	No
CVE	Security	High	Major Risk	50	Yes
Debt	Engineering	High	Major Risk	40	No
Dependency	Supply Chain	Medium	Manageable Risk	65	No
Doc Staleness	Process	Low	Informational Finding	85	No
Entanglement	Architecture	Critical	Major Risk	15	No
EOL	Platform	Low	Informational Finding	85	No
IaC	Security	Medium	Manageable Risk	65	No
Integration	Engineering	High	Major Risk	40	No
IP Ownership	Legal & Compliance	High	Major Risk	40	No
Key Person	People	Low	Informational Finding	85	No
License	Legal & Compliance	High	Major Risk	40	No

Pillar	Area	Risk	Classification	Health score	Unverified
Maintenance	Engineering	Low	Unverified	50	Yes
Privacy	Legal & Compliance	Informational	Informational Finding	95	No
Retention	People	High	Major Risk	40	No
Secrets	Security	Critical	Deal-Breaker	50	Yes

15.6 CVE Scope Notes

The CVE scope note records the partial-coverage reason: 19 package requirements could not be resolved to a version (no lockfile / unpinned), so the advisory check covered only the 1,789 resolvable packages; 'no critical CVEs' applies to that queried population only. The buyer's security team should re-query the OSV feed after the seller provides the missing lockfiles or pins the unpinned dependencies.

Table 15.3 — CVE scope notes

Domain	Scope note
CVE	19 package requirements could not be resolved to a version (no lockfile / unpinned), so the advisory check covered only the 1,789 resolvable packages; 'no critical CVEs' applies to that queried population only.

15.7 Coverage Gaps by Pillar

Table 15.4 — Coverage gaps by pillar

Pillar	Assessment status	Reason	Population	Scope note
CVE	Partial	Coverage gap	1,789	19 package requirements unresolved to a version (no lockfile / unpinned); advisory check covered 1,789 resolvable only.
Maintenance	Not assessed	Coverage gap	0	No files were scanned by the asset-staleness scanner; maintenance not assessed.
Secrets	Partial	Coverage gap	16,662	24 path-excluded candidate paths not scanned; 16,662 files scanned.

A gap is not a clean result: it means the question was not answered. The buyer must close each gap before relying on the corresponding pillar's verdict in negotiation.

15.8 Out-of-Scope Evidence Register

Eight evidence domains are not assessed by a static, offline repository scan. Each is stated as an explicit unassessed boundary with the independent evidence the buyer must obtain. Disclosure, not a measurement. The buyer's counsel should commission each item as part of pre-signing diligence; the absence of independent evidence in any of these domains is a warranty risk that should be sized into the indemnity chapter.

Table 15.5 — Out-of-scope evidence register

Domain	Status	Reason	Independent evidence
Runtime & operational behaviour	Not assessed	Static repository scan only; the target's code and systems are never executed, so runtime behaviour and production incidents are not observed.	Runtime traces, incident history, SLO / error-budget records.
Network perimeter & OT boundaries	Not assessed	Firewall / security-group rules and OT segmentation are not verified against a live environment; committed IaC text is read as candidate configuration only.	Live firewall / security-group export, network diagrams, OT segmentation policy.
External attack surface (ports, DNS)	Not assessed	No active reconnaissance is performed; live port inventories and historical DNS posture are not queried.	Independent external port scan and DNS-history report.
Identity & access controls	Not assessed	MFA enforcement, privileged-access-management logs and contractor offboarding are operational controls outside a code scan.	IAM / MFA policy export, PAM audit logs, offboarding attestation.
Data resilience & recovery	Not assessed	Backup validation, point-in-time-recovery testing and migration governance are operational processes not exercised.	Backup / restore test reports, PITR drill evidence, migration runbooks.
Delivery assurance (CI & performance)	Not assessed	Only committed CI config and artifacts are read; live pass rates, flakiness, and formal load / stress and capacity testing are not observed.	CI run history, flakiness metrics, load-test and capacity reports.
Legal instruments & contracts	Not assessed	Executed contributor assignment agreements, employment / contractor terms and vendor contracts are legal artifacts, not code.	Signed CLAs, IP-assignment and contractor agreements, vendor DPAs.
Runtime dependency & vulnerability freshness	Not assessed	Dependency vulnerability / version data is a point-in-time snapshot (OSV); continuous monitoring and deploy-time enforcement are not assessed.	Continuous SCA / SBOM monitoring feed and deploy-time gate evidence.

15.9 Taint Analysis Summary

Taint analysis found 0 flows. The pass was not bounded, meaning the analysis ran but did not establish an exhaustive bound on the taint-flow surface. The buyer's security team should treat the zero-flow result as a partial coverage signal rather than as a confirmed absence of exploitable flows; an independent dynamic taint analysis (e.g. via runtime instrumentation) should be commissioned as part of pre-signing diligence.

Table 15.6 — Taint summary

Metric	Value
Bounded	false
Total flows	0

© MTD Services

Part V — Methodology, Conventions & Reproducibility

16. Reading Notes & Honesty Conventions

16.1 Introduction

The conventions that govern how every other section must be read are fixed and target-agnostic. No figure in this section is instance-specific, and none of it is evidence in its own right. A reader who applies these conventions cannot misread a partial scan as a clean one, a scanner signal as a confirmed exposure, or a qualitative deal mechanic as a priced number.

16.2 Assessment Coverage

Assessment status is assessed, partial, or not_assessed per pillar. Only assessed pillars support conclusions; partial / not_assessed pillars are demoted to informational, labelled UNVERIFIED, and never read as a clean bill of health. Assessment state (NOT_ASSESSED, PARTIALLY_ASSESSED, ASSESSED_NO_FINDINGS, ASSESSED_WITH_FINDINGS, ERROR) is the five-value trust vocabulary that accompanies the legacy three-value status. A low risk with PARTIALLY_ASSESSED must be read as 'incomplete coverage', not 'no problem'.

Population is the evidence count each verdict rests on (files scanned, packages queried, modules in cycles, etc.). A low or missing population flags a coverage gap instead of hiding it. A zero population never reads as clean.

16.3 Evidence Honesty

Evidence state is the per-finding honesty label, attached to every material finding and shown in the Section 14 register: Confirmed, Detected-not-verified, Inferred, Partially assessed, Unassessed, Conflicting, or Unsupported. Scanner signals are never auto-confirmed. The finding ID (F-<pillar>-<rank>) is the stable handle used by the narrative, the register, the workbook, and the ledger; a body section cites the ID, it never re-renders the finding.

The contradiction ledger (Appendix R) leads every material conflict with its status (resolved, by-design, or unresolved) and decision impact; unresolved entries discount the stated confidence. It never picks a side silently. Confidence = $20 + 40 \times \text{coverage} + 40 \times \text{risk_signal}$, capped at 20 when coverage is zero, floored at 60 when the verdict is DO_NOT_ACQUIRE. Coverage is the share of pillars with usable signal; risk signal blends weighted pillar risk with the financial model. Unverified pillars depress both and are named in the executive brief.

16.4 Currency of Absence

Four markers name a value this scan did not establish. None is a zero, and each states a different kind of absence, so an empty cell is never read as a clean result:

- not quantified — the model could compute a number but a stored input is missing (a Layer-2 expected loss with no financial.risk_parameters calibration; an unset escalation threshold). It never means the risk costs nothing.

- not applicable — the cell is structurally inapplicable to that row (the fixed-version of a CVE with no fix published; the commit of a secret found only in the working tree).
- not recorded — the source does not carry the value (an aggregate finding has no single line number; the scanner never captured a commit).
- not assessed — the value was not established because coverage was incomplete (a named coverage gap).

NOT_QUANTIFIED is additionally a stored assessment state on the economic layers of Section 3, distinct from the five coverage states under Assessment Coverage. The same rule holds: absent is never zero, and an unquantified line is named rather than priced at 0.

16.5 Deal-Mechanic Vocabulary

Every condition in Section 2 carries exactly one of three deal-mechanic tags, declared where the condition is authored (evidence 2.13). The wording of a condition is a qualitative mechanic: no escrow amount, holdback, warranty cap, or indemnity ceiling is asserted anywhere in this report. Sizing those is deal counsel's call.

- Condition precedent — must be satisfied or proven before close, or the deal does not sign as structured.
- Price-adjustment lever — a funded or escrowed work item that moves value rather than blocking close.
- Warranty / representation — a seller statement whose breach is an indemnity question, not a work plan.

16.6 Severity and Ranking

- Risk level — critical, high, medium, low, or informational, demoted to informational under partial coverage. `derived_risk_level` preserves the scanner's own view.
- Health score — 0-100 per pillar, demoted to 50 for an unfinished scan so that incomplete coverage never presents as a strong pillar.
- Classification — Critical Risk, Major Risk, Minor Risk, or Acceptable, assigned in the Section 14 register and driving the conditions in Section 2.

16.7 Known Limits of This Method

EOL reconciliation: `tech_stack` counts offline repo technology lifecycle markers; the `eol` pillar verifies runtimes / dependencies against `endoflife.date`. The two are reconciled — `eol_count` is the union, so the pillars can never contradict each other. The buyer's counsel should rely on the `eol` pillar for runtime-verification evidence, not on the `tech_stack` structural-detection rating.

Static source analysis: this is a source scan. It does not establish runtime behaviour, production incidents, or anything needing access to systems, personnel, or contracts. The Out-of-Scope Evidence Register (Section 15.5) enumerates the eight evidence domains the buyer must obtain independently.

No negotiated positions: the conditions, implications, and escalation thresholds recorded here are the model's deterministic output from stored evidence. They are a starting position for negotiation, not a legal opinion. The buyer's counsel should treat each condition as a draft for negotiation, not as a final term.

© MTD Services

Appendices

Appendix A — Methodology, Scope & Scan Configuration

This appendix records the methodology and configuration of the scan that produced the underlying ground truth, so the narrative is reproducible: exact version, scan mode, indexed surface, per-pillar posture, and step timings. Every figure is reproduced from the stored payload.

A.1 Report Metadata

Table A.1 — Report metadata

Field	Value
Report ID	TDD-20261016-060430
Scan date	2026-10-16T07:15:51.747366+00:00
Target	Grafana
Scanned path	grafana
Indexed symbols	16,662
Report version	Not quantified
Elapsed seconds	4,281.52

A.2 Scan Mode

Table A.2 — Scan mode

Parameter	Value
deal_thesis	all
offline	false
scan_history	true
taint	true
target_company	Grafana
tdd_report	true
workers	2

deal_thesis = all means all six deal theses are evaluated; scan_history = true means git-history candidates are scanned (345 history-only secrets); taint = true means the taint analysis ran (0 flows found, pass not bounded); workers = 2 is the parallelism setting.

A.3 Pillar Posture Register

Table A.3 — Pillar posture register

Pillar	Area	Risk level	Health	Assessment	Top risks
AI/ML	AI/ML Exposure	Informational	90	Assessed	0
Attack Surface	Security	Medium	65	Assessed	50
CI Maturity	Process	Medium	35	Assessed	0
Complexity	Engineering	Critical	15	Assessed	50
Coverage	Engineering	High	40	Assessed	0
CVE	Security	Informational	50	Partial	0
Debt	Engineering	High	40	Assessed	50
Dependency	Supply Chain	Medium	65	Assessed	0
Doc Staleness	Process	Low	85	Assessed	0
Entanglement	Architecture	Critical	15	Assessed	0
EOL	Platform	Low	85	Assessed	0
IaC	Security	Medium	65	Assessed	1
Integration	Engineering	High	40	Assessed	0
IP Ownership	Legal & Compliance	High	40	Assessed	0
Key Person	People	Low	85	Assessed	50
License	Legal & Compliance	High	40	Assessed	50
Maintenance	Engineering	Informational	50	Not assessed	0
Privacy	Legal & Compliance	Informational	95	Assessed	1
Retention	People	High	40	Assessed	50
Secrets	Security	Informational	50	Partial	0
Tech Stack	Architecture	Low	85	Assessed	0
Test Deficit	Engineering	High	40	Assessed	0

A.4 Step Timings

Table A.4 — Step timings

Step	Seconds
index	240.61
pillars	4,003.63
deep_index	5.783
taint	20.502
financial	0.364
decision	0.001

The pillars step dominates at 4,003.63 seconds (over 66 minutes) — expected given the breadth of pillar scanners. The financial step is 0.364 seconds because the model is deterministic once the pillar evidence is loaded; the decision step is 0.001 seconds for the same reason.

© MTD Services

Appendix B — Metric Definitions & Financial Calibration

Metric definitions used throughout the narrative are fixed and target-agnostic. Cyclomatic and cognitive complexity are measured per symbol; bus factor is the reciprocal of sole-contributor concentration; debt density is normalised per thousand lines; and remediation hours-per-unit (HPU) per cost category is calibrated by the model. The calibration tables themselves live in Section 3 (the single financial home) and are cited there, not duplicated here, so a figure appears in exactly one place. This appendix references Section 3 rather than reproducing its tables; the buyer's quality-of-earnings provider should consult Section 3.2 (parameters table), Section 3.4 (remediation line items), Section 3.6 (saturation model), and Section 3.7 (SQALE remediation basis) for the canonical figures.

© MTD Services

Appendix O — Financial Reproduction Fingerprint

The financial reproduction fingerprint binds the report to the exact configuration used to produce every number: same inputs in, same outputs out. Any change to a number-driving input produces a different fingerprint and a different report under a new fingerprint. The full calibration, lineage, and sensitivity detail lives in Section 3 — not re-rendered here.

Table O.1 — Reproduction fingerprint

Field	Value
Reproduction fingerprint	b607d2e6aabcc186eeb9fb69a27d29d10ab901b978e50d332fec58eb18ce7395
Economic model fingerprint (0.3.0)	aba11b3a12341e602de6865ec282b34bb65952d165700979b067b826b05e006e
Repository	grafana
HEAD commit	5be6647ffe4c0ce6522387884e4ca51e9c181f10
Scan date	2026-10-16T07:15:51.747366+00:00

© MTD Ser

Appendix P — Evidence Provenance

The payload path is the single stored source the narrative's evidence derives from; key-variant fallbacks are resolved at render time and are not listed here. The workbook column names the sheet that inventories the same evidence; not applicable means no dedicated sheet carries it.

Table P.1 — Evidence provenance (every figure in this report, mapped to its source)

ID	Evidence	Source	Workbook
1.1	Board decision	decision.board_decision	Dashboard
1.2	Confidence score	decision.confidence_score	Dashboard
1.3	Decision driver	decision.escalation.driver	Dashboard
1.4	Remediation cost as % of price	decision.remediation_cost_pct_of_acquisition	Dashboard
1.5	Proposed price	decision.proposed_price	Dashboard
1.6	Total remediation cost	financial.total_remediation_cost	Dashboard
1.7	Total remediation hours	financial.total_remediation_hours	Dashboard
1.8	Valuation discount applied	financial.valuation_discount_pct	Dashboard
1.9	Post-merge integration drag	financial.post_merge_integration_drag_pct	Dashboard
1.10	Pillar register size	decision.pillar_register	Dashboard
1.11	Top risk findings	decision.top_risks	Dashboard
1.12	Major risks	decision.major_risks	Dashboard
1.13	Integrity status	integrity.status	Contents
1.14	Integrity error count	integrity.error_count	Contents
1.15	Integrity warning count	integrity.warn_count	Contents
2.1	Conditions for acquisition	decision.conditions_for_acquisition	Dashboard
2.2	Deal-breaker register	decision.deal_breakers	Dashboard
2.3	Categorical decision tier	decision.escalation.categorical_tier	Dashboard
2.4	Economic decision tier	decision.escalation.economic_tier	Dashboard
2.5	Conditions escalation threshold	decision.escalation.conditions_threshold_pct	Dashboard
2.6	No-go escalation threshold	decision.escalation.no_go_threshold_pct	Dashboard
2.7	Economic gate disputed	decision.escalation.disputed	Dashboard

ID	Evidence	Source	Workbook
2.8	Escalation driver	decision.escalation.driver	Dashboard
2.9	Per-pillar escalation rows	decision.escalation.pillars	Dashboard
2.1 0	Economic conditions threshold (model)	financial.assumptions.economic_escalation.conditions_if_above_pct	Dashboard
2.1 1	Economic no-go threshold (model)	financial.assumptions.economic_escalation.no_go_if_above_pct	Dashboard
2.1 2	Sensitivity sweep outcomes	financial.sensitivity	Dashboard
2.1 3	Condition deal-mechanic tags	decision.condition_details	Dashboard
3.1	Remediation line items	financial.line_items	Dashboard
3.2	Total remediation hours	financial.total_remediation_hours	Dashboard
3.3	Total remediation cost	financial.total_remediation_cost	Dashboard
3.4	Valuation discount applied	financial.valuation_discount_pct	Dashboard
3.5	Post-merge integration drag	financial.post_merge_integration_drag_pct	Dashboard
3.6	Hourly rate	financial.assumptions.hourly_rate	Dashboard
3.7	Complexity multiplier	financial.assumptions.complexity_multiplier	Dashboard
3.8	Valuation multiplier	financial.assumptions.valuation_multiplier	Dashboard
3.9	Integration drag factor	financial.assumptions.integration_drag_factor	Dashboard
3.1 0	Productive hours per quarter	financial.assumptions.productive_hours_per_quarter	Dashboard
3.1 1	Person-years of remediation	financial.assumptions.person_years	Dashboard
3.1 2	Remediation cost CI	financial.assumptions.remediation_cost_confidence_interval	Dashboard
3.1 3	Conditions threshold (model)	financial.assumptions.economic_escalation.conditions_if_above_pct	Dashboard
3.1 4	No-go threshold (model)	financial.assumptions.economic_escalation.no_go_if_above_pct	Dashboard
3.1 5	Valuation discount cap	financial.assumptions.valuation_discount_cap_pct	Dashboard
3.1 6	Integration drag cap	financial.assumptions.integration_drag_cap_pct	Dashboard
3.1 7	Aggregate hours cap	financial.assumptions.aggregate_cap	Dashboard

ID	Evidence	Source	Workbook
3.1 8	Saturation model	financial.assumptions.saturation_model	Dashboard
3.1 9	Line-item basis (HPU per category)	financial.assumptions.line_item_basis	Dashboard
3.2 0	SQALE remediation basis	financial.assumptions.sqale_remediation_basis	Dashboard
3.2 1	Sensitivity sweep details	financial.sensitivity	Dashboard
3.2 2	Financial lineage	financial.lineage	Dashboard
3.2 3	Remediation cost as % of price	decision.remediation_cost_pct_of_acquisition	Dashboard
3.2 4	Economic model fingerprint (0.3.0)	financial.economic_layers.economic_layers_fingerprint	Dashboard
3.2 5	Risk valuation lines	financial.economic_layers.layer2_risk.lines	Dashboard
3.2 6	Aggregate expected loss before	financial.economic_layers.layer2_risk.aggregate_expected_loss_before	Dashboard
3.2 7	Aggregate residual expected loss	financial.economic_layers.layer2_risk.aggregate_residual_expected_loss	Dashboard
3.2 8	Aggregate risk-reduction value	financial.economic_layers.layer2_risk.aggregate_risk_reduction_value	Dashboard
3.2 9	Quantified risk lines	financial.economic_layers.layer2_risk.quantified_count	Dashboard
3.3 0	Not-quantified risk lines	financial.economic_layers.layer2_risk.not_quantified_count	Dashboard
3.3 1	Scenario branches (0.3.0)	financial.economic_layers.layer3_scenario.branches	Dashboard
3.3 2	Weighted expectation across scenarios	financial.economic_layers.layer3_scenario.weighted_expectation	Dashboard
3.3 3	Scenario-based technology VaR label	financial.economic_layers.layer3_scenario.var_label	Dashboard
3.3 4	Deal components (never collapsed)	financial.economic_layers.layer4_deal.components	Dashboard
3.3 5	Executive deal-bridge rows	financial.economic_layers.layer4_deal.bridge	Dashboard
3.3 6	Double-counting ledger figures	financial.economic_layers.p0_double_counting.figures	Dashboard
3.3 7	Double-counting ledger clean verdict	financial.economic_layers.p0_double_counting.clean	Dashboard

ID	Evidence	Source	Workbook
3.3 8	Justified overlapping keys	financial.economic_layers.p0_double_counting.justified_overlapping_keys	Dashboard
3.3 9	Categories not costed this scan	financial.line_items	Dashboard
3.4 0	Per-line-item threshold breach view	financial.line_items	Dashboard
3.4 1	Downside exposure range and percentile VaR	financial.economic_layers.downside	Dashboard
3.4 2	Deal economics headline reconciliation	financial.economic_layers.layer4_deal	Dashboard
4.1	License findings inventory	pillars.license.raw.findings	License Contamination
4.2	Per-package detected licenses	pillars.license.raw.findings	License Contamination
4.3	Viral license count	pillars.license.raw.viral_count	License Contamination
4.4	Restrictive license count	pillars.license.raw.restrictive_count	License Contamination
4.5	Unknown license count	pillars.license.raw.unknown_count	License Contamination
4.6	Licensed packages total	pillars.license.raw.total_packages	License Contamination
4.7	Contamination chains	pillars.license.raw.contamination_chains	License Contamination
4.8	License clause findings	pillars.license.raw.clauses	License Contamination
4.9	IP ownership metrics	pillars.ip_ownership.summary	IP Ownership
4.1 0	IP ownership attribution rows	pillars.ip_ownership.raw.attributions	IP Ownership
5.1	CVE count	pillars.cve.summary.cve_count	CVEs
5.2	Critical CVE count	pillars.cve.summary.critical_cve_count	CVEs
5.3	Packages queried against advisories	pillars.cve.summary.packages_queried	CVEs
5.4	Unresolved packages	pillars.cve.summary.unresolved_packages	CVEs
5.5	Advisory source	pillars.cve.summary.source	CVEs
5.6	CVE inventory	pillars.cve.raw.cves	CVEs
5.7	Secret candidates	pillars.secrets.raw.candidates	Secrets Candidates
5.8	High-confidence secrets	pillars.secrets.summary.high_confidence_count	Secrets Candidates

ID	Evidence	Source	Workbook
5.9	Live critical secrets	pillars.secrets.summary.live_critical_count	Secrets Candidates
5.10	History-only secrets	pillars.secrets.summary.history_only_count	Secrets Candidates
5.11	Secrets by kind	pillars.secrets.summary.by_kind	Secrets Candidates
5.12	Secret candidate detail	pillars.secrets.raw.candidates	Secrets Candidates
5.13	IaC findings total	pillars.iac.summary.total_findings	IaC Findings
5.14	IaC summary metrics	pillars.iac.summary	IaC Findings
5.15	IaC findings	pillars.iac.raw.findings	IaC Findings
5.16	Attack surface candidate endpoints	pillars.attack_surface.summary.total_candidate_endpoints	Attack Surface
5.17	Unreferenced endpoints	pillars.attack_surface.summary.unreferenced_endpoints	Attack Surface
5.18	Dynamic endpoints	pillars.attack_surface.summary.dynamic_endpoints	Attack Surface
5.19	Untested candidate endpoints	pillars.attack_surface.summary.untested_candidate_endpoints	Attack Surface
5.20	Candidate exposure score	pillars.attack_surface.summary.candidate_exposure_score	Attack Surface
5.21	Candidate endpoint detail	pillars.attack_surface.raw.candidate_entry_points	Attack Surface
5.22	Privacy findings total	pillars.privacy.summary.total_findings	Privacy & Compliance
5.23	PII endpoint count	pillars.privacy.summary.pii_endpoint_count	Privacy & Compliance
5.24	Egress SDK count	pillars.privacy.summary.egress_sdk_count	Privacy & Compliance
5.25	Sensitive log count	pillars.privacy.summary.sensitive_log_count	Privacy & Compliance
5.26	Privacy findings	pillars.privacy.raw.findings	Privacy & Compliance
6.1	Direct dependency count	pillars.dependency.summary.direct_dependency_count	Dependency Packages
6.2	Pinned dependencies	pillars.dependency.summary.pinned_count	Dependency Packages

ID	Evidence	Source	Workbook
6.3	Ranged dependencies	pillars.dependency.summary.ranged_count	Dependency Packages
6.4	Unpinned dependencies	pillars.dependency.summary.unpinned_count	Dependency Packages
6.5	Pin ratio	pillars.dependency.summary.pin_ratio	Dependency Packages
6.6	Transitive resolved packages	pillars.dependency.summary.transitive_resolved_packages	Dependency Packages
6.7	Lockfiles present	pillars.dependency.summary.lockfiles_present	Dependency Packages
6.8	Manifests found	pillars.dependency.summary.manifests_found	Dependency Packages
6.9	Lockfile resolution	pillars.dependency.raw.lockfiles	Dependency Packages
6.10	Direct dependency inventory	pillars.dependency.raw.direct_dependencies	Dependency Packages
6.11	EOL runtime rows	pillars.eol.raw.eol	EOL Findings
6.12	EOL count	pillars.eol.summary.eol_count	EOL Findings
6.13	Runtimes checked	pillars.eol.summary.runtimes_checked	EOL Findings
6.14	EOL runtime detail	pillars.eol.raw.eol	EOL Findings
6.15	CVE unresolved packages (cross-ref)	pillars.cve.summary.unresolved_packages	CVEs
7.1	Symbols analyzed	pillars.complexity.summary.total_symbols_analyzed	Complex Symbols
7.2	High-complexity symbols	pillars.complexity.summary.high_complexity_count	Complex Symbols
7.3	Critical-complexity symbols	pillars.complexity.summary.critical_complexity_count	Complex Symbols
7.4	Average cyclomatic complexity	pillars.complexity.summary.avg_cyclomatic	Complex Symbols
7.5	Average cognitive complexity	pillars.complexity.summary.avg_cognitive	Complex Symbols
7.6	Complexity hotspot score	pillars.complexity.summary.complexity_hotspot_score	Complex Symbols
7.7	SQALE grade	pillars.complexity.summary.sqale_grade	Complex Symbols
7.8	SQALE remediation effort (days)	pillars.complexity.summary.sqale_remediation_effort_days	Complex Symbols

ID	Evidence	Source	Workbook
7.9	Total remediation effort (days)	pillars.complexity.summary.total_remediation_effort_days	Complex Symbols
7.10	Debt ratio	pillars.complexity.summary.debt_ratio	Complex Symbols
7.11	Duplicated LOC	pillars.complexity.summary.duplicated_loc	Complex Symbols
7.12	Duplication ratio	pillars.complexity.summary.duplication_ratio	Complex Symbols
7.13	Cyclomatic percentiles	pillars.complexity.summary.cc_percentiles	Complex Symbols
7.14	Cognitive percentiles	pillars.complexity.summary.cognitive_percentiles	Complex Symbols
7.15	Hotspot symbols	pillars.complexity.raw.complexity.symbols	Complex Symbols
7.16	Duplication groups	pillars.complexity.raw.duplication.duplication_groups	Complex Symbols
7.17	Debt markers total	pillars.debt.summary.total_markers	Debt Markers
7.18	Debt markers by type	pillars.debt.summary.by_type	Debt Markers
7.19	Debt markers by severity	pillars.debt.summary.by_severity	Debt Markers
7.20	Critical-path markers	pillars.debt.summary.critical_path_markers	Debt Markers
7.21	Debt density	pillars.debt.summary.debt_density	Debt Markers
7.22	Debt marker inventory	pillars.debt.raw.markers	Debt Markers
8.1	Modules analyzed (test deficit)	pillars.test_deficit.summary.total_modules	Test Deficit
8.2	Modules below threshold	pillars.test_deficit.summary.modules_below_threshold	Test Deficit
8.3	Overall test ratio	pillars.test_deficit.summary.overall_test_ratio	Test Deficit
8.4	Test deficit score	pillars.test_deficit.summary.test_deficit_score	Test Deficit
8.5	High regression-risk modules	pillars.test_deficit.summary.high_regression_risk_modules	Test Deficit
8.6	Test-deficit module inventory	pillars.test_deficit.raw.modules	Test Deficit
8.7	Coverage modules analyzed	pillars.coverage.summary.modules_analyzed	Coverage Gaps

ID	Evidence	Source	Workbook
8.8	Effective insured value	pillars.coverage.summary.effective_insured_value	Coverage Gaps
8.9	Value coverage ratio	pillars.coverage.summary.value_coverage_ratio	Coverage Gaps
8.10	Coverage method	pillars.coverage.summary.coverage_method	Coverage Gaps
8.11	High-value gaps	pillars.coverage.summary.high_value_gaps	Coverage Gaps
8.12	Coverage module detail	pillars.coverage.raw.modules	Coverage Gaps
8.13	High-value coverage gaps	pillars.coverage.raw.high_value_gap_modules	Coverage Gaps
9.1	Circular-dependency cycles	pillars.entanglement.summary.total_cycles	Entanglement Violations
9.2	Max cycle length	pillars.entanglement.summary.max_cycle_length	Entanglement Violations
9.3	Cross-layer violations	pillars.entanglement.summary.cross_layer_violations_count	Entanglement Violations
9.4	Modules in cycles	pillars.entanglement.summary.modules_in_cycles	Entanglement Violations
9.5	Entanglement score	pillars.entanglement.summary.entanglement_score	Entanglement Violations
9.6	Cycle inventory	pillars.entanglement.raw.cycles	Entanglement Violations
9.7	Cross-layer violation detail	pillars.entanglement.raw.cross_layer_violations	Entanglement Violations
9.8	Integration risk score	pillars.integration.summary.integration_risk_score	Serialization Risks
9.9	Schema drift risk	pillars.integration.summary.schema_drift_risk	Serialization Risks
9.10	Proprietary coupling count	pillars.integration.summary.proprietary_coupling_count	Serialization Risks
9.11	Integration findings total	pillars.integration.summary.total_findings	Serialization Risks
9.12	API contract maturity	pillars.integration.raw.api_contracts	Serialization Risks
9.13	Database coupling	pillars.integration.raw.database_coupling	Serialization Risks
9.14	Serialization risks	pillars.integration.raw.serialization_risks	Serialization Risks

ID	Evidence	Source	Workbook
9.1 5	Protocol-layer risks	pillars.integration.raw.protocol_layers	Serialization Risks
10. 1	Total authors	pillars.key_person.summary.total_authors	Key-person Risks
10. 2	Overall bus factor	pillars.key_person.summary.overall_bus_factor	Key-person Risks
10. 3	Critical key-person rows	pillars.key_person.summary.critical_count	Key-person Risks
10. 4	Key-person risk rows	pillars.key_person.raw.risks	Key-person Risks
10. 5	Key-person risk detail	pillars.key_person.raw.risks	Key-person Risks
10. 6	Module bus-factor rows	pillars.key_person.raw.modules	Key-person Risks
10. 7	Module bus-factor detail	pillars.key_person.raw.modules	Key-person Risks
10. 8	Git team signals	pillars.key_person.summary.team	Key-person Risks
10. 9	Retention total contributors	pillars.retention.summary.total_contributors	Knowledge Loss Vulnerability
10. 10	Active contributors	pillars.retention.summary.active_contributor_count	Knowledge Loss Vulnerability
10. 11	Inactive contributors	pillars.retention.summary.inactive_count	Knowledge Loss Vulnerability
10. 12	At-risk contributors	pillars.retention.summary.at_risk_count	Knowledge Loss Vulnerability
10. 13	Knowledge loss vulnerability score	pillars.retention.summary.retention_risk_score	Knowledge Loss Vulnerability
10. 14	Critical modules (retention)	pillars.retention.summary.critical_modules	Knowledge Loss Vulnerability
10. 15	Knowledge loss vulnerability detail	pillars.retention.raw.risks	Knowledge Loss Vulnerability
10. 16	At-risk contributors (model input)	financial.assumptions.informational_counts.at_risk_contributors	Dashboard
10. 17	Critical sole-maintainer modules (model input)	financial.assumptions.informational_counts.critical_sole_maintainer_modules	Dashboard
11. 1	Maintenance total files	pillars.maintenance.summary.total_files	Maintenance Hotspots
11. 2	Neglected files	pillars.maintenance.summary.neglected_count	Maintenance Hotspots

ID	Evidence	Source	Workbook
11.3	At-risk files	pillars.maintenance.summary.at_risk_count	Maintenance Hotspots
11.4	Healthy files	pillars.maintenance.summary.healthy_count	Maintenance Hotspots
11.5	Average staleness	pillars.maintenance.summary.avg_staleness	Maintenance Hotspots
11.6	Maintenance backlog score	pillars.maintenance.summary.maintenance_backlog_score	Maintenance Hotspots
11.7	Maintenance asset rows	pillars.maintenance.raw.assets	Maintenance Hotspots
11.8	Documents inventoried	pillars.doc_staleness.summary.documents_inventoried	Stale Docs
11.9	Stale documents	pillars.doc_staleness.summary.stale_documents	Stale Docs
11.10	Document staleness ratio	pillars.doc_staleness.summary.staleness_ratio	Stale Docs
11.11	Average docstring density	pillars.doc_staleness.summary.avg_docstring_density	Stale Docs
11.12	Document inventory	pillars.doc_staleness.raw.documents	Stale Docs
11.13	CI defined	pillars.ci_maturity.summary.ci_defined	CI Signals
11.14	CI files checked	pillars.ci_maturity.summary.ci_files_checked	CI Signals
11.15	CI gate strictness	pillars.ci_maturity.summary.gate_strictness	CI Signals
11.16	Tests run in CI	pillars.ci_maturity.summary.tests_run_in_ci	CI Signals
11.17	Reported coverage in CI	pillars.ci_maturity.summary.reported_coverage_pct	CI Signals
11.18	CI files	pillars.ci_maturity.raw.ci_files	CI Signals
11.19	Coverage artifacts	pillars.ci_maturity.raw.coverage_artifacts	CI Signals
12.1	AI/ML source files scanned	pillars.ai_ml.summary.source_files_scanned	AI/ML Models
12.2	Framework groups in use	pillars.ai_ml.summary.framework_groups_in_use	AI/ML Models
12.3	Framework hits	pillars.ai_ml.summary.framework_hits	AI/ML Models

ID	Evidence	Source	Workbook
12.4	SDK groups in use	pillars.ai_ml.summary.sdk_groups_in_use	AI/ML Models
12.5	SDK hits	pillars.ai_ml.summary.sdk_hits	AI/ML Models
12.6	Bundled model files	pillars.ai_ml.summary.bundled_model_files	AI/ML Models
12.7	Production model files	pillars.ai_ml.summary.production_model_files	AI/ML Models
12.8	Unlicensed model files	pillars.ai_ml.summary.unlicensed_model_files	AI/ML Models
12.9	Model file rows	pillars.ai_ml.raw.models	AI/ML Models
13.1	Technologies total	pillars.tech_stack.summary.total_technologies	Tech Stack
13.2	EOL technology count	pillars.tech_stack.summary.eol_count	Tech Stack
13.3	Legacy technology count	pillars.tech_stack.summary.legacy_count	Tech Stack
13.4	Technologies by lifecycle	pillars.tech_stack.summary.by_lifecycle	Tech Stack
13.5	Active technologies	pillars.tech_stack.summary.active_count	Tech Stack
13.6	Technology inventory	pillars.tech_stack.raw.technologies	Tech Stack
13.7	EOL count (runtime verification)	pillars.eol.summary.eol_count	EOL Findings
13.8	Runtime EOL inventory	pillars.eol.raw.eol	EOL Findings
14.1	Consolidated top risks	decision.top_risks	Dashboard
14.2	Major risks register	decision.major_risks	Dashboard
14.3	Pillar classification register	decision.pillar_register	Dashboard
14.4	Deal-breaker register	decision.deal_breakers	Dashboard
15.1	Integrity status	integrity.status	Contents
15.2	Integrity error count	integrity.error_count	Contents

ID	Evidence	Source	Workbook
15.3	Integrity warning count	integrity.warn_count	Contents
15.4	Integrity issues	integrity.issues	Contents
15.5	Unverified pillars	decision.confidence.inputs.unverified_pillars	Dashboard
15.6	Confidence coverage	decision.confidence.inputs.coverage	Dashboard
15.7	Confidence risk signal	decision.confidence.inputs.risk_signal	Dashboard
15.8	Confidence signal count	decision.confidence.inputs.signal_count	Dashboard
15.9	Confidence pillar total	decision.confidence.inputs.total_pillars	Dashboard
15.10	Confidence degraded pillars	decision.confidence.inputs.degraded	Dashboard
15.11	Per-pillar assessment posture	decision.pillar_register	Dashboard
15.12	Taint flows found	taint_summary.total_flows	Taint Summary
15.13	Taint pass bounded	taint_summary.bounded	Taint Summary
15.14	CVE scope notes	pillars.cve.scope_notes	CVEs
15.15	Coverage gaps by pillar	pillars	Not applicable
15.16	Out-of-scope evidence register	pillars	Not applicable
O1	Reproduction fingerprint	financial.fingerprint	Dashboard



Appendix R — Contradiction Ledger & Release Record

Every material conflict is listed with its status, resolution, and decision impact. Unresolved entries discount the confidence stated in the executive brief.

R.1 Contradiction C-DC-001 — Resolved

Conflict: no double-counting findings across quantified economic figures. Subjects: Remediation, Risk valuation, Scenario analysis, Deal economics. Evidence: anti-double-counting ledger. Status: resolved. Resolution: shared-registry keys show each evidence once, on multiple surfaces, never added twice. Decision impact: none.

R.2 Release Record

Table R.1 — Release record

Field	Value
Report ID	TDD-20261016-060430
Generated	2026-10-16T07:15:51.747366+00:00
Report version	0.9.2
Ledger summary	1 resolved
Scan steps	6 recorded

Appendix C — Dependency & Lockfile Inventory

C.1 Direct Dependency Inventory (top 20 of 500 rows)

The full direct dependency inventory contains 500 rows across Go modules and npm packages. The representative sample below covers the highest-priority dependencies in apps/advisor and .citools/golangci-lint; the full inventory is reproduced in the workbook sheet Dependency Packages.

Table C.1 — Direct dependency inventory (top 20 of 500 rows)

Name	Specified	Pin ned	Scop e	Ecosy stem	Manifest
4d63.com/gocheckcompilerdirectives	v1.4.0	No	go.mo d	Go	.citools/src/golangci-lint/go.mod
4d63.com/gochecknoglobals	v0.2.2	No	go.mo d	Go	.citools/src/golangci-lint/go.mod
cel.dev/expr	v0.25.3	No	go.mo d	Go	apps/advisor/go.mod
charm.land/lipgloss/v2	v2.0.6	No	go.mo d	Go	.citools/src/golangci-lint/go.mod
cloud.google.com/go/compute/metadata	v0.9.0	No	go.mo d	Go	apps/advisor/go.mod
codeberg.org/chavacava/garif	v0.2.1	No	go.mo d	Go	.citools/src/golangci-lint/go.mod
codeberg.org/polyfloyd/go-errorlint	v1.9.0	No	go.mo d	Go	.citools/src/golangci-lint/go.mod
cuelabs.dev/go/oci/ociregistry	v0.0.0-20250722084951-074d06050084	No	go.mo d	Go	.citools/src/cue/go.mod
cuelang.org/go	v0.15.4	No	go.mo d	Go	.citools/src/cue/go.mod
dario.cat/mergo	v1.0.2	No	go.mo d	Go	.citools/src/air/go.mod
dev.gaijin.team/go/exhauststruct/v4	v4.0.0	No	go.mo d	Go	.citools/src/golangci-lint/go.mod
dev.gaijin.team/go/exhauststruct/v5	v5.2.0	No	go.mo d	Go	.citools/src/golangci-lint/go.mod
dev.gaijin.team/go/golib	v0.8.1	No	go.mo d	Go	.citools/src/golangci-lint/go.mod
filippo.io/edwards25519	v1.2.0	No	go.mo d	Go	apps/advisor/go.mod
github.com/4meepo/tagalign	v1.4.4	No	go.mo d	Go	.citools/src/golangci-lint/go.mod
github.com/Abirdcfly/dupword	v0.1.8	No	go.mo d	Go	.citools/src/golangci-lint/go.mod

Name	Specified	Pin ned	Scop e	Ecosy stem	Manifest
github.com/AdminBenni/iota-mixing	v1.0.0	No	go.mo d	Go	.citools/src/golangci-lint/go.mod
github.com/air-verse/air	v1.62.0	No	go.mo d	Go	.citools/src/air/go.mod
github.com/alecthoas/chroma/v2	v2.27.0	No	go.mo d	Go	.citools/src/golangci-lint/go.mod
github.com/alecthoas/go-check-sumtype	v0.5.1-0.20260828200218-ae6904d28606	No	go.mo d	Go	.citools/src/golangci-lint/go.mod

C.2 Lockfile Resolution (full 50 lockfiles)

The full lockfile resolution table covers all 50 lockfiles in the repository. The root go.sum (3,721 resolved packages) and yarn.lock (3,253 resolved packages) dominate; the apps/* subdirectories each carry their own go.sum, indicating a multi-module Go workspace. The buyer's supply-chain team should review the lockfile-resolution pattern to understand the build's dependency-resolution surface.

Table C.2 — Lockfile resolution (full 50 rows)

Lockfile	Resolved packages
.citools/src/air/go.sum	210
.citools/src/cue/go.sum	72
.citools/src/golangci-lint/go.sum	567
.citools/src/govulncheck/go.sum	22
.citools/src/lefthook/go.sum	108
.citools/src/swagger/go.sum	149
apps/advisor/go.sum	1,757
apps/alerting/alertenrichment/go.sum	98
apps/alerting/alertrulequality/go.sum	96
apps/alerting/notifications/go.sum	300
apps/alerting/rules/go.sum	236
apps/annotation/go.sum	236
apps/collections/go.sum	170
apps/correlations/go.sum	236
apps/dashboard/go.sum	381
apps/dashvalidator/go.sum	1,747
apps/example/go.sum	252
apps/folder/go.sum	170

Lockfile	Resolved packages
apps/iam/go.sum	236
apps/live/go.sum	236
apps/logsdrilldown/go.sum	236
apps/playlist/go.sum	236
apps/plugins/go.sum	1,480
apps/preferences/go.sum	170
apps/provisioning/go.sum	284
apps/quotas/go.sum	240
apps/scope/go.sum	100
apps/secret/go.sum	178
apps/shorturl/go.sum	252
devenv/docker/blocks/prometheus_high_card/go.sum	36
devenv/docker/blocks/prometheus_utf8/go.sum	36
go.sum	3,721
hack/go.sum	22
pkg/apimachinery/go.sum	148
pkg/apiserver/go.sum	266
pkg/codegen/go.sum	146
pkg/infra/features/go.sum	196
pkg/infra/log/go.sum	46
pkg/infra/metrics/go.sum	50
pkg/plugins/codegen/go.sum	136
pkg/plugins/go.sum	380
pkg/plugins/manager/testdata/test-app-with-backend/go.sum	235
pkg/storage/unified/apistore/go.sum	491
pkg/storage/unified/resource/kv/go.sum	115
pkg/storage/unified/resourceclient/go.sum	141
pkg/storage/unified/resourcepb/go.sum	18
pkg/util/sqlite/go.sum	50
scripts/go-workspace/go.sum	2
scripts/modowners/go.sum	2
yarn.lock	3,253

Appendix D — CVE Inventory

The full CVE inventory contains 154 advisories across 9 distinct packages. Severity is reported as UNKNOWN for all 154 because the OSV feed did not return a CVSS-severity band. Fix availability is false for every advisory; fixed version is not applicable; remediation class is no_fixed_release for every advisory. The dominant affected package is `github.com/grafana/grafana` (the repo's own module path); the second-largest cluster is `github.com/nats-io/nats-server v2.14.6`.

Table D.1 — CVE records (top 18 of 154 rows)

ID	Severity	Package	Ecosystem	Version	Fix available	Fixed version	Remediation class
GHSA-3f24-pcvm-5jqc	UNKNOWN	github.com/nats-io/nats-server	go	v2.14.6	false	n/a	no_fixed_release
GHSA-3jq7-8ph8-63xm	UNKNOWN	github.com/grafana/grafana	go	0.0.0	false	n/a	no_fixed_release
GHSA-3p62-42x7-gxg5	UNKNOWN	github.com/grafana/grafana	go	0.0.0	false	n/a	no_fixed_release
GHSA-3w66-95m3-8jxg	UNKNOWN	github.com/grafana/grafana	go	0.0.0	false	n/a	no_fixed_release
GHSA-46m5-8hpj-p5p5	UNKNOWN	github.com/grafana/grafana	go	0.0.0	false	n/a	no_fixed_release
GHSA-4724-7jwc-3fpw	UNKNOWN	github.com/grafana/grafana	go	0.0.0	false	n/a	no_fixed_release
GHSA-4pwp-cx67-5cpx	UNKNOWN	github.com/grafana/grafana	go	0.0.0	false	n/a	no_fixed_release
GHSA-52jh-2xxh-pwh6	UNKNOWN	github.com/nats-io/nats-server	go	v2.14.6	false	n/a	no_fixed_release
GHSA-55h8-8g96-x4hj	UNKNOWN	github.com/nats-io/nats-server	go	v2.14.6	false	n/a	no_fixed_release
GHSA-66c4-2g2v-54qw	UNKNOWN	github.com/grafana/grafana	go	0.0.0	false	n/a	no_fixed_release
GHSA-69j6-29vr-p3j9	UNKNOWN	github.com/grafana/grafana	go	0.0.0	false	n/a	no_fixed_release
GHSA-6wh2-8hw7-jw94	UNKNOWN	github.com/grafana/grafana	go	0.0.0	false	n/a	no_fixed_release
GHSA-7g92-g4vh-hp84	UNKNOWN	github.com/grafana/grafana	go	0.0.0	false	n/a	no_fixed_release
GHSA-7m2x-qhrq-rp8h	UNKNOWN	github.com/grafana/grafana	go	0.0.0	false	n/a	no_fixed_release
GHSA-7phr-6cc9-4m5q	UNKNOWN	github.com/grafana/grafana	go	0.0.0	false	n/a	no_fixed_release

ID	Severity	Package	Ecosystem	Version	Fix available	Fixed version	Remediation class
GHSA-8r68-gvr4-jh7j	UNKNOWN	github.com/nats-io/nats-server	go	v2.14.6	false	n/a	no_fixed_release
GHSA-9493-h4f5-633x	UNKNOWN	github.com/grafana/grafana	go	0.0.0	false	n/a	no_fixed_release
GHSA-9983-vrx2-fg9c	UNKNOWN	github.com/nats-io/nats-server	go	v2.14.6	false	n/a	no_fixed_release

The full 154-row inventory is reproduced in the workbook sheet CVEs. The buyer's security team should re-query each advisory against the NVD to obtain the CVSS-severity rating, because the OSV feed's UNKNOWN rating is itself a coverage gap. The 19 unresolved packages should be cross-referenced against the seller's lockfile inventory to identify which advisories apply to dependencies that are actually loaded at runtime.

Appendix E — License Findings Inventory

E.1 Per-Package License Findings (top 18 of 5,497 rows)

The full per-package license inventory contains 5,497 rows. The representative sample below covers the highest-risk viral and restrictive licenses (AGPL-3.0, AGPL-3.0-only, GPL v3, MPL-2.0) and the dominant permissive licenses (Apache-2.0, MIT). The full inventory is reproduced in the workbook sheet License Contamination.

Table E.1 — Per-package license findings (top 18 of 5,497 rows)

Package name	Detected license	Viral	Restrictive	Confidence	Source file
(repo-level)	AGPL-3.0	Yes	Yes	0.8	LICENSE
(repo-level)	AGPL-3.0	Yes	Yes	0.8	packages/grafana-ol11y-ds-frontend/LICENSE_AGPL
(repo-level)	AGPL-3.0	Yes	Yes	0.8	packages/grafana-sql/LICENSE_AGPL
(repo-level)	AGPL-3.0	Yes	Yes	0.8	packaging/msi/resources/LICENSE.md
(repo-level)	AGPL-3.0	Yes	Yes	0.8	packaging/msi/resources/LICENSE.rtf
@grafana/ol11y-ds-frontend	AGPL-3.0-only	Yes	Yes	0.7	package.json
@grafana/prometheus	AGPL-3.0-only	Yes	Yes	0.7	package.json
@grafana/prometheus	AGPL-3.0-only	Yes	Yes	0.7	public/app/plugins/datasource/cloudwatch/package.json
@grafana/sql	AGPL-3.0-only	Yes	Yes	0.7	package.json
envtpl	GPL v3	Yes	Yes	0.7	devenv/docker/blocks/collected/requirements.txt
@axe-core/playwright	MPL-2.0	Yes	No	0.7	package.json
axe-core	MPL-2.0	Yes	No	0.7	package.json
(repo-level)	Apache-2.0	No	No	0.8	packages/grafana-alerting/LICENSE_APACHE2
(repo-level)	Apache-2.0	No	No	0.8	packages/grafana-api-clients/LICENSE_APACHE2
(repo-level)	Apache-2.0	No	No	0.8	packages/grafana-data/LICENSE_APACHE2
(repo-level)	Apache-2.0	No	No	0.8	packages/grafana-e2e-selectors/LICENSE_APACHE2

Package name	Detected license	Viral	Restrictive	Confidence	Source file
(repo-level)	Apache-2.0	No	No	0.8	packages/grafana-eslint-rules/LICENSE_APACHE2
(repo-level)	Apache-2.0	No	No	0.8	packages/grafana-flamegraph/LICENSE_APACHE2

E.2 License Clause Findings (48 rows)

License clause findings identify attribution, warranty_disclaimer, and patent_grant clauses across 48 license files. Each clause is paired with its severity and matched-package count; the matched-package count is 0 entries in every case because the clause-level analysis is performed at the license-file level rather than the package level.

Table E.2 — License clause findings (top 14 of 48 rows)

License file	Clause type	Severity	Matched packages	Clause text
packages/grafana-alerting/LICENSE_APACHE2	attribution	attribution	0	any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form...
packages/grafana-api-clients/LICENSE_APACHE2	attribution	attribution	0	any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form...
packages/grafana-data/LICENSE_APACHE2	attribution	attribution	0	any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form...
packages/grafana-e2e-selectors/LICENSE_APACHE2	attribution	attribution	0	any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form...
packages/grafana-eslint-rules/LICENSE_APACHE2	attribution	attribution	0	any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form...
packages/grafana-flamegraph/LICENSE_APACHE2	attribution	attribution	0	any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form...
packages/grafana-i18n/LICENSE_APACHE2	attribution	attribution	0	any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form...

License file	Clause type	Severity	Matched packages	Clause text
packages/grafana-openapi/LICENSE_APACHE2	attribution	attribution	0	any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form...
packages/grafana-plugin-compat/LICENSE_APACHE2	attribution	attribution	0	any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form...
packages/grafana-runtime/LICENSE_APACHE2	attribution	attribution	0	any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form...
packages/grafana-schema/LICENSE_APACHE2	attribution	attribution	0	any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form...
packages/grafana-test-utils/LICENSE_APACHE2	attribution	attribution	0	any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form...
packages/grafana-ui/LICENSE_APACHE2	attribution	attribution	0	any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form...
pkg/build/wire/LICENSE	attribution	attribution	0	any Derivative Works that You distribute, all copyright, patent, trademark, and attribution notices from the Source form...

The 48 clause findings indicate that the seller's Apache-2.0 licensed packages carry the standard attribution clause, which is permissive (not viral). The AGPL-3.0 clause findings (warranty_disclaimer, patent_grant) are noted separately and should be reviewed against the buyer's copyleft-exposure analysis.



Appendix F — Complexity, Duplication & SQALE Detail

F.1 Complexity Hotspot Symbols (top 16 of 57,667 rows)

Table F.1 — Complexity hotspot symbols

Name	Filepath	Cycl o.	Cog n.	Maint. idx	Max nest	Para m count	Comp osite risk
Plot	public/vendor/flot/jquery.flot.js	473	1,683	0	n/r	n/r	0.95
updateSchema	public/app/features/dashboard/state/DashboardMigrator.ts	138	210	0	n/r	n/r	0.90
jsonDataToMetaJ SONData	apps/plugins/pkg/app/meta/converte r.go	134	138	0	n/r	n/r	0.9125
InitializeForTest	pkg/server/bootstrap/wire/wire_gen. go	130	129	0	n/r	n/r	0.8575
Initialize	pkg/server/bootstrap/wire/wire_gen. go	130	129	0	n/r	n/r	0.87
TestRouteGetRul eStatuses	pkg/services/ngalert/api/api_promet heus_test.go	121	186	0	n/r	n/r	0.9125
bytes2Value	pkg/util/xorm/session_convert.go	121	558	0	n/r	n/r	0.90
slice2Bean	pkg/util/xorm/session.go	120	455	0	n/r	n/r	0.90
getNavTitle	public/app/core/utils/navBarItem- translations.ts	109	109	10.7	n/r	n/r	0.8911
createGrafDir	pkg/tests/testinfra/testinfra.go	102	109	0	n/r	n/r	0.9375
authorize	pkg/services/ngalert/api/authorizati on.go	90	84	0	n/r	n/r	0.90
process	pkg/registry/apis/provisioning/contr oller/repository.go	88	134	0	n/r	n/r	0.90
graphToTimeseri esOptions	public/app/plugins/panel/timeseries/ migrations.ts	80	307	2.05	n/r	n/r	0.9084
readDashboardIte r	pkg/services/store/kind/dashboard/d ashboard.go	76	237	14.82	n/r	n/r	0.9329
getStatementPosi tion	public/app/plugins/datasource/cloud watch/language/cloudwatch-logs- sql/completion/statementPosition.ts	73	103	10.96	n/r	n/r	0.8906
buildUpdates	pkg/util/xorm/statement.go	69	623	16.96	n/r	n/r	0.8661

F.2 Duplication Groups (top 18 of 18,406 rows)

Duplication groups total 18,406 across the codebase. Each group is identified by its block-start line, block length, and occurrence count. The representative sample below covers common duplication patterns; the full inventory is reproduced in the workbook sheet Complex Symbols.

Table F.2 — Duplication groups (top 18 of 18,406 rows)

Block start line	Block length (lines)	Occurrences
1	10	2
10	10	2
100	10	2
1,009	10	3
101	10	3
1,017	10	3
102	10	2
104	10	2
104	10	6
105	10	6
106	10	2
1,063	10	2
1,077	10	4
1,077	10	2
108	10	2
109	10	2
11	10	2
110	10	2

Block start line is the 1-based line at which the duplicated symbol/module block begins in its file; block length is that block's span and occurrences is how many copies were found.

F.3 SQALE Debt Modules (top 20 of 16,658 rows)

SQALE debt modules total 16,658. The representative sample below covers modules with grade A (no remediation effort required). The full inventory is reproduced in the workbook sheet Complex Symbols.

Table F.3 — SQALE debt modules

Base lines	Debt ratio	Module	Remediation effort	SQALE grade
1	0	e2e-playwright/test-plugins/grafana-extensiontest-app/components/ActionButton/index.ts	0	A
1	0	e2e-playwright/test-plugins/grafana-extensiontest-app/components/App/index.tsx	0	A
1	0	e2e-playwright/test-plugins/grafana-extensiontest-app/components/QueryModal/index.ts	0	A

Base lines	Debt ratio	Module	Remediation effort	SQALE grade
1	0	e2e-playwright/test-plugins/grafana-extensiontest-app/plugins/grafana-extensionexample1-app/components/App/index.tsx	0	A
1	0	e2e-playwright/test-plugins/grafana-extensiontest-app/plugins/grafana-extensionexample2-app/components/App/index.tsx	0	A
1	0	grafana-mixin/scripts/common.sh	0	A
1	0	packages/grafana-data/src/types/slider.ts	0	A
1	0	packages/grafana-e2e-selectors/src/selectors/constants.ts	0	A
1	0	packages/grafana-e2e-selectors/src/types/index.ts	0	A
1	0	packages/grafana-plugin-configs/constants.ts	0	A
1	0	packages/grafana-plugin-configs/jest/mocks/images.ts	0	A
1	0	packages/grafana-ui/src/components/Forms/types.ts	0	A
1	0	packages/grafana-ui/src/components/SecretInput/index.tsx	0	A
1	0	packages/grafana-ui/src/components/SecretTextArea/index.tsx	0	A
1	0	packages/grafana-ui/src/types/interactiveTable.ts	0	A
1	0	packages/grafana-ui/src/types/orientation.ts	0	A
1	0	packages/grafana-ui/src/types/select.ts	0	A
1	0	packages/grafana-ui/src/types/size.ts	0	A
1	0	pkg/plugins/pluginassets/testdata/module-hash-no-manifest-txt/module.js	0	A
1	0	pkg/plugins/pluginassets/testdata/module-hash-no-module-js/something.js	0	A



Appendix G — Debt Marker Inventory

The full debt-marker inventory contains 883 rows. The representative sample below covers the 16 highest-severity markers; the full inventory is reproduced in the workbook sheet Debt Markers. Markers are recorded with file path, line number, marker type, severity, critical-path placement, and marker text.

Table G.1 — Debt markers (top 16 of 883 rows)

Filepath	Line	Marker	Severity	Critical path	Text
eslint.config.js	40	fixme	high	No	// [FIXME] add comment about this applying everywhere
eslint.config.js	624	fixme	high	No	// FIXME: Remove once all enterprise issues are fixed -
eslint.config.js	638	fixme	high	No	// FIXME: Remove once all enterprise issues are fixed -
eslint.config.js	658	fixme	high	No	// FIXME: Remove once all enterprise issues are fixed -
eslint.config.js	683	fixme	high	No	// FIXME: Remove once all enterprise issues are fixed -
packages/grafana-api-clients/src/clients/rtkq/dashboard/v2/endpoints.gen.ts	1,073	fixme	high	No	/** Link type. Accepted values are dashboards (to refer to another dashboard) and link...
packages/grafana-api-clients/src/clients/rtkq/dashboard/v2beta1/endpoints.gen.ts	1,617	fixme	high	No	/** Link type. Accepted values are dashboards (to refer to another dashboard)...
packages/grafana-api-clients/src/clients/rtkq/provisioning/v0alpha1/endpoints.gen.ts	1,710	fixme	high	No	/** Paths to be deleted. Examples: dashboard.json (file) ...
packages/grafana-api-clients/src/clients/rtkq/provisioning/v0alpha1/endpoints.gen.ts	1,734	fixme	high	No	/** Paths to be deleted. Examples ...
packages/grafana-api-clients/src/clients/rtkq/provisioning/v0alpha1/endpoints.gen.ts	1,762	fixme	high	No	/** FIXME: we should validate this in admission hooks Target branch for export (only git) */
packages/grafana-api-clients/src/clients/rtkq/provisioning/v0alpha1/endpoints.gen.ts	1,770	fixme	high	No	/** FIXME: we should validate this in admission hooks Prefix in target file system */
packages/grafana-schema/src/schema/dashboard/v2/types.spec.gen.ts	1,586	fixme	high	No	// FIXME: The type is generated as `type: DashboardLinkType   dashboardLinkType.Link;`...
packages/grafana-schema/src/schema/dashboard/v2alpha1/types.spec.gen.ts	1,050	fixme	high	No	// FIXME: The type is generated as `type: DashboardLinkType   dashboardLinkType.Link;`...

Filepath	Line	Marker	Severity	Critical path	Text
packages/grafana-schema/src/schema/dashboard/v2beta1/types.spec.gen.ts	1,578	fixme	high	No	// FIXME: The type is generated as `type: DashboardLinkType   dashboardLinkType.Link;`...
packages/grafana-test-utils/src/types/browse-dashboards.ts	1	fixme	high	No	// FIXME: This file is a duplication of types within the core code
packages/grafana-ui/src/components/Forms/commonStyles.ts	39	hack	high	No	/* Welcome to 2005. This is a HACK to get rid of Chromes default autofill styling */

The `eslint.config.js` cluster of five `FIXMEs` (lines 40, 624, 638, 658, 683) is the highest-concentration debt pattern in the codebase. Four of the five read 'FIXME: Remove once all enterprise issues are fixed' — this pattern indicates a known outstanding clean-up tied to the open-source / enterprise boundary that the seller has deferred. The buyer's counsel should require disclosure of the specific 'enterprise issues' referenced.

Appendix H — Attack Surface Candidate Endpoints

The full attack-surface inventory contains 118 candidate entry points. The representative sample below covers application_entry (medium risk, untested) and candidate (low risk, mixed test status) endpoints. The full inventory is reproduced in the workbook sheet Attack Surface.

Table H.1 — Candidate entry points (top 14 of 118 rows)

Symbol name	Filepath	Line	Endpoint type	Exposure	Framework	Risk level	Test status
murmurhash3_32_gc	packages/grafana-flamegraph/src/FlameGraph/murmur3.ts	21	application_entry	application	unknown	medium	untested
defineThemes	packages/grafana-ui/src/components/Monaco/theme.ts	31	application_entry	application	unknown	medium	untested
resetSelectStyles	packages/grafana-ui/src/components/Select/resetSelectStyles.ts	6	application_entry	application	unknown	medium	untested
flatten	public/app/core/utils/flatten.ts	4	application_entry	application	unknown	medium	untested
requestAnimationFrame	public/app/features/explore/TraceView/components/utils/test/requestAnimationFrame.ts	17	application_entry	application	unknown	medium	untested
cancelAnimationFrame	public/app/features/explore/TraceView/components/utils/test/requestAnimationFrame.ts	21	application_entry	application	unknown	medium	untested
useMigrations	public/app/plugins/datasource/azurmonitor/components/LogsQueryEditor/useMigrations.ts	43	application_entry	application	unknown	medium	untested
createMockDataSource	public/app/plugins/datasource/azurmonitor/mocks/datasource.ts	27	application_entry	application	unknown	medium	untested
createMockPanelData	public/app/plugins/datasource/azurmonitor/mocks/panelData.ts	7	application_entry	application	unknown	medium	untested
createMockQuery	public/app/plugins/datasource/azurmonitor/mocks/query.ts	4	application_entry	application	unknown	medium	untested
messageFromError	public/app/plugins/datasource/azurmonitor/utils/messageFromError.ts	13	application_entry	application	unknown	medium	untested
migrateAnnotation	public/app/plugins/datasource/azurmonitor/utils/migrateAnnotation.ts	10	application_entry	application	unknown	medium	untested
useLastError	public/app/plugins/datasource/azurmonitor/utils/useLastError.ts	9	application_entry	application	unknown	medium	untested

Symbol name	Filepath	Line	Endpoint type	Exposure	Framework	Risk level	Test status
migrateAnnotation	packages/grafana-sql/src/utils/migration.ts	6	application_entry	application	unknown	medium	untested

External reachability could not be established for 117 of the 118 candidates because framework semantics were unresolved. 95 candidates originate from application_entry detection. The candidate exposure score of 0.1047 is an upper-bound signal for review prioritisation, not a confirmed vulnerability rate.

© MTD Services

Appendix I — Key-Person & Knowledge Loss Vulnerability Detail

I.1 Key-Person Risk Rows (top 14 of 3,217 rows)

Table I.1 — Key-person risk detail

Author name	Author email	Risk score	Total commits	Departure impact
ryantxu@gmail.com	ryantxu@gmail.com	0.26468	234,722	Low
ashley.harrison@grafana.com	ashley.harrison@grafana.com	0.216071	131,354	Low
joshhunt@users.noreply.github.com	joshhunt@users.noreply.github.com	0.103575	63,357	Low
torkel@grafana.com	torkel@grafana.com	0.0803188	90,155	Low
stephanie.hingtgen@grafana.com	stephanie.hingtgen@grafana.com	0.0686434	40,405	Low
hugo.haggmark@gmail.com	hugo.haggmark@gmail.com	0.0615704	65,580	Low
29139614+renovate[bot]@users.noreply.github.com	29139614+renovate[bot]@users.noreply.github.com	0.0612221	11,923	Low
roberto.jimenez@grafana.com	roberto.jimenez@grafana.com	0.0528524	132,108	Low
macabu@users.noreply.github.com	macabu@users.noreply.github.com	0.050841	31,702	Low
leoniya@gmail.com	leoniya@gmail.com	0.0498112	48,560	Low
45561153+kaydelaney@users.noreply.github.com	45561153+kaydelaney@users.noreply.github.com	0.0477866	28,972	Low
marcus.efraimsson@gmail.com	marcus.efraimsson@gmail.com	0.0463529	26,936	Low
academo@users.noreply.github.com	academo@users.noreply.github.com	0.0456318	7,270	Low
laura.fernandez@grafana.com	laura.fernandez@grafana.com	0.041486	11,503	Low

I.2 Module Bus-Factor Rows (top 14 of 2,449 rows)

Table I.2 — Module bus-factor detail

Module path	Bus factor	Total files
pkg/setting	22	54
pkg/api	12	96
_unassigned	9	6,605
grafana-data/src/types	9	58

Module path	Bus factor	Total files
pkg/services/sqlstore	9	21
public/app/types	9	26
pkg/api/dtos	8	18
grafana-data/src/utlis	7	51
pkg/registry/backgroundsvcs	7	1
pkg/server	7	29
pkg/services/sqlstore/migrations	7	41
pkg/tests/testinfra	7	2
pkg/util	7	33
public/app/core/utlis	7	53

I.3 Knowledge Loss Vulnerability Rows (top 14 of 3,217 rows)

Table I.3 — Knowledge loss vulnerability detail

Author name	Author email	Tenure days	Days since last commit	Retention risk	Blast radius at risk
undeflnd	10127682+undeflnd@users.noreply.github.com	1,021	0	Critical	19
Galen Kistler	109082771+gtk-grafana@users.noreply.github.com	1,534	0	Critical	68
Fayzal Ghantiwala	114010985+fayzal-g@users.noreply.github.com	896	55	Critical	0
volcanonoodle	114113189+volcanonoodle@users.noreply.github.com	1,063	2	Critical	72
Liza Detrick	114438185+L2D2Grafana@users.noreply.github.com	883	7	Critical	0
Shubham Nainwal	118589955+Shubham19032004@users.noreply.github.com	491	93	Critical	0
grafana-delivery-bot[bot]	132647405+grafana-delivery-bot[bot]@users.noreply.github.com	1,212	150	Critical	0
Fabrizio	135109076+fabrizio-grafana@users.noreply.github.com	1,198	1	Critical	42

Author name	Author email	Tenure days	Days since last commit	Retention risk	Blast radius at risk
Lucy Chen	140550297+lucychen-grafana@users.noreply.github.com	1,154	21	Critical	0
Tobias Skarhed	1438972+tskarhed@users.noreply.github.com	2,455	8	Critical	30
Marc M.	146180665+grafakus@users.noreply.github.com	716	0	Critical	121
alerting-team[bot]	158350966+alerting-team[bot]@users.noreply.github.com	591	0	Critical	0
Adam Yeats	16296989+adamyeads@users.noreply.github.com	1,186	3	Critical	15
Sofia Papagiannaki	1632407+papagian@users.noreply.github.com	1,820	0	Critical	246

Appendix J — Maintenance, IaC & CI/CD Detail

J.1 Maintenance Assets (none recorded)

No maintenance asset rows are recorded in this scan. The asset-staleness scanner produced zero rows, which is why the maintenance pillar is demoted to UNVERIFIED. The buyer should commission an independent asset-staleness assessment as part of pre-signing diligence.

J.2 IaC Findings (full 1 row)

Table J.1 — IaC findings

Rule ID	Title	Severity	File	Line	Remediation
IAC-DOCKER-ROOT	Container runs as root	Medium	Dockerfile	403	Add a dedicated non-root user and USER directive in every stage.

J.3 CI Files (top 20 of 98 rows)

Table J.2 — CI files

CI file path
/content/grafana/.github/workflows/actionlint.yml
/content/grafana/.github/workflows/add-to-whats-new.yml
/content/grafana/.github/workflows/alerting-swagger-gen.yml
/content/grafana/.github/workflows/alerting-update-module.yml
/content/grafana/.github/workflows/analytics-events-report.yml
/content/grafana/.github/workflows/auto-milestone.yml
/content/grafana/.github/workflows/backend-code-checks.yml
/content/grafana/.github/workflows/backend-unit-tests.yml
/content/grafana/.github/workflows/backport-trigger.yml
/content/grafana/.github/workflows/backport-workflow.yml
/content/grafana/.github/workflows/build-docker-variants.yml
/content/grafana/.github/workflows/build-go-matrix.yml
/content/grafana/.github/workflows/bump-version.yml
/content/grafana/.github/workflows/changelog.yml
/content/grafana/.github/workflows/check-frontend-test-coverage.yml
/content/grafana/.github/workflows/cleanup-branches.yml
/content/grafana/.github/workflows/codeowners-validator.yml
/content/grafana/.github/workflows/commands.yml

CI file path`/content/grafana/.github/workflows/community-release.yml``/content/grafana/.github/workflows/create-next-release-branch.yml`**J.4 Coverage Artifacts (none)**

No coverage artifacts are recorded in this scan. This is consistent with the `reported_coverage_pct` = not quantified figure in Section 11: the CI surface does not publish a coverage report that the scanner could consume.

© MTD Services

Appendix K — Privacy & Secrets Detail

K.1 Privacy Findings (full 1 row)

Table K.1 — Privacy findings

Rule ID	Category	Title	Severity	File	Line	Remediation
PRIV-PLAINTEXT-CRED	Plaintext credential	Plaintext credential material in committed config	Medium	.github/workflows/relyance-scan.yml	26	Move to a secret store / environment injection and rotate the committed value.

K.2 Secret Candidates (top 14 of 427 rows)

Table K.2 — Secret candidates

Kind	File	Line	Confidence	In history	Risk cap
aws_access_key	pkg/tsdb/cloudwatch/models/settings_test.go	202	95	Yes	critical
aws_access_key	pkg/tsdb/cloudwatch/models/settings_test.go	223	95	Yes	critical
aws_access_key	pkg/tsdb/cloudwatch/models/settings_test.go	248	95	Yes	critical
aws_access_key	pkg/tsdb/cloudwatch/models/settings_test.go	112	95	No	critical
aws_access_key	pkg/tsdb/cloudwatch/models/settings_test.go	130	95	No	critical
aws_access_key	pkg/tsdb/cloudwatch/models/settings_test.go	148	95	No	critical
aws_access_key	pkg/tsdb/cloudwatch/models/settings_test.go	166	95	No	critical
aws_access_key	pkg/tsdb/cloudwatch/models/settings_test.go	184	95	No	critical
aws_access_key	pkg/tsdb/cloudwatch/models/settings_test.go	34	95	No	critical

Kind	File	Line	Confidence	In history	Risk cap
aws_access_key	pkg/tsdb/cloudwatch/models/settings_test.go	56	95	No	critical
aws_access_key	pkg/tsdb/cloudwatch/models/settings_test.go	87	95	No	critical
aws_access_key	pkg/tsdb/cloudwatch/models/settings_test.go	102	95	No	critical
aws_access_key	pkg/tsdb/cloudwatch/models/settings_test.go	71	95	No	critical
aws_access_key	pkg/util/uri_sanitise_test.go	29	94	No	critical

Appendix L — AI/ML Inventory

L.1 Model Files (none recorded)

No model-file rows are recorded in this scan. This is consistent with the `bundled_model_files = 0` and `production_model_files = 0` figures in Section 12: the AI/ML surface area is composed of SDK calls and framework imports, not bundled model artifacts. The buyer's AI/ML team should validate that no model is loaded at runtime; if runtime model loading is detected, the model license and training-data provenance must be verified.

© MTD Services

Appendix M — Integrity & Data-Quality Issues

The full 8-row integrity issues inventory is reproduced below. Five warnings are critical_pillar_no_findings (high/critical pillars rendering no item-level findings); three warnings are unverified_pillar (partial or not-assessed pillars). No errors are recorded.

Table M.1 — Integrity issues (full 8 rows)

Tier	Code	Subject	Message
Warn	critical_pillar_no_findings	pillars.coverage	Pillar 'coverage' is high but renders no item-level findings.
Warn	critical_pillar_no_findings	pillars.entanglement	Pillar 'entanglement' is critical but renders no item-level findings.
Warn	critical_pillar_no_findings	pillars.integration	Pillar 'integration' is high but renders no item-level findings.
Warn	critical_pillar_no_findings	pillars.ip_ownership	Pillar 'ip_ownership' is high but renders no item-level findings.
Warn	critical_pillar_no_findings	pillars.test_deficit	Pillar 'test_deficit' is high but renders no item-level findings.
Warn	unverified_pillar	pillars.cve	Pillar 'cve' is partial — conclusions UNVERIFIED.
Warn	unverified_pillar	pillars.maintenance	Pillar 'maintenance' is not_assessed — conclusions UNVERIFIED.
Warn	unverified_pillar	pillars.secrets	Pillar 'secrets' is partial — conclusions UNVERIFIED.

Appendix N — Taint Analysis Summary

N.1 Taint Summary

Table N.1 — Taint summary

Metric	Value
Bounded	false
Total flows	0

N.2 Top Taint Flows

0 flows. The taint pass was not bounded, meaning the analysis ran but did not establish an exhaustive bound on the taint-flow surface. The buyer's security team should treat the zero-flow result as a partial coverage signal rather than as a confirmed absence of exploitable flows.

© MTD Services

Appendix Q — Glossary

Terms are used consistently and never redefined per section, so the buyer and its advisers converge on one shared frame. The glossary below is alphabetically sorted and defines, in plain language, every technical or specialist term appearing in any TDD table column heading. Definitions are consistent with contextual usage.

Table Q.1 — Glossary (alphabetically sorted)

Term	Meaning
AGPL-3.0	GNU Affero General Public License v3.0. A strong copyleft license that extends GPL obligations to network-served software, requiring source disclosure to users interacting with the software over a network.
Apache-2.0	Apache License, Version 2.0. A permissive open-source license allowing use, modification, and distribution with attribution, including an express patent grant.
Assessment state	Five-value trust vocabulary (NOT_ASSESSED, PARTIALLY_ASSESSED, ASSESSED_NO_FINDINGS, ASSESSED_WITH_FINDINGS, ERROR) accompanying each pillar verdict; communicates the level of confidence the underlying evidence supports.
Assessment status	Pillar-level coverage label: assessed, partial, or not_assessed. Only assessed pillars support conclusions; partial / not_assessed pillars are demoted to informational and labelled UNVERIFIED.
Attack surface	Set of code paths reachable from untrusted input. Candidate endpoints are detected by static analysis and risk-scored for review prioritisation, not as confirmed vulnerabilities.
Attribution	License clause requiring preservation of copyright, patent, trademark, and attribution notices in derivative works distributed by the licensee.
Author	Git contributor identity derived from commit metadata. Used in key-person and retention analyses as a contributor-activity signal, not as an employment-status or assignability verdict.
Blast radius at risk	Estimate of the number of modules a given contributor's departure would destabilise, derived from sole-maintainership and tenure signals.
Bus factor	Reciprocal of sole-contributor concentration per module. A low bus factor flags flight risk: fewer engineers must depart before the module becomes unmaintainable.
Bus factor proxy	Aggregate team-level bus-factor signal derived from author-concentration ratios; complements the per-module bus factor.
Cadence per week	Average number of commits per week observed across the analysed history window. A sustained-cadence indicator, not a productivity metric.
Candidate endpoint	Function or symbol identified by static analysis as a potential untrusted-input entry point. Status is a detection signal; reachability is resolved separately.
Candidate exposure score	Upper-bound signal for review prioritisation across candidate endpoints. Not a confirmed vulnerability rate.
CC percentiles	Cyclomatic complexity percentiles (typically P50, P90, P99) computed across all analysed symbols; describe the distribution of structural complexity.
Certificate block	Detected textual block matching the shape of an X.509 certificate or PEM-encoded key material; treated as a secret candidate requiring validation.

Term	Meaning
CI Maturity	Pillar assessing the presence and strictness of continuous-integration pipelines inferred from committed workflow files. Static, not a runtime pass-rate measure.
Classification	Risk-tier label assigned in the consolidated register (Critical Risk, Major Risk, Minor Risk, Acceptable). Drives the conditions in the recommendation.
Cognitive complexity	Software-quality metric estimating the human effort required to understand a function, weighting nesting, recursion, and breaks in linear flow more heavily than cyclomatic complexity.
Cognitive percentiles	Distribution statistics (P50, P90, P99) of cognitive complexity across analysed symbols.
Commit	Atomic change recorded in the Git history. Used as the unit of activity in key-person and team-cadence analyses.
Condition precedent	Closing condition that must be satisfied or waived before signing or before the deal closes. Failure to satisfy blocks the transaction as structured.
Confidence score	Composite figure computed as $20 + 40 \times \text{coverage} + 40 \times \text{risk_signal}$, capped at 20 when coverage is zero, and floored at 60 when the verdict is <code>DO_NOT_ACQUIRE</code> . Communicates the epistemic strength of the recommendation.
Confirmed	Evidence-state label reserved for findings validated by independent corroboration. None of the findings in this report carry this label; absence is named rather than implied.
Contamination chain	Linked set of packages whose licenses propagate obligations to dependent code, sized by transitive reachability from a viral or restrictive source.
Coverage method	Description of the coverage proxy used. In this scan, a static symbol-share proxy weighting test-file symbols by structural value; explicitly not runtime or line / branch coverage.
Coverage ratio	Effective proportion of production-symbol value covered by test-file symbols. Used to size uninsured exposure.
Cross-layer violation	Static dependency that crosses an architectural layer boundary (e.g. presentation calling data). Counted and severity-rated; not a runtime behaviour.
CVE	Common Vulnerabilities and Exposures identifier. Advisory records were refreshed against OSV at scan time; severity is reported as recorded by the advisory source.
Days since last commit	Elapsed days between the latest observed commit for a contributor and the scan date. Used as an activity-decay signal in retention analysis.
Deal-breaker	Pillar finding severe enough to force a <code>DO_NOT_ACQUIRE</code> verdict under the decision model, irrespective of remediation economics.
Debt density	Technical-debt markers per thousand lines of code; normalises marker counts against codebase size.
Debt marker	Explicit in-source annotation indicating known technical debt (e.g. <code>FIXME</code> , <code>TODO</code> , <code>HACK</code> , <code>XXX</code>). Tracked by type, severity, and critical-path placement.
Dependency	Third-party package declared in a manifest. Direct dependencies are explicit; transitive dependencies are resolved via lockfile.
Direct dependency	Package declared in a manifest. Distinguished from transitive dependencies pulled in by the resolver.
Doc Staleness	Pillar measuring the proportion of inventoried documentation files whose last-modified date exceeds the staleness threshold.

Term	Meaning
Duplicated LOC	Lines of code participating in duplicated blocks across the analysed codebase, summed across all duplication groups.
Economic escalation	Decision-model mechanism linking the remediation-cost share of proposed price to escalation tiers (conditions at 5% + \$250K floor; no-go at 25%).
EOL	End-of-life. Technology, runtime, or dependency that has passed its last security or feature update. Reconciled across tech_stack (offline markers) and the eol pillar (endoflife.date runtime verification).
Entanglement score	Aggregate measure of cyclic dependency and cross-layer violation density. Higher scores indicate greater integration friction.
Evidence state	Per-finding honesty label attached to every material finding: Confirmed, Detected-not-verified, Inferred, Partially assessed, Unassessed, Conflicting, or Unsupported.
Finding id	Stable identifier of the form F-<pillar>-<rank> used by the narrative, register, workbook, and ledger to cite one assessed finding.
Framework	Software framework detected by manifest or import patterns (e.g. Huggingface for AI/ML, gin for HTTP routing).
Framework group	Count of distinct framework families detected in the AI/ML scan; communicates breadth of AI/ML integration, not depth.
Git history	Commit log scanned for secret candidates and contributor activity. Path-excluded candidates are named rather than silently ignored.
GPL v3	GNU General Public License v3. A copyleft license requiring derivative works to be distributed under the same license; viral in the contamination sense.
GraphQL	Query-language API specification. Presence or absence detected by static manifest inspection; absence does not imply absence of GraphQL at runtime.
Headline EV	Transaction enterprise value declared in the scan input; the reference against which remediation cost is measured as a percentage.
Health score	Per-pillar 0-100 score. Demoted to 50 for partial / not_assessed pillars so an unfinished scan never reads as a clean bill of health.
High confidence secret	Secret candidate whose detected pattern exceeds the high-confidence threshold; treated as a critical-severity finding requiring validation, not a confirmed exposure.
High regression-risk module	Module identified by the test-deficit pillar as carrying elevated regression risk under refactoring; costed for test investment in the remediation model.
High-value gap	Coverage gap concentrated in a module whose structural risk weight exceeds the high-value threshold; prioritised in the test-investment work stream.
HPU	Hours per unit. Remediation effort per finding within a cost category, saturated by a cap and decay rate under the financial model.
IaC	Infrastructure-as-Code. Committed configuration describing infrastructure (e.g. Dockerfiles, Terraform, GitHub Actions). Findings are committed-text signals, not runtime enforcement.
Indexed files	Count of files parsed and loaded into the code-property graph backing the pillar scanners. Lower than total file count indicates parse failures or path exclusions.
Inferred	Evidence-state label for findings derived by inference from primary signals (e.g. retention risk from contributor activity patterns). Requires validation before negotiation reliance.

Term	Meaning
Integration drag	Post-merge operational friction estimated from remediation hours; expressed as a percentage capped at 80% by the financial model.
Integration risk score	Composite pillar-level score (0-10) reflecting proprietary coupling, schema drift, database coupling, and serialization risk. 10 indicates maximum integration friction.
IP Ownership	Pillar assessing the attribution of file authorship between corporate-domain and external contributors. Attribution ratios are a diligence signal, not legal proof of title.
IP risk score	Composite figure combining external-author concentration, external-blamed-line percentage, and external-owned-file count; ranges 0-1, higher is riskier.
Knowledge loss vulnerability	Per-contributor risk derived from tenure, recent activity, and sole-maintainership; classifies retention risk into low, medium, critical tiers.
Knowledge transfer	Cost category funding the documentation and pairing required to mitigate sole-maintainership in critical modules; sized per unique module, not per at-risk contributor.
License	Pillar assessing per-package detected licenses against viral, restrictive, and unknown classifications; flags contamination exposure for legal review.
Lockfile	Resolver-generated file pinning transitive dependency versions (e.g. go.sum, yarn.lock). Presence indicates deterministic builds; absence flags reproducibility risk.
Maintenance backlog score	Aggregate figure combining neglected-file count, average staleness, and complexity distribution. Zero in this scan because the staleness scanner produced no rows.
Manifest	Author-declared dependency specification (e.g. package.json, go.mod). Distinct from a lockfile, which records resolved versions.
Max cycle length	Module count of the longest detected cyclic dependency. Long cycles indicate deep architectural entanglement and high decoupling effort.
Migration files	Schema-change artifacts indicating database migration discipline. Count communicates migration history depth; absence is a hygiene signal.
Modules in cycles	Count of modules participating in at least one detected cyclic dependency. Communicates the breadth of entanglement, not its depth.
MPL-2.0	Mozilla Public License v2.0. A weak copyleft license applying file-level copyleft to MPL-covered files while permitting combination with proprietary code.
No-go threshold	Remediation cost share of proposed price above which the decision model forces a DO_NOT_ACQUIRE verdict. Set to 25% in this scan.
OpenAPI	OpenAPI Specification for REST APIs. Presence detected by manifest inspection; absence in this scan flags schema-drift exposure.
ORM	Object-Relational Mapping library abstracting SQL access. Absence in this scan is consistent with the high raw-SQL count observed.
Path tier	Classification of the file path containing a secret candidate (e.g. prod, test, dev, vendor). Drives risk-cap assignment under the secrets pillar.
Person-years	Remediation hours divided by 2,080 (annual working hours). Communicates effort in staffing terms for the post-close plan.
Pin ratio	Pinned dependencies divided by direct dependencies. A low ratio flags reproducibility and supply-chain risk; not a contractual commitment.

Term	Meaning
PII endpoint	Endpoint handling personally identifiable information. Counted by privacy scanning of detected endpoint signatures; zero is not a compliance verdict.
Privacy finding	Detection of plaintext-credential material, sensitive logging, or PII handling in committed configuration. Flag-and-inventory basis, not a compliance verdict.
Probability after	Estimated probability of a risk materialising after remediation. Stated only when the Layer-2 risk valuation line is quantified; otherwise marked not quantified.
Probability before	Estimated probability of a risk materialising before remediation. Stated only when the Layer-2 risk valuation line is quantified.
Production model file	AI/ML model artifact shipped to production. Counted by AI/ML scan; zero is favourable in this scan.
Proprietary coupling	Static dependency on a Grafana-proprietary package. Higher counts flag integration friction in a separation or carve-out scenario.
Protocol layer	Network-protocol-level risk indicator (e.g. raw_socket usage for WebSocket handling). Counted for security review, not as a runtime vulnerability.
Raw SQL	SQL string embedded in application code outside an ORM abstraction. Higher counts indicate coupling to a specific SQL dialect and migration risk.
Remediation class	Category applied to a CVE record describing the available remediation path (e.g. no_fixed_release). Drives scheduling of the post-close remediation plan.
Remediation effort	Time required to remediate a finding or a category of findings. SQALE-derived for complexity; HPU-derived for other categories.
Residual expected loss	Expected loss surviving remediation, computed as probability_after x economic_impact_after for quantified risk lines.
Retention risk	Per-contributor classification (low / medium / critical) of the risk that the contributor departs before close and during the transition window.
Risk level	Pillar-level rating: critical, high, medium, low, or informational. Demoted to informational under partial coverage; derived_risk_level preserves the scanner's own view.
Risk reduction value	Aggregate expected loss before remediation minus aggregate residual expected loss; the value the remediation programme is intended to deliver.
Risk signal	Weighted blend of pillar risk into the confidence score. Combined with coverage to produce the 0-100 confidence figure.
Risk valuation	Layer-2 financial translation of a finding into probability x economic impact, producing expected-loss figures before and after remediation.
Saturation cap	Maximum count of findings within a cost category to which full HPU applies; above the cap, the decay HPU is used to prevent runaway cost.
Saturation decay	Hours-per-unit applied to findings above the saturation cap for a given category; reflects diminishing remediation effort per repeated finding.
Schema drift risk	Likelihood that API or storage schema has diverged from a documented contract. Rated high in this scan; reflects absence of OpenAPI and presence of multiple schema versions.
Secret candidate	Pattern match indicating possible secret material. Requires human validation before reliance; high-confidence and history-only candidates are tracked separately.

Term	Meaning
Sensitive log	Log statement detected as handling sensitive data. Zero in this scan is a detection result, not a confirmation of absence.
Serialization risk	Static pattern indicating unsafe deserialization (e.g. <code>dynamic_function</code> call, <code>eval_call</code>). High severity by default; treated as a security review item.
Severity	Per-finding rating: informational, low, medium, high, or critical. Weighted in the risk signal by 0, 1, 2, 3, 4 respectively.
Severity risk weight	Numeric weight applied to a finding's severity when computing the risk signal. Informational 0, low 1, medium 2, high 3, critical 4.
Sole-maintainer module	Module with bus factor of one. Critical sole-maintainer modules drive the knowledge-transfer cost category and the retention condition.
SQALE	Software Quality Assessment based on Lifecycle Expectations. Standardised remediation-effort basis producing per-module hours and a letter grade (A best, E worst).
SQALE grade	Letter grade summarising the SQALE debt ratio. Grade E in this scan signals severe debt relative to codebase size.
Stale document	Documentation file whose last-modified date exceeds the staleness threshold. Counted by <code>doc_staleness</code> scan; ratio communicates documentation drift.
Static symbol-share proxy	Coverage estimation method counting test-file symbols weighted by structural value, in lieu of runtime line or branch coverage. Communicates structural coverage, not executed coverage.
Taint flow	Static data-flow path from an untrusted source to a sensitive sink. Zero flows in this scan; the pass was not bounded and may not be exhaustive.
Tech Stack	Pillar counting detected technologies and their lifecycle status. Structural-detection basis, reconciled with runtime EOL verification.
Technology VaR	Value-at-Risk figure for technology exposure, derived from scenario weighting. Honestly labelled Scenario-Based Technology VaR when produced; a technology-risk model output, not a market-risk measure.
Tenure days	Days between a contributor's first and latest observed commit. A signal of institutional knowledge depth, not of employment tenure.
Test coverage ratio	Per-module ratio of test-file symbol value to production-symbol value. Zero in many high-risk modules is the leading regression-risk indicator.
Test deficit score	Aggregate figure combining module count below threshold and overall test ratio. Higher scores flag greater regression risk under refactoring.
Test ratio	Per-module ratio of test files to source files. A coarse structural signal, not a runtime coverage measure.
Top author share	Largest single contributor's share of commits. Higher values indicate greater concentration risk.
Transitive resolved package	Indirect dependency resolved via a lockfile. Count communicates supply-chain breadth and transitive-advisory exposure.
Unlicensed model file	AI/ML model artifact without a detected license. Zero in this scan is favourable; absence of bundled model files is the underlying cause.
Unpinned dependency	Manifest-declared dependency using a version range rather than an exact version. Flags reproducibility and supply-chain risk.

Term	Meaning
Unreferenced endpoint	Candidate endpoint with no detected inbound edges in the static graph. Communicates potential dead code or undocumented exposure.
Untested candidate endpoint	Candidate endpoint for which no test file is detected. Higher counts flag review backlog in the attack-surface work stream.
Unverified pillar	Pillar whose conclusions are demoted to UNVERIFIED due to partial or absent coverage. Named explicitly in the executive brief.
Value coverage ratio	Aggregate value coverage across all modules; communicates the proportion of high-blast symbols insured by tests.
Viral license	License that propagates its obligations to derivative works (e.g. GPL, AGPL). Triggers contamination-chain analysis and warranty risk in a closed-source acquirer scenario.
Warranty	Seller statement whose breach is an indemnity question rather than a work plan. Distinct from a condition precedent or a price-adjustment lever.
Weighted expectation	Probability-weighted expected loss across enabled scenarios. Honest label Scenario-Based Technology VaR when produced.
WebSocket	Communication protocol enabling full-duplex channels over a single TCP connection. Detected via raw_socket pattern in this scan; flags protocol-layer review items.

Where a term is defined differently in different contexts (e.g. confidence has a technical meaning in the financial model and a colloquial meaning in narrative), the technical meaning is given; colloquial usage is consistent with the technical meaning.